



FACILITY SYSTEMS

System solutions for offices,
conference and training rooms

It's electric.

**BACH
MANN**

Bachmann International

Build on the best connections

Bachmann makes connections. Ensuring that power and data are available right where you need them. In industry, business and the home, in offices and training facilities, on desks and tables at conferences. Bachmann facility and IT systems are flexible enough that you can modify them at any time to suit future power or data management needs. And with Bachmann's up-to-the-minute range of electrical components you can be sure of satisfying even your customers' more unusual electrical and electronics requirements.

One of Bachmann's primary objectives is to deliver innovative products to help our customers achieve long-term success. For this reason we exploit all the possibilities offered by professional engineering and modern process management to develop our standardised and customised systems and products.

Bachmann facility systems

Plug into a world of possibilities

With Bachmann facility systems you can be sure of having access to the best connectors and connections wherever you are in the world. Our systems are configurable with all standard international socket outlets and data connections. Modules can be retrofitted quickly and easily, or even interchanged. In short, when it comes to energy and data management systems that are fit for the future, Bachmann maximises your options.

However, there are two things we insist must feature in each and every product and service we deliver: our high-grade design and our consistent quality.




Desktop connection panels / Fitting in desks




SLIDE 6

Opening and closing by means of a control unit. When the unit is closed, the cut-out in the desk or table is flush with the surface and items can be placed on top of it. Features torque limitation.



CONFERENCE 8


Practical power and data supply. Recessed in the top of the desk or table when not in use. Simply press down with your thumb to open the unit. Features a spring clip, can be closed once cables have been connected.



TOP FRAME 12

TOP FRAME is the new power and data supply solution for conference facilities.

Thanks to the foldaway cover, power and data can be conveniently accessed from any seat around the conference table.



CONI 18

Unrestricted access to power and data supply from the comfort of a desk or table. Integrated into your desk together with connected cables. The integrated brush insert prevents cables jamming.



CONI COVER 24

Elegant access to separate power supply units under the desk or table. Also ideal for retrofitting. Thanks to the integrated brush insert, can even be closed once the devices have been connected.



POWER FRAME 26

For integrated power and data connections to workstations. Versatile application options. The power strip simply clicks into the built-in frame.



POWER FRAME COVER **NEW** 30

The worthy new addition to the POWER FRAME. An elegant and attractive aluminium cover that is fully at home in design-oriented conference and office environments.



TWIST **NEW** 32

Very compact power strip and space-saving cable management. TWIST is so flat that it doesn't impact on anything installed underneath it. red dot product design award winner 2012



ELEVATOR **NEW** 34

Designed for a standard 79 mm hole diameter, ELEVATOR is the compact power package.

Recessed in the top of the desk or table when not in use; simply touch to raise.



LIFT 36

Practical combination of sophisticated design and high-precision mechanics. Recessed in the top of the desk or table when not in use. Simply touch to raise. For docking on all four sides.

Desktop connection panels / Fitting on desks



DESK 1 40

Ideal wherever workstation flexibility is required. Modular design for individual configuration of communication and power supply connections. Fixed or free-standing installation.



DESK 2 50

The new generation of desk with superior design credentials. The modularity for which Bachmann is renowned ensures adaptability to future requirements.

Desktop connection panels / Mounting below desks

STEP 56


For flexible power and data supply at workstations, in partition systems, sill-type trunking, false floors, etc. Consistent modularity means that the possibilities are virtually endless.



Custom modules

CUSTOM MODULE 62

Wherever CUSTOM appears in this catalogue, you can be sure of finding modules which can be interchanged with maximum flexibility. CUSTOM MODULES for data, video and audio connections perfectly adapt Bachmann facility systems to provide a solution that fits individual requirements perfectly.



Media technology

Media Express 92

Plug & play technology for simplicity and efficiency

Media Switch 100

Flexible and reliable thanks to high-quality components

Media Control 106

Simple control of complex processes in media and facility applications



LanLight®, the smart supply system

LanLight® system overview 116

Modular building installation solution offering flexible supply to office workstations

Basic unit and inserts 120

Connecting plates for power and data

Lift cover 122

Modern floor boxes for dry-cleaned floors

Pillars 123

Mobile pillars for power and data distribution in raised and false floors

LanLight®



Consolidation points

CONSOLIDATION POINTS 124

Underfloor distributors for power and data technology



ACCESSORIES, CABLES & CABLE MANAGEMENT 128



SLIDE

Functionality at the touch of a button

SLIDE is opened and closed again at the touch of a button. When the unit opens, the integrated electronics push the cut-out in the desk or table down and underneath its surface. For unrestricted access to power and data supply modules. When the unit is closed, the cut-out in the desk or table is flush with the surface and items can be placed on top of it, making for a very practical solution.

Electronically controlled torque limitation protects users and cables. There is no risk of fingers or power supply cables getting trapped or crushed. SLIDE is available in various configurations and power strips are easily interchangeable.

SLIDE – the unobtrusive way of making functions available when they are needed. Simply at the touch of a button.

The benefits at a glance

- Opens and closes at the touch of a button
- Loadable when closed
- Fully integrated into the top of your desk or table
- Torque limitation ensures safety
- Power strip can be interchanged easily


Art. no. | Version

SLIDE housing**Black**

- 913.000
- Module for mounting in desk or table systems
 - Complete kit incl. motion mechanism, control electronics and fixing materials
 - Incl. built-in frame for 2 power strips (see page 16)
 - Incl. stainless steel button with 2.0 m control cable and connecting plug to control the SLIDE
 - Suitable for installation in desk or table tops (thickness must be adapted to 8 mm)
 - Incl. cut-out drawing for preparation of desk or table top
 - Dimensions (L x W x H): approx. 725 x 340,5 x 70,3 mm

SLIDE housing illuminated**Black**

- 913.005
- Built-in frame for fitting in desk or table systems
 - Complete kit incl. motion mechanism, control electronics and fixing materials
 - With 2 blue LED strip lights that light up when open
 - Incl. built-in frame for 2 power strips (see page 16)
 - Including stainless steel button with 2.0 m control cable and connector plug to control the SLIDE
 - Suitable for installation in desk or table tops (thickness must be adapted to 8 mm)
 - Incl. cut-out drawing for preparation of desk or table top
 - Dimensions (L x W x H): approx. 725 x 340,5 x 70,3 mm



You will find power strips suitable for Slide, Conference and Top Frame on page 16/17



SLIDE – a user-friendly solution even at installation stage.

All set for quick fitting

The SLIDE module screws onto the underside of your desk or table top. The screw fixtures are designed for tops up to 20 mm thick. If the thickness is more than 20 mm you will need to rout the area around the SLIDE module housing down to 20 mm. The dimensions of the sliding panel in the desk or table top are approx. 302.5 x 236 mm (L x W). The built-in frame for the socket outlets is attached to the SLIDE module using the screws included in the scope of supply. The power strips (short version) can also be attached to this built-in frame and interchanged if required. Please refer to page 16 for power strips.

Sealed cables can also be supplied

The SLIDE module's moving carriage is opened and closed using a pushbutton. The carriage itself has an "elongated slot" so that cables can be routed even when the unit is closed. Customers can choose whether to also include this slot in the desk or table top in the design of the cut-out.

Electronics for safety

As soon as a resistance is felt by the moving "carriage", the electronics will bring it to a halt. This prevents fingers and cables getting trapped, avoiding possible injuries or damage.

CONFERENCE offers individual access to power and data supplies in a most discreet and elegant manner. On conference tables, in training centres and on high-grade workstations.

When not in use, CONFERENCE is hidden in the top of the desk or table. When you need power or data, press with your thumb to release the magnetic catch and the opening flap swings up. Once you have connected your notebook, projector, microphone, etc. the flap can be closed again. The cables are accommodated by the narrow closing flap opposite - nothing gets squashed and the elegant appearance of the desk or table is retained.

CONFERENCE built-in frames can be supplied for both retrofitting and for installing flush with the desk or table top. Where installed under a desk or table, the opening and closing flaps are flush with the desk or table top. As we can supply flaps on request in virtually every coating imaginable and even ready for veneer finishing, CONFERENCE is able to meet the most stringent of requirements in terms of design elegance and configuration harmony.

The configuration of CONFERENCE data connections can be freely selected. Power strips can also be interchanged quickly and at any time, without the need for tools. Maximum functionality and top-end design can therefore be adapted to advancements in communication technology for many years to come.

**The benefits
at a glance**

- Integrated into the top of your desk or table
- Simply press with your thumb to open
- Flap can be closed with cables connected
- For retrofitting and flush mounting
- Can be installed flush with the top of the desk or table
- Suitable for veneer finishing
- Configuration can be freely selected (see custom modules from page 62)
- Complete power strip can be quickly interchanged




Simply press with your thumb to open CONFERENCE. Thanks to its flexible closing flap, the unit can even be closed once devices have been plugged in without crushing the cables.



CONFERENCE

Setting a design standard

CONFERENCE – as variable as your requirements.




Simple built-in frame fitting

The built-in frame is very easy to install - only standard tools are required. Simply make a rectangular cut-out in the top of your desk or table.

Frameless

Conference under-table mounting frames (frameless) are fitted from the underside of the desk or table top. Thus only the pivoting flaps are visible on the desk or table top. The necessary drawings containing the special details of the table cut-out are supplied with the or can be downloaded from www.bachmann.com. If required, the flaps can be removed from the frame by means of the integrated bayonet catch. You can also custom match the flaps to the finish of your desk or table top by gluing on a suitable veneer (this is not done ex works).

The dimensions of the cut-out are included in the frame packaging materials, are available by e-mail or can be downloaded from www.bachmann.com



Power strip simply clicks into place

The power strip is not supplied with the built-in frame and must be ordered separately.

It simply clicks into the built-in frame (tools are not required).

Since the power strip can be interchanged at any time, the user is guaranteed long-term flexibility and adaptability to future requirements.

CONFERENCE with frame

- Chamfered side panels, can be flush-mounted on desk or table surface
- Incl. quick-change mechanism for swapping power strips
- Incl. fixing claws and fitting instructions with cut-out dimensions

Art. no. | Version

CONFERENCE built-in frame, long		Moonstone metallic
338.0200	· Outer dimensions: approx. 466.1 x 182.4 mm, built-in dimensions: approx. 450.1 x 166.4 mm · Built-in depth: 110 mm	


CONFERENCE built-in frame, short		Moonstone metallic
338.0201	· Outer dimensions: approx. 284.6 x 182.4 mm, built-in dimensions: approx. 268.6 x 166.4 mm · Built-in depth: 110 mm	

CONFERENCE built-in frame, long		RAL9006,silver-grey
338.0221	· Outer dimensions: approx. 466.1 x 182.4 mm, built-in dimensions: approx. 450.1 x 166.4 mm · Built-in depth: 110 mm	

CONFERENCE built-in frame, short		RAL9006,silver-grey
338.0219	· Outer dimensions: approx. 284.6 x 182.4 mm, built-in dimensions: approx. 268.6 x 166.4 mm · Built-in depth: 110 mm	

CONFERENCE built-in frame, long		Chrome effect paint finish
338.0212	· Outer dimensions: approx. 466.1 x 182.4 mm, built-in dimensions: approx. 450.1 x 166.4 mm · Built-in depth: 110 mm	

CONFERENCE built-in frame, short		Chrome effect paint finish
338.0210	· Outer dimensions: approx. 284.6 x 182.4 mm, built-in dimensions: approx. 268.6 x 166.4 mm · Built-in depth: 110 mm	



CONFERENCE frameless

Art. no. | Version

CONFERENCE built-in frame for below table, long		RAL9006,silver-grey
338.0230	· Dimensions (visible surface): approx. 442.5 x 119 mm · Built-in depth: 107 mm	

CONFERENCE built-in frame for below table, short		RAL9006,silver-grey
338.0231	· Dimensions (visible surface): approx. 261.5 x 119 mm · Built-in depth: 107 mm	



You will find power strips suitable for Slide, Conference and Top Frame on page 16/17

TOP FRAME is the new power and data supply solution for conference facilities. Thanks to the foldaway cover, power and data can be conveniently accessed from any seat around the conference table. The balanced geometry of TOP FRAME fits elegantly into the desk or table top, making it possible to finish the surface with a high-quality veneer.

TOP FRAME is also elegantly simple to open:
just press lightly with a finger and it opens and closes again - silently.

With its all-round frame, Top Frame is also suitable for retrofitting. The power strips are of course quick to exchange and can be equipped with Bachmann's flexible custom modules.

TOP FRAME is available in various versions:

EV1 anodised aluminium or powder-coated in RAL 9006. Other surface finishes are available on request. A veneer of up to 0.6 mm can also be glued to the flap without the dimensions of the cut-out having to be changed.

The power strip clips into the installation frame without tools. There is a short version with 4 modules and a long version with 8 modules to suit both TOP FRAME solutions.

**The benefits
at a glance**

- Access to power supply and data from any seat
- Silent opening
- Integrated into the top of your desk or table
- Can be installed flush with the top of the desk or table
- Version with surround frame suitable for retrofitting
- Suitable for veneer finishing
- Configuration can be freely selected
- Complete power strip can be quickly interchanged



TOP FRAME opens silently and can also be conveniently operated from the seat opposite.



TOP FRAME

Perfect elegance

TOP FRAME frameless

- Includes fixing accessories

Art. no. | Version

TOP FRAME installed under desk Black

Top Frame installed under desk or table without flap, black powder-coated housing

925.100	· 4-way · Dimensions (L x W x H): approx. 300 x 92 x 98 mm
925.101	· 8-way · Dimensions (L x W x H): approx. 482.5 x 92 x 98 mm

TOP FRAME cover Blasted and anodised EV1

Top Frame cover blasted and anodised, with fixing screws

925.0044	· 4-way · for mounting on TOP FRAME installed under desk (art. no. 925.100)
925.0034	· 8-way · for mounting on TOP FRAME installed under desk (art. no. 925.101)

TOP FRAME cover Blasted and black anodised


Top Frame cover blasted and black anodised, with fixing screws

925.0047	· 4-way · for mounting on TOP FRAME installed under desk (art. no. 925.100)
925.0049	· 8-way · for mounting on TOP FRAME installed under desk (art. no. 925.101)

TOP FRAME cover Anodised EV1

Top Frame cover anodised EV1, with fixing screws

925.0022	· 4-way · for mounting on TOP FRAME installed under desk (art. no. 925.100)
925.0023	· 8-way · for mounting on TOP FRAME installed under desk (art. no. 925.101)




TOP FRAME with frame


- Includes fixing accessories

Art. no. | Version


TOP FRAME		RAL 9006
Asymmetrical surround frame, short - for 4-way power strip		
925.501	· Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 340,5 x 162 x 98,35 mm	



TOP FRAME		RAL 9006
Asymmetrical surround frame, long - for 8-way power strip		
925.501	· Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 583 x 162 x 110 mm	



TOP FRAME		RAL 9006
Symmetrical surround frame, short - for 4-way power strip		
925.801	· Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 400,5 x 192 x 98,35 mm	



TOP FRAME		RAL 9006
Symmetrical surround frame, long - for 8-way power strip		
925.801	· Aluminium flap RAL 9006, black powder-coated housing · Dimensions (L x W x H): approx. 583 x 192 x 98,35 mm	



Please refer to the next two pages for power strips appropriate for Slide, Conference and Top Frame

4-way power strips for Slide / Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version



CUSTOM	4-way: 3 x custom modules + power socket outlet	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.002	· 1 socket outlet with earthing contact, child-proof, black, set at 35°
	909.025	· 1 child-proof French / UTE socket outlet, black, set at 35°
	909.028*	· 1 Swiss / CH socket outlet, black, set at 0°
	909.065*	· 1 Italian / earth contact combination, black, set at 35°



CUSTOM	4-way: 2 x custom modules + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.003	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
	909.010	· 2 child-proof French / UTE socket outlets, black, set at 35°
	909.017	· 2 Swiss / CH socket outlets, black, set at 0°
	909.029*	· 2 Italian / earth contact combination, black, set at 35°



CUSTOM	4-way: 1 x custom module + power socket outlets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
	909.004	· 3 socket outlets with earthing contact, child-proof, black, set at 35°
	909.011	· 3 child-proof French / UTE socket outlets, black, set at 35°
	909.018	· 4 Swiss / CH socket outlets, black, set at 0°
	909.058*	· 3 Italian / earth contact combination, black, set at 35°
	909.0023*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°



CUSTOM	4-way: 4 x custom modules	Length: approx. 260 mm
Anodised aluminium profile; without power connection		
	909.000	· Without socket outlets



USB CHARGER	CUSTOM	4-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power outlet sockets	Length: approx. 260 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
		909.0056	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger, 1 x custom module
		909.0059	· 2 child-proof French / UTE socket outlets, black, set at 35° · 1 x USB double charger, 1 x custom module



8-way power strips for Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version



USB CHARGER	CUSTOM	8-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power outlet sockets	Length: approx. 444 mm
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket			
		909.0057	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger, 4 x custom modules
		909.0060	· 3 child-proof French / UTE socket outlets, black, set at 35° · 1 x USB double charger, 4 x custom modules
		909.0058	· 3 UK 3.15 A individually fused, child-proof, black, set at 45° · 1 x USB double charger, 2 x custom modules

* No storage type

8-way power strips for Conference / Top Frame

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no.	Version	
8-way: 6 x custom modules + power socket outlet		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
909.005	· 2 socket outlets with earthing contact, child-proof, black, set at 35°	
909.012	· 2 child-proof French / UTE socket outlets, black, set at 35°	
909.033*	· 2 Swiss / CH socket outlets, black, set at 0°	
		
8-way: 5 x custom modules + power socket outlet		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
909.006	· 3 socket outlets with earthing contact, child-proof, black, set at 35°	
909.013	· 3 child-proof French / UTE socket outlets, black, set at 35°	
909.0029*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°	
		
8-way: 4 x custom modules + power socket outlet		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
909.007	· 4 socket outlets with earthing contact, child-proof, black, set at 35°	
909.014	· 4 child-proof French / UTE socket outlets, black, set at 35°	
909.019*	· 5 Swiss / CH socket outlets, black, set at 0°	
909.050*	· 4 Italian / earth contact combination, black, set at 35°	
909.0028	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°	
		
8-way: 3 x custom modules + power socket outlet		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
909.008	· 5 socket outlets with earthing contact, child-proof, black, set at 35°	
909.015	· 5 child-proof French / UTE socket outlets, black, set at 35°	
909.020*	· 6 Swiss / CH socket outlets, black, set at 0°	
909.0027*	· 3 UK 3.15 A individually fused, child-proof, black, set at 45°	
		
8-way: 2 x custom modules + power socket outlet		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; power input: GST18i3 plug, power output: GST18i3 socket		
909.009	· 6 socket outlets with earthing contact, child-proof, black, set at 35°	
909.016	· 6 child-proof French / UTE socket outlets, black, set at 35°	
909.0026	· 4 UK 3.15 A individually fused, child-proof, black, set at 45°	
		
8-way: 8 x custom modules		Length: approx. 444 mm CUSTOM
Anodised aluminium profile; without power connection		
909.001	· Without socket outlets	
		

CONFERENCE guide rail set

Art. no.	Version	
CONFERENCE guide rail set		Black
For power strips (pages 6 - 7)		
940.099	· Guide rail, plastic, black	
	· Incl. 2 countersunk head screws 2.9 x 13 mm with torx to DIN 7982	
		

* No storage type

CONI brings flexibility to the desktop, for example in conference and training rooms. CONI facilitates unrestricted individual access to power, media and data supplies from the comfort of a desk or table. Minimal depth also means no restriction on leg movement under the desk or table, even where the units are fitted near the edge. Furthermore, a wide range of standard surface finishes ensure a high level of design freedom.

When not in use, CONI integrates into the surface of the desk or table. Should you need power, data or media, simply open the cover, plug into a socket and close the cover again. The integrated brush insert prevents cables from jamming. The harmonic appearance of an "even" table is retained.

The configuration of CONI data connections can be freely selected (see custom modules from page 62). Power strips can also be interchanged quickly and at any time, without the need for tools. Integrated functionality and flexibility not just for today but also for the advancements of tomorrow.

**The benefits
at a glance**

- Integrated into the top of your desk or table
- Minimum built-in depth, robust frame design
- Integrated brush insert for closing once cables have been connected
- Configuration can be freely selected (see custom modules from page 62)
- Complete power strip can be quickly interchanged
- Suitable for retrofitting



CONI provides unrestricted access to power, media and data supplies. Thanks to the integrated brush insert, the cover can be closed once devices have been connected without jamming the cables.



CONI

Integrated functionality

CONI built-in frame, short and long version

Built-in depth is 56 mm, suitable for desk or table top thicknesses of 10 mm and more. The R5 corner radius facilitates flush mounting in desks or tables.


The brush strips can easily be replaced with colour strips; no tools are required. Simply remove the built-in frame from the top of the desk or table and unscrew the 3 re-usable plastic rivets.

**CONI mounting frame, short**

Outer dimensions: approx. 248 x 151 mm

CONI mounting frame, long

Outer dimensions: approx. 386.5 x 151 mm




Art. no. | Version

CONI short**Silver-grey**

338.0203 | · Silver-grey similar to RAL9006

CONI long**Silver-grey**


338.0205 | · Silver-grey similar to RAL9006

**CONI short****Anthracite**

338.0204 | · Anthracite

CONI long**Anthracite**


338.0206 | · Anthracite

**CONI short****Chrome-plated**

338.0214 | · Chrome-plated

CONI long**Chrome-plated**

338.0227 | · Chrome-plated

**CONI short****Satin white**

911.000 | · Satin white RAL9010

CONI long**Satin white**


911.001 | · Satin white RAL9010

**CONI short****Black**

911.002 | · Black RAL9005

CONI long**Black**

911.003 | · Black RAL9005

**CONI short****Stainless steel**

911.004 | · Ground stainless steel

CONI long**Stainless steel**

911.005 | · Ground stainless steel

Coni holder

- For mounting CONI power strips without using a built-in frame, can be installed underneath the top of a desk or table in a cable tray, for example. Standard chipboard screws are needed for mounting.
- Takes account of the rear-side outlet and bending radii of power and data connections.

Art. no. | Version

Coni holder, upright

918.002	· Black · 2 items in plastic bag · Distance between socket outlet profile and floor: 30 mm from floor to top edge · Power strip: 74 mm
---------	---



CONI Holder

- For optional mounting on CONI mounting frame (short and long version)
- Allows excess lengths of cable to be stowed when plugged in
- Easy to fit by hooking into mounting frame already fitted, using plastic rivets supplied
- Small extra built-in depth of approx. 20 mm in addition to depth of mounting frame



Art. no. | Version

CONI Holder

911.910	· Version for Coni mounting frame, short
911.913	· Version for Coni mounting frame, long



CONI brushes


Art. no. | Version

CONI brush strip, short

911.900	· Red
911.901	· Blue
911.902	· White
911.903	· Yellow
911.904	· Black

CONI brush strip, long

911.905	· Red
911.906	· Blue
911.907	· White
911.908	· Yellow
911.909	· Black



3-way power strips for CONI

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no. | Version



CUSTOM	3-way: 2 x custom modules + power socket outlet	Length: approx. 217 mm
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	912.002	· 1 socket outlet with earthing contact, child-proof, black, set at 35°
	912.009	· 1 child-proof French / UTE socket outlet, black, set at 35°
	912.016	· 1 Swiss / CH socket outlet, black, set at 0°
	912.0055*	· 1 Italian / earth contact combination, black, set at 35°



CUSTOM	3-way: 1 x custom module + power socket outlets	Length: approx. 217 mm
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	912.003	· 2 socket outlets with earthing contact, black, set at 35°
	912.010	· 2 child-proof French / UTE socket outlets, black, set at 35°
	912.015	· 3 Swiss / CH socket outlets, black, set at 0°
	912.037*	· 1 socket outlet with earthing contact, black, set at 35°, · 1 Swiss / CH socket outlet, black, set at 0°
	912.045*	· 2 UK 3.15 A individually fused, child-proof, black, set at 90°



CUSTOM	3-way: 1 x custom module + power socket outlets, black and red	Length: approx. 217 mm
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)		
	912.023*	· 1 socket outlet with earthing contact, black, set at 35° · 1 socket outlet with earthing contact, red, set at 35°



3-way: 2 x CAT5e + power socket outlets		Length: approx. 217 mm
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	333.1008	· 2 socket outlets with earthing contact, black, set at 35° · 2 CAT5e RJ45, front: Socket / rear: Socket



3-way: Power socket outlets		Length: approx. 217 mm
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug		
	333.1007	· 3 socket outlets with earthing contact, black, set at 35°



CUSTOM	3-way: 3 x custom modules	Length: approx. 217 mm
Anodised aluminium profile; without power connection		
	912.000	· Without socket outlets

Art. no. | Version



USB CHARGER	CUSTOM	3-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power outlet sockets	Length: approx. 217 mm
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
		912.0167	· 1 socket outlet with earthing contact, child-proof, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A), 1 x custom module
		912.0156	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A)
		912.0171	· 1 child-proof French / UTE socket outlet, black, set at 35° · 1 x USB double charger (5.2 V/2.15 A), 1 x custom module

NEW

* No storage type

6-way power strips for CONI

Power cables and custom modules are available separately. See glossary for country-specific information.

Art. no.	Version		
6-way: 5 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.004	· 1 socket outlet with earthing contact, child-proof, black, set at 35°		
6-way: 4 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.005	· 2 socket outlets with earthing contact, child-proof, black, set at 35°		
912.011	· 2 child-proof French / UTE socket outlets, black, set at 35°		
912.017	· 3 Swiss / CH socket outlets, black, set at 0°		
912.0125*	· 1 UK 3.15 A individually fused, child-proof, black, set at 45°		
6-way: 3 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.006	· 3 socket outlets with earthing contact, child-proof, black, set at 35°		
912.012	· 3 child-proof French / UTE socket outlets, black, set at 35°		
912.018	· 4 Swiss / CH socket outlets, black, set at 0°		
912.022*	· 3 UK 3.15 A individually fused, child-proof, black, set at 90°		
912.0124*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°		
6-way: 2 x custom modules + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.007	· 4 socket outlets with earthing contact, child-proof, black, set at 35°		
912.013	· 4 child-proof French / UTE socket outlets, black, set at 35°		
912.019	· 5 Swiss / CH socket outlets, black, set at 0°		
912.035*	· 1 socket outlet with earthing contact, black, set at 35°		
	· 3 Swiss / CH socket outlets, black, set at 0°		
912.0123	· 3 UK 3.15 A individually fused, child-proof, black, set at 45°		
6-way: 1 x custom module + power socket outlet		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.008	· 5 socket outlets with earthing contact, child-proof, black, set at 35°		
912.014	· 5 child-proof French / UTE socket outlets, black, set at 35°		
912.021*	· 4 UK 3.15 A individually fused, child-proof, black, set at 90°		
912.0122	· 4 UK 3.15 A individually fused, child-proof, black, set at 45°		
6-way: 3 x custom modules + power socket outlet, black and red		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.024	· 1 socket outlet with earthing contact, child-proof, black, set at 35°		
	· 2 socket outlets with earthing contact, child-proof, red, set at 35°		
6-way: 2 x custom modules + power socket outlet, black and red		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; power input: 2 x 0.1 m cable (black and red) and GST18i3 plug (black)			
912.025	· 2 socket outlets with earthing contact, black, set at 35°		
	· 2 socket outlets with earthing contact, red, set at 35°		
6-way: 6 x custom modules		Length: approx. 356 mm	CUSTOM
Anodised aluminium profile; without power connection			
912.001	Without socket outlets		
6-way: 1 x USB double charger (5.2 V/2.15 A) + custom modules + power outlet sockets		Length: approx. 356 mm	CUSTOM USB CHARGER
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug			
912.0168	· 2 socket outlets with earthing contact, child-proof, black, set at 35°		
	· 1 x USB double charger, 3 x custom modules		
912.0169	· 3 child-proof Swiss / CH socket outlets, black, set at 90°		
	· 1 x USB double charger, 3 x custom modules		
912.0172	· 2 child-proof French / UTE socket outlets, black, set at 35°		
	· 1 x USB double charger, 3 x custom modules		
912.0170	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°		
	· 1 x USB double charger, 2 x custom modules		



CONI COVER

Easy access



CONI COVER is an elegant way of accessing separate power supply units or standard cable installation systems under the tops of desks and tables. It is ideal, for example, for desks and tables with built-in cable ducts. CONI COVER can of course also be retrofitted to existing equipment.

To access the connections underneath the top of the desk or table, simply open the CONI COVER cover. Thanks to the integrated brush insert, the cover can even be closed again once the devices have been connected. The harmonic appearance of an "even" table is retained.

CONI COVER, the elegant cover for practical solutions - access couldn't be easier!

The benefits at a glance

- Compatible for universal use with all types of duct and furniture
- Ideal for subsequent installation
- Integrated brush insert for closing once cables have been connected

CONI COVER / Built-in frame

CONI COVER built-in frames are available in short and long versions. The R5 corner radius facilitates flush mounting in desks or tables. The built-in depth is approx. 24 mm, suitable for desk or table top thicknesses of 16 mm and more. Fixing to the tabletop is with 4 screws. These are screwed on from the inside through corresponding holes on the long sides of the built-in frame. Fitting instructions and cut-out dimensions are supplied with the unit.

CONI COVER built-in frame, short

Outer dimensions: 248 x 149 mm

CONI COVER built-in frame, long

Outer dimensions: 387 x 149 mm

Art. no. | Version

CONI COVER short

Silver-grey

338.0081 | · Sheet steel silver-grey RAL9006 (similar)

CONI COVER long

Silver-grey

338.0080 | · Sheet steel silver-grey RAL9006 (similar)

CONI COVER short

Satin white

911.500 | · Satin white RAL9010

CONI COVER long

Satin white

911.501 | · Satin white RAL9010

CONI COVER short

Black

911.502 | · Black RAL9005

CONI COVER long

Black


911.503 | · Black RAL9005



CONI COVER and STEP The expandable combination.

The modular design of the STEP power strips puts everything you need for your specific, customised supply of power and data at your fingertips. CONI COVER with its integrated brush insert provide access that is both fast and elegant.

STEP can be found from page 56.



Easy access to all power supply units located underneath the top of the desk or table. For example to modular STEP power strips.

STEP can be found on page 56

POWER FRAME is the compact solution for integrated and easily accessible power and data connections for workstations.

They can either be installed as new or supplied as equipment for retrofitting.

Combining compact dimensions with high-quality timeless design, POWER FRAME opens up virtually unlimited application options that go far beyond the realm of office workstations. Such as in sales showrooms and display windows and at trade fair and demonstration stands, in short, wherever secure and rapid connections are the order of the day.

Furthermore, the selected power strip simply plugs into the built-in frame from below without the need for any tools - do things get any better than this?

POWER FRAME - for a more compact and more efficient solution.

**The benefits
at a glance**

- Compact dimensions
- Suitable for retrofitting
- Timeless design
- Versatile in application
- Rapid installation of complete power strips



POWER FRAME is the solution for easy-to-access power and data connections at workstations and elsewhere. The power strip is simply clicked into the built-in frame from below.



POWER FRAME

Compact and efficient

POWER FRAME –
the practical unit for rapid installation.



POWER FRAME is an easily accessible unit for supplying electricity to workstations. The power strip clicks into the built-in frame and can be interchanged if necessary or fitted with custom modules.

Built-in frame for desk/table top thicknesses: as of 10 mm
Built-in depth (of the frame): approx. 36 mm
Corner radius for flush mounting: R5
Total built-in depth (including cables): approx. 70 mm
The power and data connection sockets are located on the rear of the power strip.

Built-in frame

Art. no.	Version	Outer dimensions: approx. 241 x 73 mm
317.000	· Silver-grey similar to RAL 9006	
317.001	· Stainless steel	
915.000	· Black RAL 9005	
915.001	· White RAL 9010	

Art. no.	Version	Length: approx. 283.5 x 73 mm
317.006	· Silver-grey similar to RAL 9006	
915.004	· Black RAL 9005	

Plastic power strips, 3-way

Art. no.	Version	Length: approx. 220 mm
CUSTOM 3-way: 2 x custom modules + power socket outlet		
Plastic profile; power input: 0.1 m cable and GST18i3 plug		
916.061	· 1 socket outlet with earthing contact, child-proof, black, set at 35°	
916.063	· 1 child-proof French / UTE socket outlet, black, set at 35°	
CUSTOM 3-way: 1 x custom module + power socket outlet		
Plastic profile; power input: 0.1 m cable and GST18i3 plug		
916.060	· 2 socket outlets with earthing contact, child-proof, black, set at 35°	
916.062	· 2 child-proof French / UTE socket outlets, black, set at 35°	
CUSTOM 3-way: Power socket outlets		
Plastic profile; power input: 0.1 m cable and GST18i3 plug		
317.117	· 3 socket outlets with earthing contact, child-proof, black, set at 35°	
916.059	· 3 child-proof French / UTE socket outlets, black, set at 35°	

Aluminium power strips, 3-way

Art. no. | Version

3-way: 2 x custom modules + power socket outlets		Length: approx. 220 mm	CUSTOM	
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
916.001	· 1 socket outlet with earthing contact, child-proof, black, set at 35°			
916.003	· 1 child-proof French / UTE socket outlet, black, set at 35°			
916.005*	· 1 Swiss / CH socket outlet, black, set at 0°			
3-way: 1 x custom module + power socket outlets		Length: approx. 220 mm	CUSTOM	
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
916.000	· 2 socket outlets with earthing contact, child-proof, black, set at 35°			
916.002	· 2 child-proof French / UTE socket outlets, black, set at 35°			
916.004*	· 3 Swiss / CH socket outlets, black, set at 0°			
916.082	· 2 UK 3.15 A individually fused, child-proof, black, set at 90°			
3-way: 2 x CAT5e + power socket outlets		Length: approx. 220 mm		
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
317.101	· 2 socket outlets with earthing contact, child-proof, black, set at 35°			
	· 2 CAT5e RJ45, front: Socket / rear: Socket			
3-way: Power socket outlets		Length: approx. 220 mm		
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
317.100	· 3 socket outlets with earthing contact, child-proof, black, set at 35°			
317.102	· 3 child-proof French / UTE socket outlet, black, set at 35°			
916.1129	· 3 UK 3.15 A individually fused, child-proof, black, set at 90°			
3-way: 3 x custom modules		Length: approx. 220 mm	CUSTOM	
Anodised aluminium profile; without power connection				
916.010	· Pure custom modules variant			
3-way: 1 x USB double charger (5.2 V/2.15 A) + 1 x custom module + power outlet sockets		Length: approx. 220 mm	CUSTOM	USB CHARGER
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
916.0039	· 1 socket outlet with earthing contact, child-proof, black, set at 35°			
916.0042	· 1 child-proof French / UTE socket outlet, black, set at 35°			
3-way: 1 x USB double charger (5.2 V/2.15 A) + power outlet sockets		Length: approx. 220 mm	CUSTOM	USB CHARGER
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
916.0040	· 2 socket outlets with earthing contact, child-proof, black, set at 35°			

Power strips, 4-way

Art. no. | Version

4-way: 1 x USB double charger (5.2 V/2.15 A) + 2 x custom modules + power outlet sockets		Length: approx. 261.9 mm	CUSTOM	USB CHARGER
Anodised aluminium profile; power input: 0.1 m cable and GST18i3 plug				
916.0041*	· 1 socket outlet with earthing contact, child-proof, black, set at 35°			
4-way: 2 x custom modules + power socket outlets		Length: approx. 261.9 mm	CUSTOM	
Black plastic; power input: 0.1 m cable and GST18i3 plug				
916.0601	· 2 socket outlets with earthing contact, child-proof, black, set at 35°			
4-way: 3 x custom modules + power socket outlets		Length: approx. 261.9 mm	CUSTOM	
Black plastic; power input: 0.1 m cable and GST18i3 plug				
916.0611	· 1 socket outlet with earthing contact, child-proof, black, set at 35°			

* No storage type





POWER FRAME COVER

Finally power found elegance

POWER FRAME COVER is the next logical step from the compact POWER FRAME. An elegant and attractive aluminium cover, designed especially for design-oriented conference and office settings. Power and data connections are protected from dust and dirt as an added bonus.

**The benefits
at a glance**

- Designer piece made from anodised aluminium
- For conference tables and desks
- Access to power supply and data from any seat
- Dust protection
- Versatile options for combining with socket outlets and data/audio/video modules



POWER FRAME COVER

Art. no. | Version

POWER FRAME COVER 3-way		Dimensions: approx. 255 x 87 x 8 mm
3-way Power Frame black (art. 915.000), with aluminium flap, for gluing into desk or table		
915.500	· Aluminium	
915.503	· Aluminium, painted in white RAL 9010	
915.501	· Aluminium, painted in stainless steel	




POWER FRAME COVER 4-way		Dimensions: approx. 298 x 87 x 8 mm
4-way Power Frame black (art. 915.004), with aluminium flap, for gluing into desk or table		
915.502	· Aluminium	



In combination with the POWER FRAME COVER, only power strips with custom modules which terminate flush with the surface can be used.

You will find suitable power strips on the previous pages.





reddot design award
winner 2012

TWIST

Power outside the box

TWIST is a power strip for the office, lounge and kitchen. Its compact design and low built-in depth allow it to be integrated in desks or kitchen work surfaces without taking up too much space. The power cable is kept close to the housing, making the built-in depth just around 40 mm - it can therefore be easily fitted above drawers.

The stainless steel or chrome look enables TWIST to blend seamlessly into both modern and organic design and colour concepts. The catch is really clever: after use, the cover is rotated and the socket outlets disappear under it.

TWIST won the Red Dot Product Design Award 2012.



The benefits at a glance

- Very low built-in depth (approx. 40 mm)
- Compact design (Hxdia.: approx. 42.5 x 115 mm)
- Space-saving cable routing
- Quick and easy to assemble
- Stainless steel or chrome matt
- Red Dot Product Design Award Winner 2012



TWIST

Art. no. | Version

TWIST 2S

Metallic covering plate with stainless steel look; power input: 2.0 m cable with end sleeves and enclosed earthing contact mounting plug, black

- | | |
|---------|--|
| 931.000 | <ul style="list-style-type: none"> · 2 x socket outlets with earthing contact, child-proof, black · Built-in diameter 105 mm, built-in depth 40 mm · For desk or table top thicknesses of 20 mm or more |
|---------|--|

TWIST 1S 2P

Metallic covering plate, chrome matt; power input: 0.2 m with GST18i3 plug

- | | |
|---------|---|
| 931.001 | <ul style="list-style-type: none"> · 1 x socket outlet with earthing contact, child-proof, black · 2 x Keystone fittings for data sockets · Built-in diameter 105 mm, built-in depth 40 mm · For desk or table top thicknesses of 20 mm or more |
|---------|---|

Hole saw diameter 105 mm

For installing TWIST

- | | |
|---------|--|
| 931.900 | <ul style="list-style-type: none"> · In wood / plastic · Cutting depth up to 44 mm |
|---------|--|

Mounting tool for hole saw 931.900


- | | |
|---------|---|
| 918.900 | <ul style="list-style-type: none"> · With centre drill |
|---------|---|



Photo shows similar product

TWIST is so compact that it can even be fitted above drawers.

With a total height of 42.5 mm, TWIST is so compact that it can be fitted on virtually all surfaces. Even underlying drawers don't present a problem. And thanks to the flexible cable outlet, the cable fits into a milled groove.



40 mm is all the space TWIST needs.



ELEVATOR

Introducing power in the elevator


ELEVATOR fits in perfectly in any work environment. With a 79 mm diameter, ELEVATOR is ideally suited to integrating power and data connections in tight spaces.

Apply thumb pressure to raise and lower ELEVATOR. ELEVATOR is available in two versions: with three socket outlets or with one socket outlet and two data connections.

Installation is incredibly easy. ELEVATOR is placed in a cut-out 79 mm in diameter and secured to the top of the desk or table from below using a lock ring.

The benefits at a glance

- Apply thumb pressure to raise
- 2 configurations
- Suitable for 79 mm standard hole
- Quick and easy to assemble
- Suitable for retrofitting
- Aluminium nickel-plated, brushed
- Classic design
- For desk or table top thicknesses of 16 - 40 mm





ELEVATOR

Art. no. | Version

ELEVATOR power strip

Aluminium profile with stainless steel look; kitchen variant

Power input: 2.0 m H05VV-F 3G 1.5 mm² with end sleeves and enclosed earthing contact mounting plug

- | | |
|---------|--|
| 928.003 | <ul style="list-style-type: none"> · 1 socket outlet with earthing contact, child-proof, black, set at 35° · 2 x Euro socket outlets, child-proof, black |
|---------|--|

Aluminium profile E0EV01 anodised; office variant

Power input: 0.3 m H05VV-F3G 1.5 mm² with GST18 plug; data cables 3.0 m and plug

- | | |
|---------|--|
| 928.004 | <ul style="list-style-type: none"> · 1 socket outlet with earthing contact, child-proof, black, set at 35° · 2 CAT5e RJ45 with 3.0 m data cable and RJ45 plug |
| 928.005 | <ul style="list-style-type: none"> · 1 socket outlet with earthing contact, child-proof, black, set at 35° · 1 USB A socket with 3.0 m data cable and plug · 1 CAT5e RJ45 with 3.0 m data cable and RJ45 plug |
| 928.006 | <ul style="list-style-type: none"> · 1 socket outlet with earthing contact, child-proof, black, set at 35° · 1 HDMI socket with 3.0 m data cable and plug · 1 CAT5e RJ45 with 3.0 m data cable and plug |

Art. no. | Version

Hole saw diameter 79 mm

For installing ELEVATOR


- | | |
|---------|--|
| 928.900 | <ul style="list-style-type: none"> · In wood / plastic · Cutting depth up to 44 mm |
|---------|--|

Mounting tool for hole saw

- | | |
|---------|---|
| 918.900 | <ul style="list-style-type: none"> · With centre drill |
|---------|---|



Photo shows similar product



Dimensions in mm

ELEVATOR fits into hole cut-outs with a 79 mm diameter

100 mm high, 79 mm in diameter: With 3 sockets, ELEVATOR really pulls its punch in tight spaces. ELEVATOR opens autonomously with thumb pressure. After use, it is lowered again.



LIFT is the totally practical combination of sophisticated looks and high-precision mechanical design. The unit is recessed neatly in the top of the desk or table when not in use. Simply touch to raise out of the desk or table ready for docking on all four sides. Once you have finished using the LIFT unit, simply push it back into its initial recessed position by hand.

LIFT can be supplied in a variety of power and data connection configurations. This highly compact unit needs a drill hole only 140 mm in diameter for installation. Built-in depth both open and closed is just 195 mm.

By setting cutting-edge technology in motion, LIFT makes power and data supply a truly enjoyable experience.

**The benefits
at a glance**

- Simply touch to raise
- Attractive looks all round
- Access points on four sides
- Incredibly compact dimensions
- Low built-in depth
- 4 plug-in units on 1 height unit



Simply touch to raise and lower LIFT. The unit has connection points on four sides and can be supplied in a variety of power and data connection configurations.



LIFT

High-tech in motion



Enclosure colour BLACK

Art. no. | Version

LIFT: Power outlet sockets

Enclosure colour black; power input: 0.5 m cable and GST18i3 plug

	904.000	· 4 socket outlets with earthing contact, child-proof, black, set at 35°
	904.004	· 4 child-proof French / UTE socket outlets, black, set at 35°
	904.024*	· 4 Swiss / CH socket outlets, black, set at 0°
	904.020*	· 4 UK 3.15 A individually fused, child-proof, black, set at 90°

LIFT: 2 x CAT6 + power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug; 3.0 m data cable and RJ45 plug

	904.001	· 3 socket outlet with earthing contact, child-proof, black, set at 35°
	904.005	· 3 child-proof French / UTE socket outlets, black, set at 35°
	904.025*	· 3 Swiss / CH socket outlets, black, set at 0°
	904.021*	· 3 UK 3.15 A individually fused, child-proof, black, set at 90°

LIFT: 2 x CAT6, 1 x VGA + mini stereo jack + power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug;

CAT6 3.0 m data cable and RJ45 plug; VGA 15-pole and mini stereo jack with 3.0 m cable and plug;

	904.002	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
	904.006	· 2 child-proof French / UTE socket outlet, black, set at 35°
	904.026*	· 2 Swiss / CH socket outlets, black, set at 0°
	904.022*	· 2 UK 3.15 A individually fused, child-proof, black, set at 90°

LIFT: 2 x CAT6, 2 x USB + power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug;

CAT6 3.0 m data cable and RJ45 plug; USB A socket with 3.0 m cable and plug;

	904.003	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
	904.007	· 2 child-proof French / UTE socket outlet, black, set at 35°
	904.027*	· 2 Swiss / CH socket outlets, black, set at 0°
	904.023*	· 2 UK 3.15 A individually fused, child-proof, black, set at 90°

LIFT: 2 x CAT 6, 1 x VGA + mini stereo jack, 1 x HDMI, power outlet socket

Enclosure colour black; power input: 3.0 m cable and plug

	904.045	· CAT6 3.0 m data cable and RJ45 plug; VGA 15-pole and mini stereo jack with 3.0 m cable and plug · 1 x socket outlet with earthing contact, child-proof, black, set at 35°, with 3.0 m cable and plug · 2 CAT6 RJ45 with 3.0 m data cable and RJ45 plug · 1 x VGA+mini stereo jack with 3.0 m cable each · 1 x HDMI with plug
--	---------	--

USB CHARGER**LIFT: 1 x USB double charger (5.2 V/2.15 A), 2 x CAT6 + power outlet sockets**

Enclosure colour black; power input: 3.0 m cable and plug; 3.0 m data cable and RJ45 plug

	904.0001*	· 2 x socket outlets with earthing contact, child-proof, black, set at 35° · 1 x USB double charger · 2 x CAT6 RJ45 socket
--	-----------	--

* No storage type

Enclosure colour SILVER




Art. no. | Version

LIFT: Power outlet sockets

Enclosure colour silver; power input: 0.5 m cable and GST18i3 plug


904.008 | · 4 socket outlets with earthing contact, child-proof, black, set at 35°



LIFT: 2 x CAT6 + power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug; 3.0 m data cable and RJ45 plug

904.009 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°



LIFT: 2 x CAT6, 1 x VGA + mini stereo jack + power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug;

CAT6 3.0 m data cable and RJ45 plug; VGA 15-pole and mini stereo jack with 3.0 m cable and plug

904.010 | · 2 socket outlets with earthing contact, child-proof, black, set at 35°



LIFT: 2 x CAT6, 2 x USB +power outlet sockets

Enclosure colour black; power input: 3.0 m cable and plug;

CAT6 3.0 m data cable and RJ45 plug; USB A socket with 3.0 m cable and plug

904.011 | · 2 socket outlets with earthing contact, child-proof, black, set at 35°



Hole saw

diameter 140 mm

For installing LIFT

904.900 | · Hole saw for clamping, with centre drill
· Diameter 140 mm



Photo shows similar product

DESK is the ideal solution for data, media and power management wherever workstations need to be flexible. Typical situations might include meeting rooms, home offices or desk sharing environments.

DESK's modular design means that it can be supplied ex works precisely configured with the communication and power supply connections required for the workstation and application at and in which the products are to be used. Thus for power connections there is a free choice of either the flexible Wieland system or permanent connections. The data connections are fitted with adapters as standard, but can likewise also be fixed connections.

When it comes to positioning the DESK units, again versatility is the key. They are fixed to the desk/table top by mounting brackets or screws or can be free-standing, as best suits the application and good style.

**The benefits
at a glance**

- Flexibility of use regardless of location
- With Wieland connector system or fixed connection cables
- Fixed or free-standing on desk/table
- Custom versions adapt to future requirements



DESK's modular design means that it can be supplied ex works precisely configured with the required communication and power supply connections. DESK can be fixed to a table or desk top or be free-standing.



DESK 1

Versatility with style

DESK 1 – every possibility at your fingertips.



Plug connections as standard

The standard power connection features a Wieland plug-in connector in the rear panel and provides both reliable power feed and also flexibility in cable length. The cables can be swapped for longer or shorter power supply cables, for example. We use Wieland's GST18 connector, which is popular all over the world, as standard. This plug connection has a catch mechanism which complies with the relevant standards and can be released again if required. The contacts on the plug connection are safe to touch.

A power output socket provides a means of forwarding power to the next module.

Mounting without damage

DESK 1 can be mounted on the edge of a desk or table quickly and easily using a mounting bracket. A size 4 Allen key is required in order to tighten the inside screw on the bracket. Mounting does not damage the tabletop/desktop. You will find a range of mounting brackets and units on page 47.

DESK 1 plus STEP in combination

Combining DESK 1 with a STEP power strip provides the ideal overall solution for an individual office workstation. DESK 1 provides easy access to power and data connections for various devices (laptop, mobile phone, USB etc.) whilst the STEP power strip under the desk/table top supplies power to fixed devices such as PC, monitor, printer etc. The STEP power strip is screwed in place underneath the top of the desk or table or placed in a duct underneath.

The integrated Wieland connector system enables multiple power strips to be connected in series in compliance with standards.





DESK 1 – Product matrix

You will find a detailed product description on the following pages.

DESK 1	Country ID	Socket inserts	Empty spaces for custom modules	USB charger	Illuminated switch	CAT5e RJ45 Socket/socket	VGA+3.5 mm mini stereo jack	USB 3.0 A/A socket	Incl. mounting bracket	Incl. supply cable	Child-proof	Length in mm
902.0182	EN	2	1	yes	-	-	-	-	-	-	yes	281.3
902.011	EN	2	2	-	-	-	-	-	-	-	yes	322.5
902.0183*	EN	2	2	yes	-	-	-	-	-	-	yes	323.8
902.0048	EN	3	-	-	-	-	-	-	-	-	yes	270.0
339.1002	EN	3	-	-	-	-	-	-	yes	-	yes	225.0
902.0050	EN	3	-	-	yes	-	-	-	-	-	yes	313.0
339.1001	EN	3	-	-	yes	-	-	-	yes	yes	yes	268.0
339.1004	EN	3	-	-	-	2	-	-	yes	-	yes	280.0
339.1005	EN	3	-	-	-	2	1	-	yes	-	yes	325.0
339.1006	EN	3	-	-	-	2	-	1	yes	-	yes	325.0
902.000	EN	3	1	-	-	-	-	-	-	-	yes	322.5
902.017	EN	3	1	-	yes	-	-	-	-	-	yes	365.0
902.001	EN	3	2	-	-	-	-	-	-	-	yes	365.0
902.018	EN	3	2	-	yes	-	-	-	-	-	yes	408.0
902.012	EN	1/2	2	-	-	-	-	-	-	-	yes	385.0
902.002	EN	3	3	-	-	-	-	-	-	-	yes	366.3
902.019	EN	3	3	-	yes	-	-	-	-	-	yes	450.0
902.003	EN	3	4	-	-	-	-	-	-	-	yes	450.0
902.0049	EN	4	-	-	-	-	-	-	-	-	yes	313.0
339.1000	EN	4	-	-	-	-	-	-	yes	yes	yes	268.0
902.0185	UTE	2	1	yes	-	-	-	-	-	-	yes	281.3
902.004	UTE	3	1	-	-	-	-	-	-	-	yes	323.0
902.005	UTE	3	2	-	-	-	-	-	-	-	yes	365.0
902.006	UTE	3	3	-	-	-	-	-	-	-	yes	366.3
902.007	UTE	3	4	-	-	-	-	-	-	-	yes	450.0
902.0161	CH	2	2	yes	-	-	-	-	-	-	-	323.8
902.008	CH	3	1	-	-	-	-	-	-	-	-	258.0
902.009	CH	3	2	-	-	-	-	-	-	-	-	301.0
902.010	CH	3	3	-	-	-	-	-	-	-	-	258.0
902.0184	UK	2	1	yes	-	-	-	-	-	-	yes	300.7
902.024	UK	2	2	-	-	-	-	-	-	-	yes	346.3
902.039	UK	3	2	-	-	-	-	-	-	-	yes	309.0

DESK 1 power strips



Max. 16 A/230 V~ See glossary for country-specific information

Power cables and mounting brackets are available separately

Art. no. | Version

Power outlet sockets

Anodised aluminium profile; power input: GST18 / power output: GST18

 902.0048 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 270 mm

Power outlet sockets

Anodised aluminium profile; power input: GST18 / power output: GST18

 902.0049 | · 4 socket outlets with earthing contact, child-proof, black, set at 35°, length 313 mm

 902.0050 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°
· 1 switch 2-pole illuminated
· Length 313 mm



DESK 1 power strips



Max. 16 A/230 V~ See glossary for country-specific information

with spaces for custom modules

Power cables, custom modules and mounting brackets are available separately

Art. no. | Version

CUSTOM 1 x custom module + power outlet sockets

Anodised aluminium profile; power input: GST18 / power output: GST18

 902.000 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 322.5 mm

 902.017 | · 3 socket outlet with earthing contact, child-proof, black, set at 35°
· 1 switch 2-pole illuminated, length 365 mm

 902.004 | · 3 child-proof French / UTE socket outlets, black, set at 35°, length 322.5 mm

 902.008 | · 3 Swiss / CH socket outlets, black, set at 0°, length 258 mm

**CUSTOM 2 x custom modules + power outlet sockets**

Anodised aluminium profile; power input: GST18 / power output: GST18

 902.001 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 365 mm

 902.011 | · 2 socket outlets with earthing contact, child-proof, black, set at 35°, length 322.5 mm

 902.018 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 407.5 mm
· 1 switch 2-pole illuminated

 902.005 | · 3 child-proof French / UTE socket outlets, black, set at 35°, length 365 mm

 902.009 | · 3 Swiss / CH socket outlets, black, set at 0°, length 300.5 mm

 902.039* | · 3 UK 3.15 A individually fused, child-proof, black, set at 90°, length 309 mm

 902.024 | · 2 UK 3.15 A individually fused, child-proof, black, set at 45°, length 346.3 mm

**CUSTOM 3 x custom modules + power outlet sockets**

Anodised aluminium profile; power input: GST18 / power output: GST18

 902.002 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 366.3 mm

 902.019 | · 3 socket outlets with earthing contact, child-proof, black, set at 35°
· 1 switch 2-pole illuminated, length 450 mm

 902.006 | · 3 child-proof French / UTE socket outlets, black, set at 35°, length 366.3 mm

 902.010 | · 3 Swiss / CH socket outlets, black, set at 0°, length 257.5 mm

**You can find suitable Wieland cables on page 131**

* No storage type

DESK 1 power strips



Max. 16 A/230 V~ See glossary for country-specific information

with spaces for custom modules

Power cables, custom modules and mounting brackets are available separately

Art. no. | Version

4 x custom modules + power outlet sockets		CUSTOM	
Anodised aluminium profile; power input: GST18 / power output: GST18			
902.003	· 3 socket outlets with earthing contact, child-proof, black, set at 35°, length 450 mm		
902.007	· 3 child-proof French / UTE socket outlets, black, set at 35°, length 450 mm		
2 x custom modules + power outlet sockets		CUSTOM	
Anodised aluminium profile; power input: 2 x GST18 (black and red)			
902.012	· 1 socket outlet with earthing contact, child-proof, black, set at 35° · 2 socket outlets with earthing contact, child-proof, red, set at 35°, length 385 mm		
1 x custom module + power socket outlet + illuminated switch		CUSTOM	
Anodised aluminium profile; power input: GST18 / power output: GST18			
902.017	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · 1 x illuminated switch; length 365 mm		
2 x custom modules + power socket outlets + illuminated switch		CUSTOM	
Anodised aluminium profile; power input: GST18 / power output: GST18			
902.018	· 3 socket outlet with earthing contact, child-proof, black, set at 35° · 1 x illuminated switch; length 407.5 mm		
3 x custom modules + power socket outlets + illuminated switch		CUSTOM	
Anodised aluminium profile; power input: GST18 / power output: GST18			
902.019	· 3 socket outlet with earthing contact, child-proof, black, set at 35° · 1 x illuminated switch; length 450 mm		

Art. no. | Version

DESK 1 with 1 x USB double charger (5.2 V/2.15 A), 1 x custom module + power outlet sockets		CUSTOM USB CHARGER	
Anodised aluminium profile; power input: GST18/ power output: GST18			
902.0182	· 2 socket outlets with earthing contact, child-proof, black, set at 35°, length 281.3 mm		
902.0185	· 2 child-proof French / UTE socket outlets, black, set at 35°, length 281.3 mm		
902.0184	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°, length 300.7 mm		

DESK 1 with 1 x USB double charger (5.2 V/2.15 A), 2 x custom module + power outlet sockets		CUSTOM USB CHARGER	
Anodised aluminium profile; power input: GST18/ power output: GST18			
902.0183*	· 2 socket outlets with earthing contact, child-proof, black, set at 35°, length 323.8 mm		
902.0161	· 2 Swiss / CH socket outlets, black, set at 90°		

You can find suitable Wieland cables on page 131

* No storage type



Max. 16A/230V~

See glossary for country-specific information

- Anodised aluminium profile, socket outlets, black
- Incl. standard mounting bracket and screws

Art. no. | Version

**DESK 1 3 x earthing contact, GST18****Length: approx. 280 mm**

2 x CAT5e

- 339.1004
- 3 socket outlets with earthing contact, child-proof, black, set at 35°
 - 2 x CAT5e RJ45, front: Socket / rear: Socket
 - Power input: GST18i3 plug, power output: GST18i3 socket
 - Incl. standard mounting bracket and screws

**DESK 1 3 x earthing contact, GST18****Length: approx. 325 mm**

2 x CAT5e, 1 x VGA

- 339.1005
- 3 socket outlets with earthing contact, child-proof, black, set at 35°
 - 2 x CAT5e RJ45, front: Socket / rear: Socket
 - 1 x VGA 15-pole + mini stereo jack 3.5 mm
 - Power input: GST18i3 plug, power output: GST18i3 socket
 - Incl. standard mounting bracket and screws

**DESK 1 3 x earthing contact, GST18****Length: approx. 325 mm**

2 x CAT5e, 1 x USB

- 339.1006
- 3 socket outlets with earthing contact, child-proof, black, set at 35°
 - 2 x CAT5e RJ45, front: Socket / rear: Socket
 - 1 x USB A/A socket
 - Power input: GST18i3 plug, power output: GST18i3 socket
 - Incl. standard mounting bracket and screws

**DESK 1 3 x earthing contact, GST18****Length: approx. 225 mm**

- 339.1002
- 3 socket outlets with earthing contact, child-proof, black, set at 35°
 - Power input: GST18i3 plug, power output: GST18i3 socket
 - Incl. standard mounting bracket and screws

**DESK 1 4 x earthing contact****Length: approx. 268 mm**

Fixed connection

- 339.1000
- 4 socket outlets with earthing contact, child-proof, black, set at 35°
 - Power input: 3.0 m, H05VV-F 3G 1.50 mm² black, with right angle plug with earthing contact
 - Incl. standard mounting bracket and screws

**DESK 1 3 x earthing contact****Length: approx. 268 mm**

Fixed connection, 1 x switch

- 339.1001
- 3 socket outlets with earthing contact, child-proof, black, set at 35°
 - 1 x switch 2-pole, green illuminated
 - Power input: 3.0 m, H05VV-F 3G 1.50 mm² black, with right angle plug with earthing contact
 - Incl. standard mounting bracket and screws

* No storage type

Desk 1 accessories

Art. no.	Version
DESK 1 slimline mounting bracket for desk/table top thicknesses up to 50 mm	
918.001	- Stainless steel, material thickness 3 mm - Contents: 2 stainless steel mounting brackets + 2 M5 x 45 mm Allen keys
DESK 1 standard mounting bracket for desk/table top thicknesses up to 50 mm	
930.120	- Anodised aluminium, material thickness approx. 9 mm - Contents: 2 x mounting clamp aluminium profile anodised 2 x M5 x 60 mm Allen keys
DESK 1 long mounting bracket for desk/table top thicknesses up to 80 mm	
930.180	- Long mounting bracket 50–80 mm - Contents: 2 x mounting clamp black paint finish RAL9011 2 x M5 x 45 mm Allen keys 2 x M5 x 60 mm Allen keys
Spax screws for DESK end caps for desk/table top thicknesses as of 15 mm	
930.183	2 x Spax screws 4 x 90 mm incl. brass threaded sleeve
DESK 1 mounting plate	
930.182	- Plastic, black - Mounting plates for attachment to DESK end caps - Contents: 2 x mounting plates 2 x screws 2 x TESA POWER STRIP





Automatic switchoff

Switch off and save power

The Bachmann automatic switchoff unit allows efficient savings in power consumption without major wiring outlay during times when equipment is not in use in today's office landscapes.

The complete switching-off of equipment is no longer left to chance; now power is saved as soon as the workstation PC is shut down.

The effectiveness of this system exceeds the savings possible with master-and-slave power strips, since practically **no standby current is drawn by the master device** and power consumption during non-use hours is exactly zero.

The benefits at a glance

- Complete switchoff
- No standby current is drawn by the master device
- No electricity - no fire risk
- Potential energy saving of up to € 70 per year and workstation
- Improves the CO₂ footprint



Automatic switchoff modules

Art. no. | Version

STEP ALU automatic switchoff

Length: approx. 263 mm

- 906.005
- Anodised aluminium profile
 - 1 x automatic switchoff with socket outlet
 - 1 x button connection with 0.5 m cable and connector for linking to module 917.060
 - Power input: GST18i3 plug, power output: GST18i3 socket


Module 1 x button automatic switchoff / Automatic Saves Energy

- 917.060
- 1 x button, black, with 1.0 m cable and 2-pole plug
 - Activating the button restores power to the devices connected to the automatic switchoff unit.
 - Use in any power strip with custom modules



A desk connection panel with custom module space and STEP are needed to complete the system.

The automatic switchoff makes possible savings of up to €70 per year and workstation.



DESK 2 is a power strip that can be populated with various communication modules. It has been designed for flexible use in the office, meeting rooms, home offices or desk sharing environments.

The power strip is made from aluminium and is available in various colours. The connections are screwed onto the standardised module windows and can be easily changed over.

DESK 2 is secured to the desktop with aluminium retaining brackets, cables are routed behind the screen.

DESK 2 won the red dot design award 2011, IF Product Design Award 2012 and was nominated for the German Design Award 2012.

The design is simple and straightforward, the materials used are of high quality and durable.

**The benefits
at a glance**

- Design solution for modern workstations
- User-focused 45° orientation
- Covered wiring to the edge of a desk or table
- Custom versions adapt to future requirements
- Red Dot Design Award Winner 2011
- IF Award winner 2012
- Nominated for the German Design Award 2012



Particular attention has been paid to the design of the DESK 2. In terms of technology, DESK 2 has a modular structure, just like its predecessor DESK 1. Like all other Bachmann desk connection panels with media and data modules, DESK 2 is adapted to individual requirements and future purposes using Bachmann custom modules.



DESK 2

Design meets technology



reddot design award
winner 2011



DESK 2 – Product matrix

DESK 2	Country ID	Socket inserts	Empty spaces for custom modules	USB charger	Colour	CAT6 RJ45 Socket/socket	USB 3.0 A/A socket	HDMI socket / socket	Incl. mounting bracket	Incl. supply cable	Child-proof	Length in mm
902.203	EN	2	1	-	white	-	-	-	yes	-	yes	204
902.228	EN	2	1	yes	white	-	-	-	yes	-	yes	239.2
902.211	EN	2	2	-	white	-	-	-	yes	-	yes	239
902.229*	EN	2	2	yes	white	-	-	-	yes	-	yes	281.7
902.2048	EN	3	-	-	white	-	-	-	yes	-	yes	197
902.300	EN	3	-	-	white	-	-	-	yes	yes	yes	197
902.301	EN	3	-	-	white	1	1	-	yes	yes	yes	239
902.302	EN	3	-	-	white	2	1	1	yes	yes	yes	282
902.200	EN	3	1	-	white	-	-	-	yes	-	yes	239
902.201	EN	3	2	-	white	-	-	-	yes	-	yes	282
902.202	EN	3	3	-	white	-	-	-	yes	-	yes	324
902.232*	UTE	2	1	yes	white	-	-	-	yes	-	yes	239.2
902.204	UTE	3	1	-	white	-	-	-	yes	-	yes	239
902.205	UTE	3	2	-	white	-	-	-	yes	-	yes	282
902.213	UK	2	-	-	white	-	-	-	yes	-	yes	196.7
902.206	UK	2	1	-	white	-	-	-	yes	-	yes	239
902.231*	UK	2	1	yes	white	-	-	-	yes	-	yes	274.2
902.207	UK	2	2	-	white	-	-	-	yes	-	yes	274
902.214	UK	4	-	-	white	-	-	-	yes	-	yes	316.7
902.230*	CH	2	2	yes	white	-	-	-	yes	-	-	281.7
902.208	CH	3	1	-	white	-	-	-	yes	-	-	239
902.209	CH	3	2	-	white	-	-	-	yes	-	-	282
902.403	EN	2	1	-	Stainless steel	-	-	-	yes	-	yes	204
902.428	EN	2	1	yes	Stainless steel	-	-	-	yes	-	yes	239.2
902.411	EN	2	2	-	Stainless steel	-	-	-	yes	-	yes	239
902.429*	EN	2	2	yes	Stainless steel	-	-	-	yes	-	yes	281.7
902.4048	EN	3	-	-	Stainless steel	-	-	-	yes	-	yes	197
902.500	EN	3	-	-	Stainless steel	-	-	-	yes	yes	yes	197
902.501	EN	3	-	-	Stainless steel	1	1	-	yes	yes	yes	239
902.502	EN	3	-	-	Stainless steel	2	1	1	yes	yes	yes	282
902.400	EN	3	1	-	Stainless steel	-	-	-	yes	-	yes	239
902.401	EN	3	2	-	Stainless steel	-	-	-	yes	-	yes	282
902.402	EN	3	3	-	Stainless steel	-	-	-	yes	-	yes	324
902.432*	UTE	2	1	yes	Stainless steel	-	-	-	yes	-	yes	239.2
902.404	UTE	3	1	-	Stainless steel	-	-	-	yes	-	yes	239
902.405	UTE	3	2	-	Stainless steel	-	-	-	yes	-	yes	282
902.431*	UK	2	1	yes	Stainless steel	-	-	-	yes	-	yes	274.2
902.407	UK	2	2	-	Stainless steel	-	-	-	yes	-	yes	274
902.406	UK	2	1	-	Stainless steel	-	-	-	yes	-	yes	239
902.430*	CH	2	2	yes	Stainless steel	-	-	-	yes	-	-	281.7
902.408	CH	3	1	-	Stainless steel	-	-	-	yes	-	-	239
902.409	CH	3	2	-	Stainless steel	-	-	-	yes	-	-	282

* No storage type

DESK 2 power strips

Art. no.	Version	
Power socket outlets		Length: approx. 197 mm
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST18; incl. mounting bracket		
902.2049	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in RAL 9010 white	
902.4048	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in stainless steel	
902.300	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in RAL 9010 white 1.5 m separate device supply cable, GST18/earth contact	
902.500	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in stainless steel	
Power outlet sockets		
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST 18i; incl. mounting bracket		
902.213	2 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in RAL 9010 white, length: 196.7 mm	
902.214*	4 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in RAL 9010 white, length: 316.7 mm	



DESK 2 power strips, empty

Art. no.	Version	
1 x custom module + power socket outlets		Length: approx. 239 mm
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST18; incl. mounting bracket		
902.200	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in RAL 9010 white	
902.204	3 child-proof French / UTE socket outlets, black, set at 35° - Painted in RAL 9010 white	
902.206	2 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in RAL 9010 white	
902.208	3 Swiss / CH T13 socket outlets, black, set at 90° - Painted in RAL 9010 white	
902.400	3 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in stainless steel	
902.404	3 child-proof French / UTE socket outlets, black, set at 35° - Painted in stainless steel	
902.406	2 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in stainless steel	
902.408	3 Swiss / CH T13 socket outlets, black, set at 90° - Painted in stainless steel	
1 x custom module + power socket outlets		Length: approx. 204 mm
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST18; incl. mounting bracket		
902.203	2 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in RAL 9010 white	
902.403	2 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in stainless steel	
2 x custom modules + power socket outlets		Length: approx. 239 mm
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST18; incl. mounting bracket		
902.211	2 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in RAL 9010 white	
902.411	2 socket outlets with earthing contact, child-proof, black, set at 35° - Painted in stainless steel	
2 x custom modules + power socket outlets		Length: approx. 274 mm
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm ² with GST18; incl. mounting bracket		
902.207*	2 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in RAL 9010 white	
902.407*	2 UK 3.15 A individually fused, child-proof, black, set at 45° - Painted in stainless steel	



* No storage type

DESK 2 power strips



Art. no. | Version

2 x custom modules + power socket outlets**Length: approx. 282 mm**Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm² with GST18; incl. mounting bracket

	902.201	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in RAL 9010 white
	902.205	· 3 child-proof French / UTE socket outlet, black, set at 35° · Painted in RAL 9010 white
	902.209	· 3 Swiss / CH T13 socket outlets, black, set at 90° · Painted in RAL 9010 white
	902.401	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in stainless steel
	902.405	· 3 child-proof French / UTE socket outlets, black, set at 35° · Painted in stainless steel
	902.409	· 3 Swiss / CH T13 socket outlets, black, set at 90° · Painted in stainless steel

**3 x custom modules + power socket outlets****Length: approx. 324 mm**Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm² with GST18; incl. mounting bracket

	902.202	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in RAL 9010 white
	902.402	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in stainless steel

DESK 2 power strips

Art. no. | Version

USB CHARGER

CUSTOM

DESK 2 with 1 x USB double charger (5.2 V/2.15 A), 1 x custom module + power outlet socketsAluminium profile; power input 0.2 m H05VV-F3G 1.5 mm² with GST 18; incl. mounting bracket

	902.228	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · Length 239.2 mm · Painted in RAL 9010 white
	902.232*	· 2 child-proof French / UTE socket outlets, black, set at 35° · Length 239.2 mm · Painted in RAL 9010 white
	902.231*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45° · Length 284.2 mm · Painted in RAL 9010 white
	902.428	· 2 socket outlets with earthing contact, child-proof, black, set at 35° · Length 239.2 mm · Painted in stainless steel
	902.432*	· 2 child-proof French / UTE socket outlets, black, set at 35° · Length 239.2 mm · Painted in stainless steel
	902.431*	· 2 UK 3.15 A individually fused, child-proof, black, set at 45° · Length 284.2 mm · Painted in stainless steel

* No storage type

DESK 2 power strips

Art. no.	Version		
DESK 2 with 1 x USB double charger (5.2 V/2.15 A), 2 x custom module + power outlet sockets			CUSTOM USB CHARGER
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm² with GST18; incl. mounting bracket			
902.229*	2 socket outlets with earthing contact, child-proof, black, set at 35° - Length 281.7 mm Painted in RAL 9010 white		
902.230*	2 Swiss / CH T13 socket outlets, black, set at 90° - Length 281.7 mm Painted in RAL 9010 white		
902.429*	2 socket outlets with earthing contact, child-proof, black, set at 35° - Length 281.7 mm Painted in stainless steel		
902.430*	2 Swiss / CH T13 socket outlets, black, set at 90° - Length 281.7 mm Painted in stainless steel		

DESK 2 power strips, equipped

Art. no.	Version			
1 x custom module + power socket outlets		Length: approx. 239 mm		
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm² with GST18; incl. mounting bracket				
902.301	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in RAL 9010 white · 1 CAT6 coupling socket/socket · 1 USB A/A 3.0 Keystone module · 1.5 m separate device supply cable, GST18/earth contact			
902.501	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in stainless steel · 1 CAT6 coupling socket/socket · 1 USB A/A 3.0 Keystone module · 1.5 m separate device supply cable, GST18/earth contact			
2 x custom modules + power socket outlets		Length: approx. 282 mm		
Aluminium profile; power input: 0.2 m H05VV-F3G 1.5 mm² with GST18; incl. mounting bracket				
902.302	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in RAL 9010 white · 2 CAT6 coupling socket/socket · 1 USB A/A 3.0 Keystone module · 1 HDMI Keystone socket/socket · 1.5 m separate device supply cable, GST18/earth contact			
902.502	· 3 socket outlets with earthing contact, child-proof, black, set at 35° · Painted in stainless steel · 2 CAT6 coupling socket/socket · 1 USB A/A 3.0 Keystone module · 1 HDMI Keystone socket/socket · 1.5 m separate device supply cable, GST18/earth contact			

Accessories

Art. no.	Version	
DESK 2 cable routing		
Covered cable routing to under the edge of a desk or table		
918.106	Plastic, painted in RAL 9010 white	
918.107	Plastic, painted in stainless steel	

The DESK 2 mounting brackets are suitable for desk/table top thicknesses of between 10 mm and 40 mm. Alternatively, DESK 1 standard mounting brackets (art. no. 930.120) can also be used for DESK 2. In combination with DESK 2, these cover a clamping range of 25 mm to 55 mm.

STEP embodies the principle of modularity with absolute consistency. Accordingly, the system is ideal for flexible power and data supply at workstations, in partition systems, false floors and other connection applications.

The modularity of the STEP power strips makes for virtually endless possibilities: from simple sets for supplying electricity to power strips with integrated data connections, RCDs/MCBs, overvoltage protection, connections for media technology and much more.

For electricity distribution STEP uses the Wieland connector system as standard and can therefore be supplied with a variety of cable lengths. Other plug connection systems can also be supplied on request.


STEP delivers individual tailor-made solutions meeting all the requirements of modern power and data supply. In short: Fit for the future - step by step.

**The benefits
at a glance**

- Consistent modularity
- Versatile applications
- Standard connection system
- Can be removed at any time
- Functional efficiency



STEP is ideal for flexible power and data supply at workstations, in partition systems, false floors and other connection applications.



STEP

Fit for the future - step by step

STEP – the all-round system designed for expansion.



Perfectly tailored for the best connections

The STEP power strip is available with an aluminium or plastic profile. It is possible to connect multiple power strips together to form a modular system. STEP is designed primarily as a simple electricity supply unit for office workstations. Permanently positioned devices such as PCs, monitors, printers, etc. can be connected to STEP.

STEP power strips have a power input and a power output, each of which is built into the end caps. The Wieland GST18 plug connectors fitted are particularly tried-and-tested solutions for office use and have the coding and latch mechanism required to comply with the applicable standard.



Versatile mounting options

STEP power strips are versatile in their application. They can be fitted for example under table/desk tops, in cable ducts and in partitions. Different mounting accessories are available for the various applications (see page 61 onwards).



STEP combination options

You can plug separate modules together or combine them as you wish with a connecting cable.

STEP can thereby function as a unique power distribution system. Other plug-in connection systems (e.g. Wago Winsta, Woertz, Ensto) can be supplied on request.

See glossary for country-specific information

Power cables and custom modules are available separately

Art. no. | Version

STEP BASE: Power socket outlets Length: approx. 220 mm

Plastic profile; power input: GST18 / power output: GST18

336.600	· 3 socket outlets with earthing contact, child-proof, black, set at 35°
336.601	· 3 socket outlets with earthing contact, child-proof, red, set at 35°
336.603	· 3 child-proof French / UTE socket outlet, black, set at 35°
906.1306	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°
906.0059	· 2 UK 3.15 A individually fused, child-proof, black, set at 45°, 2 switches
906.0055	· 4 UK 3.15 A individually fused, child-proof, black, set at 45°
906.0060	· 4 UK 3.15 A individually fused, child-proof, black, set at 45°, 1 switches



STEP BASE: Power socket outlets Length: approx. 262.5 mm (note special lengths)

Plastic profile; power input: GST18 / power output: GST18

336.604	· 4 socket outlets with earthing contact, child-proof, black, set at 35°
336.606	· 4 child-proof French / UTE socket outlets, black, set at 35°
336.626	· 5 socket outlets with earthing contact, child-proof, black, set at 35°, length 305 mm



STEP ALU: Power socket outlets Length: approx. 220 mm (note special lengths)

Aluminium profile; power input: GST18 / power output: GST18

336.039	· 3 socket outlets with earthing contact, child-proof, black, set at 35°
336.067	· 3 socket outlets with earthing contact, child-proof, red, set at 35°
906.1075	· 3 child-proof French / UTE socket outlets, black, set at 35°, length 220 mm
336.046	· 4 child-proof French / UTE socket outlets, black, set at 35°, length 262.5 mm
336.072	· 3 child-proof French / UTE socket outlets, red IT, set at 35°
336.088	· 4 child-proof French / UTE socket outlets, red IT, set at 35°, length 262.5 mm
906.1086*	· 3 Swiss / CH socket outlets, black, set at 90°
906.1059*	· 3 UK 3.15 A individually fused, child-proof, black, set at 45°, length 314.5 mm
336.076	· 3 USA socket outlets, black, set at 0°, length 195 mm



STEP ALU: 1 x custom module + power socket outlets Length: approx. 220 mm

CUSTOM

Aluminium profile; power input: GST18 / power output: GST18

906.000	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
906.002	· 2 child-proof French / UTE socket outlets, black, set at 35°
906.071	· 2 Swiss / CH socket outlets, black, set at 90°
336.079	· 2 UK 3.15 A individually fused, child-proof, black, set at 45° (length 284.5 mm)



STEP ALU: 2 x custom modules + power socket outlets Length: approx. 262.5 mm

CUSTOM

Aluminium profile; power input: GST18 / power output: GST18

906.001	· 2 socket outlets with earthing contact, child-proof, black, set at 35°
906.009*	· 2 child-proof French / UTE socket outlet, black, set at 35°
906.080*	· 2 Swiss / CH socket outlets, black, set at 90°



STEP ALU: 1 x switch + power socket outlets Length: approx. 262.5 mm

Aluminium profile; Power input: GST18 / power output: GST18

906.003	· 3 x socket outlets with earthing contact, child-proof, black, set at 35° · Switch, switches sockets only (not power output)
906.031	· 3 x socket outlets with earthing contact, child-proof, black, set at 35° · Switch, switches sockets and power output



STEP ALU: 1 x USB double charger (5.2 V/2.15 A), 1 x custom module + power outlet sockets Length: approx. 262.8 mm

CUSTOM

USB CHARGER

Aluminium profile; power input: GST18 / power output: GST18

906.0113*	· 2 x socket outlets with earthing contact, child-proof, black, set at 35°
-----------	--



* No storage type

All STEP safety modules are compatible with STEP ALU and STEP BASE

See glossary for country-specific information. **Power cables and custom modules are available separately.**

Art. no. | Version

STEP ALU overvoltage protection, GST18 Length: approx. 147 mm

Aluminium profile; power input: GST18 / power output: GST18

336.003 | · Overvoltage protection unit, 2 kV, with function and fail indicator

STEP ALU overvoltage protection + mains and frequency filters, GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

336.004 | · Overvoltage protection unit, 2 kV, with function and fail indicator and mains filter 30 MHz

STEP ALU MCB, GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

336.015 | · Miniature circuit-breaker 16 A, 2-pole
· Characteristic B

STEP ALU RCD, GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

336.014 | · Residual current device 16 A, tripping current 30 mA, response time 30 ms, 2-pole

STEP ALU RCD, GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

906.067 | · Residual current device 16 A, tripping current 10 mA, response time 30 ms, 2-pole
· Power input: GST18i3 plug; power output: GST18i3 socket;

STEP ALU RCD/MCD GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

336.065 | · Combined RCD/MCD comprising:
- Residual current device 16 A, tripping current 30 mA, response time 30 ms, 2-pole
- Miniature circuit-breaker 16 A rated current, 400 V, 2-pole
· Characteristic B; 6 kA

STEP ALU Master & Slave, GST18 Length: approx. 220 mm

Aluminium profile; power input: GST18 / power output: GST18

336.006 | · Master & Slave circuit with threshold value setting 10 W and higher
· Effective power: 0.29 W / apparent power: 1.05 W

STEP ALU automatic switchoff Length: approx. 263 mm

Aluminium profile; power input: GST18 / power output: GST18

906.005 | · 1 x automatic switchoff with socket outlet
· 1 x button connection with 0.5 m cable and connector for linking to module 917.060



STEP accessories

Art. no.	Version
----------	---------

Fitting accessories

- | | |
|---------|---|
| 375.502 | <ul style="list-style-type: none"> Contents: - 4 screws 2.9 x 30 mm - 2 end cap cover strips to provide a visual finish (fitted on the end caps where two strips are linked together) - 1 end cap for power outlet socket |
|---------|---|

**Stainless steel mounting bracket**

- | | |
|---------|---|
| 940.096 | <ul style="list-style-type: none"> For insertion into the rear of a STEP profile Ideal for use with power strips with data connections 2 items |
|---------|---|

**Stainless steel mounting bracket with elongated hole**

- | | |
|---------|--|
| 940.024 | <ul style="list-style-type: none"> For insertion into the rear of a STEP profile With elongated hole (keyhole) for screwing into place, ideal for use with power strips with data connections 1 item left, 1 item right |
|---------|--|

**Stainless steel mounting plate, flat**

- | | |
|---------|---|
| 940.097 | <ul style="list-style-type: none"> For insertion into the rear of a STEP profile For screwing in place e.g. under a desk or table 2 items, packed in plastic bag |
|---------|---|

**STEP cover plates**

- | | |
|---------|---|
| 375.529 | <ul style="list-style-type: none"> For fitting over the end caps of STEP power strips For visual finish Plastic, black 2 items, packed in plastic bag |
|---------|---|

**Sheet steel mounting plate**

- | | |
|---------|--|
| 940.108 | <ul style="list-style-type: none"> For insertion into rear of STEP profile Tightening the nut on the threaded screw fixes the power strip in place Contents: - 1 mounting plate incl. M5 screw, washer and nut |
|---------|--|

**STEP plastic mounting clip**

- | | |
|---------|---|
| 918.025 | <ul style="list-style-type: none"> For mounting STEP BASE and STEP ALU power strips in suitable cut-outs in sheet steel (2.0 mm thickness) Contents: 2 plastic mounting clips, 4 screws 2.9 x 30 mm Drawings for the required cut-outs can be requested if required. |
|---------|---|

**For earthed power supply cable to STEP unit, see Accessories section**

- Pre-assembled power supply cables with integrated earth connection
- Earthing of the power strip is independent of the installation
- Ideal in combination with STEP power strips (starting on page 56)



Bachmann custom modules are the central components of video, audio and network connections. Their construction offers you simple and flexible installation in facility systems, rack systems and electrical installations. The versatility of custom modules make Bachmann facility systems even more flexible. With the easy-to-swap modules you can create units to meet the individual data, video and audio connection requirements of your customers quickly and simply.

Now Bachmann is also offering this flexibility for 10" and 19" panel installations. The standard custom modules facilitate the optimal configuration for every media and network connection requirement. Here also, socket/socket or screw-terminal connections provide great simplicity of installation.

When it comes to electrical installations, Bachmann custom modules are again an outstanding addition. The small number of parts make the custom modules compatible with the current switch ranges of reputable manufacturers. Simple fitting and removal mean that all installations can be quickly adapted to changed requirements and brought up to the current state of the art.

**The benefits
at a glance**

- Flexibly interchangeable modules
- For data, video and audio connections
- Can be used in facility systems, rack systems and electrical installations
- Integration with the switch ranges of leading manufacturers
- Easy to connect via socket/socket or screw terminals




Power strips



19" and 10" media racks




Electrical installations



CUSTOM MODULES

As versatile as your applications



The empty built-in frame ^① of Bachmann Facility systems accommodates the custom modules ^② which are fixed in place with two Torx screws ^③. The custom modules can be easily exchanged by loosening the screws.

Custom modules in the facility systems



Individual configuration


Modern technology and strong ideas are at the heart of each and every Bachmann facility system. With expansion-compatible multiple-socket outlets and facility custom modules for individual configuration, these systems provide the ideal basis for setting up flexible connections. Practical units provide secure networking in the office, while elegantly designed, concealed supply systems offer trouble-free communications for conferences. In addition to standard units factory-configured with sockets, Bachmann facility products also include empty modules that you can configure yourself. Custom modules are supplied complete with screws.



The greatest flexibility - prepared for the future

Whenever you change the configuration you have the opportunity to upgrade your equipment to the latest state of the art. Built-in insulation protects you from contact with live parts when exchanging modules. There is no requirement to recheck the electrical connections of the unit after changing modules, and the warranty is not affected. You can find facility system products in the main Bachmann catalogue and in the separate Facility Systems catalogue.

 Compatible with Bachmann facility systems




Our 19" and 10" racks^① accept custom modules^② which are simply inserted and screwed in. System integration is made easy with the open construction and socket/socket or screw-terminal custom modules.

Custom modules in the rack installation

Full integration of media and network technologies


The 19" and 10" panels offer simple and flexible integration of media and network technologies into your rack system. The custom modules, easily screwed into place (Torx M2 screws^③ included with the panels) enable you to respond to changes in system requirements at any time. Socket / socket and screw-terminal technology offers a compact and clearly arranged installation. The panels are particularly economical on space, requiring only one height unit (44.5 mm).



903.000 Bachmann 19" panel, 1 U, with strain-relief bar, accepts 10 custom modules (screws for mounting the modules included)

903.001 Bachmann 10" panel, 1 U, with strain-relief bar, accepts 5 custom modules (screws for mounting the modules included)

Compatible with Bachmann IT rack panel



Using a mounting plate ① and adapter frame ② (see page 66), custom modules ③ can be installed in a switch box.

Custom modules in the electrical installations

Unlimited installation options

The addition of a few extra components opens up whole new possibilities for electrical installations. Installed in either a switch box or sill-type trunking, the extensive range of custom modules allows the easy integration of audio, video and data networks. By using the standard 50 x 50 mm and 55 x 55 mm adapter frames, the custom modules form an optimal complement to the current switch ranges of reputable manufacturers. The connections to the rear can be made either as socket / socket or by means of screw terminals. No complicated soldering or cabling is required. A compatibility list of custom modules to the switch ranges of various manufacturers can be found on page 68 onwards.




917.064 mounting plate
(Suitable Torx M2 screws included)



Adapter frame, 50x50 mm and
55x55 mm in black and white



Mounting box for trunking (example)
You can obtain various mounting or device
boxes from trunking manufacturers



The mounting box is inserted into the trunking. On this base, the mounting plate ^① and adapter frame ^② (50x50 mm or 55x55 mm) and Bachmann custom module ^③ are bolted.

Bachmann custom modules ^③ can even be fitted into conventional floor boxes. The custom module holder ^④ for floor box systems allows the module to be fitted directly. There is thus no need for a mounting plate ^① or adapter frame ^②. The Bachmann custom module bracket ^④ is suitable for floor boxes from various manufacturers. Please check the installation depth required by the custom modules.



Compatible with Bachmann electrical installations

Manufac- turer *	Switch range *	Bachmann Adapter frame ** Colour black	Bachmann Adapter frame ** Colour white	+ Adapter manufacturer number
Berker	S.1	917.066	917.169	–
	B.1	917.066	917.169	–
	B.3	917.066	917.169	–
	B.7 Glass	917.066	917.169	–
	K.1	917.065	917.168	11087124 11087106 11087109 11087102
	K.5	917.065	917.168	11.087.104
	Arsys	917.065	917.168	11080101 11089104 11089111 11080169 11080102
	Module 2	917.065	917.168	114309 114302
Busch-Jaeger	carat	917.065	917.168	1746/10-81 1746/10-82 1746/10-84
	pure stainless steel	917.065	917.168	1746/10-866
	pulse	917.065	917.168	1746/10-71 1746/10-72 1746/10-74 1746/10-79 1746/10-777 1746/10-783
	solo	917.065	917.168	1746/10-82 1746/10-84 1746/10-85 1746/10-86 1746/10-87 1746/10-88 1746/10-803 1746/10-815
	Busch-axcent	917.065	917.168	1746/10-84
	future	917.065	917.168	1746/10-82 1746/10-84 1746/10-85 1746/10-89
	Future linear	917.065	917.168	1746/10-81 1746/10-82 1746/10-83 1746/10-84 1746/10-89
EGB	Elegant Standard	917.065	917.168	143.090.045
ELSO	JOY	917.065	917.168	363080 363084
	RIVA	917.065	917.168	203080 203084 2030831 2030811 2030819
	RIVA	917.066	917.169	203160 203164 2031611 2031619
	SCALA	917.065	917.168	203080 203084 2030811 2030819
	SCALA	917.066	917.169	203160 203164 2031611 2031619
	FASHION	917.065	917.168	203080 203084 203081 2030812 203082 2030831 203086 203089 2030844
	FASHION	917.066	917.169	203160 203164 203160D
	NOVIA	917.066	917.169	284800 284804
	NOVIA	917.065	917.168	283160 283164 2831631 2831612 283166 283169 2.831.611
	CLASSIC	917.065	917.168	303110 303111
Gira	Standard 55	917.066	917.169	–
	E2	917.066	917.169	–
	Event	917.066	917.169	–
	Esprit	917.066	917.169	–
	E22	917.066	917.169	0.289.202
	Stainless steel series 20/21	917.066	917.169	028.920
	TX_44	917.066	917.169	028966 028967 028965
	Surface switch	917.066	917.169	0289111 0289112
	S-Color	917.065	917.168	028240 028242 028243 028246 028247
Jäger	Opus	917.065	917.168	560.050.02
Jung	AS 500	917.066	917.169	–
	AS Universal	917.066	917.169	–
	A 500	917.066	917.169	–
	A plus	917.066	917.169	–
	A creation	917.066	917.169	–
	LS-design	917.066	917.169	AL2961Z5-L ES2961Z5-L
	LS 990	917.066	917.169	LS961Z5WW LS961Z5SW LS961Z5AL
	LS plus	917.066	917.169	AL2961Z5-L ES2961Z5-L

* Name and product designation of respective manufacturer


** To install in the switch range, please also order the appropriate Bachmann adapter frame.

Manufac- turer *	Switch range *	Bachmann Adapter frame ** Colour black	Bachmann Adapter frame ** Colour white	+ Adapter manufacturer number
Jung	FD-design	917.066	917.169	AL2961Z5-L ES2961Z5-L
	CD 500	917.065	917.168	590ZCD 590ZWW
	LS 990	917.065	917.168	LS961Z LS961ZWW LS961ZLG LS961ZSW
	LS 990	917.065	917.168	LS961Z5 LS961Z5WW LS961Z5SW
	Aluminium	917.065	917.168	LS961Z LS961ZWW LS961ZLG LS961ZSW
	Aluminium	917.066	917.169	LS961Z5 LS961Z5WW LS961Z5SW AL2961Z5-L ES2961Z5-L
	Stainless steel	917.065	917.168	LS961Z LS961ZWW LS961ZLG LS961ZSW
	Stainless steel	917.066	917.169	LS961Z5 LS961Z5WW LS961Z5SW AL2961Z5-L ES2961Z5-L
	Anthracite	917.065	917.168	LS961Z LS961ZWW LS961ZLG LS961ZSW
	Anthracite	917.066	917.169	LS961Z5 LS961Z5WW LS961Z5SW AL2961Z5-L ES2961Z5-L
	Bright chrome	917.065	917.168	LS961Z LS961ZWW LS961ZLG LS961ZSW
	Bright chrome	917.066	917.169	LS961Z5 LS961Z5WW LS961Z5SW AL2961Z5-L ES2961Z5-L
Merten	1-M	917.066	917.169	–
	ATELIER-M	917.066	917.169	–
	M-SMART	917.066	917.169	–
	M-PLAN	917.066	917.169	–
	M-PLAN GLASS	917.066	917.169	–
	M-PLAN Metal	917.066	917.169	–
	M-PLAN II	917.066	917.169	–
	M-ARC	917.066	917.169	–
	M-STAR	917.066	917.169	–
	ARTEC	917.065	917.168	516094 516099
	AQUADESIGN	917.065	917.168	518344 518319 518314 518360
PEHA	Standard	917.066	917.169	219511 219611
	Standard	917.065	917.168	219411 219211 219711 219311 218711
	Dialog	917.065	917.168	828611 819511 768611 847311 838011 778611 316611
	Aura	917.065	917.168	117211 129511 155811
	Nova	917.065	917.168	027211 042211 057211
	Nova	917.066	917.169	100511 100711 100611
POPP	FOREVER	917.065	917.168	729828 729811
	PALLAS	917.065	917.168	729842 729866 729859
	ARCADA	917.065	917.168	–
Presto-Vedder	Regina classic	917.065	917.168	730RW 730RUW
	Alessa	917.065	917.168	230RUW
	Alessa plus	917.065	917.168	230RUW
	Fiorena	917.065	917.168	3030RUW 3030RW 3030RSI 3030RSGR
Siemens	DELTA line	917.065	917.168	5TG2557 5TG2587 5TG1160 5TG1150
	DELTA vita	917.065	917.168	5TG2557 5TG1160 5TG1150
	DELTA miro	917.065	917.168	5TG2557 5TG2587 5TG1160 5TG1150
	DELTA style	917.065	917.168	5TG1326 5TG1326-1 5TG1366
	DELTA style	917.066	917.169	5TG1327 5TG1327-1 5TG1367
	DELTA profile	917.065	917.168	5TG1806 5TG1866 5TG1766 5TG1836 5TG1706-1 5TG1746-1
	DELTA profile	917.066	917.169	5TG1893 5TG1885 5TG1762 5TG1835 5TG1705-1 5TG1745-1

* Name and product designation of respective manufacturer

** To install in the switch range, please also order the appropriate Bachmann adapter frame.

Switch range



Art. no. | Version

Custom module mounting plate for switch range**Stainless steel**

917.064

- Stainless steel mounting plate suitable for conventional devices, for flush mounted, cavity and device boxes for trunking
- Incl. 2 Torx M2 screws
- An extra mounting box is needed for trunking (see manufacturer's range)

**Adapter frame for switch range****Plastic**

917.065

- 50 x 50 mm
- Black
- Fits into conventional switch ranges (50 x 50 mm internal dimensions) in conjunction with the stainless steel mounting plate 17.064
- Please check the compatibility list from page 68 onwards

**Adapter frame for switch range****Plastic**

917.168

- 50 x 50 mm
- White RAL 9010
- Fits into conventional switch ranges (50 x 50 mm internal dimensions) in conjunction with the stainless steel mounting plate 17.064
- Please check the compatibility list from page 68 onwards

**Adapter frame for switch range****Plastic**

917.066

- 55 x 55 mm
- Black
- Fits into conventional switch ranges (55 x 55 mm internal dimensions) in conjunction with the stainless steel mounting plate 17.064
- Please check the compatibility list from page 68 onwards

**Adapter frame for switch range****Plastic**

917.169

- 55 x 55 mm
- White RAL 9010
- Fits into conventional switch ranges (55 x 55 mm internal dimensions) in conjunction with the stainless steel mounting plate 17.064
- Please check the compatibility list from page 68 onwards

Floor boxes

Art. no. | Version

Floor box mounting 2 x**Sheet steel****2 x custom modules**

- 917.068
- For fitting in OBO Bettermann device case / floor-box systems
 - Accepts 3 custom modules (transverse mounting)
 - Incl. 2 Torx M2 screws

**Floor box mounting 3 x****Sheet steel****3 x custom modules**

- 917.067
- For fitting in OBO Bettermann device case / floor-box systems
 - Accepts 3 custom modules (transverse mounting)
 - Incl. 2 Torx M2 screws

**Floor box mounting 2 x****Plastic black****2 x custom modules**

- 917.139
- Mounting for Electraplan floor boxes
 - Accepts 2 custom modules (transverse mounting)
 - Incl. Torx M2 screws for custom modules

**Floor box mounting 3 x****Plastic black****3 x custom modules**

- 917.140
- Mounting for Electraplan floor boxes
 - Accepts 3 custom modules (transverse mounting)
 - Incl. Torx M2 screws for custom modules




Media racks/IT panels


Art. no. | Version

10" custom module panel 1 U Black anodised aluminium

- 903.001
- Accepts up to 5 custom modules
 - Incl. fixing accessories and Torx M2 screws

**19" custom module panel 1 U Black anodised aluminium**

- 903.000
- Accepts up to 10 custom modules
 - Incl. fixing accessories and Torx M2 screws



Modules for Keystone data connections

· All modules are supplied with 2 Torx T6 screws.



Art. no. | Version

2 x Keystone modules

- | | |
|---------|---|
| 917.000 | <ul style="list-style-type: none"> · Module, black, accepts 2 data sockets with Keystone fitting · Suitable for the data sockets listed below |
| 917.158 | <ul style="list-style-type: none"> · Module, white, accepts 2 data sockets with Keystone fitting · Suitable for the data sockets listed below |

**1 x Keystone module**

- | | |
|---------|--|
| 917.001 | <ul style="list-style-type: none"> · Module, black, accepts 1 data socket with Keystone fitting · Suitable for the data sockets listed below |
| 917.159 | <ul style="list-style-type: none"> · Module, white, accepts 1 data socket with Keystone fitting · Suitable for the data sockets listed below |

**2 x Keystone module with metal holder**

- | | |
|---------|---|
| 917.061 | <ul style="list-style-type: none"> · Module, black, accepts 2 data sockets with Keystone fitting · Keystone fitting with metal holder on rear of cover for high mechanical stresses · Suitable for the data sockets listed below |
|---------|---|

**1 x Keystone module with metal holder**

- | | |
|---------|--|
| 917.062 | <ul style="list-style-type: none"> · Module, black, accepts 1 data socket with Keystone fitting · Keystone fitting with metal holder on rear of cover for high mechanical stresses · Suitable for the data sockets listed below |
|---------|--|

Data connections for custom modules 917.000, 917.001, 917.061 and 917.062

Socket / socket (Suitable data cables can be found in the accessories)

Art. no. | Version

**CAT6 coupling socket/socket**

- | | |
|---------|--|
| 940.044 | <ul style="list-style-type: none"> · Type: BTR E-DAT · Front: RJ45 (Keystone fitting), rear: RJ45 (E-DAT mounting) · Shielded |
|---------|--|

**CAT6 coupling / socket/socket**

- | | |
|---------|---|
| 940.083 | <ul style="list-style-type: none"> · Front: RJ45 (Keystone fitting), rear: RJ45 (Keystone fitting) · Shielded |
|---------|---|

**CAT6 coupling socket/socket**

- | | |
|---------|---|
| 940.112 | <ul style="list-style-type: none"> · Front: RJ45 (Keystone fitting), rear: RJ45 (Keystone fitting) · Unshielded |
|---------|---|

**CAT5e coupling socket / socket**

- | | |
|---------|---|
| 940.057 | <ul style="list-style-type: none"> · Front: RJ45 (Keystone fitting), rear: RJ45 (Keystone fitting) · Shielded |
|---------|---|

**ISDN RJ12 socket / socket**

- | | |
|---------|---|
| 940.085 | <ul style="list-style-type: none"> · Front: RJ12 (Keystone fixing), rear: RJ12 (Keystone fixing) · Unshielded |
|---------|---|


**Keystone socket cover**

- | | |
|---------|--|
| 917.057 | <ul style="list-style-type: none"> · Socket cover, clips into an empty Keystone socket · Can be used as a place holder for sockets inserted subsequently · Suitable for 917.000 / 917.001 / 917.061 / 917.062 |
|---------|--|

Data connections for custom modules 917.000, 917.001, 917.061 and 917.062

Socket/supply cable

Art. no.	Version
CAT6a 10GB Patch cable plug / socket 3.0m	
918.033	- Front: Socket RJ45 CAT6a TKM 10GB - Cable, black, with RJ45 plug
	Shielded
CAT6a 10GB Patch cable plug / socket 5.0m	
918.034	- Front: Socket RJ45 CAT6a TKM 10GB - Cable, black, with RJ45 plug
	Shielded
CAT6a 10GB socket TKM	
918.035	- CAT6a connector socket TKM 10GB - Without cable (designed for tool-free connection of data cable)
	Shielded
Shutter RJ 45	
930.143	- Cover for Keystone custom module - Does not require tools - Suitable for custom modules 917.000/917.001/917.051/917.052 - With paper strips for inscriptions - Universally suits 1 and 2 data connections
	Ideal as dust cover for data socket contacts when not in use



Keystone connections for media technology

Art. no.	Version
Custom module 1 x HDMI Keystone	
918.040	- Front: HDMI socket - Rear: HDMI socket, without cable - Fits into Keystone frame 917.000 or 917.001
	Requires approx. 85 mm installation depth
Custom module 1 x mini stereo jack 3.5 mm Keystone	
917.157	- Front: 3.5 mm mini stereo jack socket - Rear: Mini stereo jack socket with approx. 0.1 m cable - Fits into Keystone frame 917.000 or 917.001
	Requires approx. 65 mm installation depth
Custom module 1 x USB 3.0 A / A Keystone	
917.120	- Front: USB A socket - Rear: USB A socket - Fits into Keystone frame 917.000 or 917.001 (see page 72)
	Requires approx. 85 mm installation depth



OWG connections

Art. no. | Version

OWG - LC duplex Keystone

- 918.071 | · OWG-LC duplex coupling
 ■ ■ ■ | · Keystone fixing

OWG - ST duplex Keystone

- 918.073 | · OWG-ST duplex coupling
 ■ ■ ■ | · Keystone fixing

TOSLINK Keystone

- 918.045 | · TOSLINK optic fibre audio coupler
 ■ ■ ■ | · Keystone fixing

OWG - SC Keystone

- 918.072 | · OWG-SC coupling
 ■ ■ ■ | · Keystone fixing

OWG-MT-RJ Keystone

- 918.074 | · OWG-MT-RJ coupling
 ■ ■ ■ | · Keystone fixing

Cable feedthroughs

Module 1 x data cable feedthrough

- 917.032 | · Module with drill hole and 2-part cable bushing for data cables up to 11 mm in diameter
 ■ ■ ■

**Module 1 x VGA cable feedthrough**

- 917.033 | · 1 x 2-part cable bushing, ideal for routing VGA cables, without cables.
 ■ ■ ■ | · Suits cables up to 24 mm diameter



Modules for data connections

· All modules are supplied with 2 Torx T6 screws.

BTR**

- E-DAT module CAT6a 8(8)
- E-DAT module coupling 8(8) CAT6

DAETWYLER**

- unilan MS 1/8 CAT6 RJ45
- unilan RJ45 feedthrough coupling CAT6
- unilan MU 1/8 CAT6 RJ45

KERPEN**

- VarioKeystone socket module RJ45

Module 2 x BTR E-DAT module CAT6

- 917.038 | · Module with cut-out and mounting module for 2 x BTR E-DAT module CAT6 (not included)
 ■ ■ ■ | · Also suitable for Daetwyler Unilan module MS 1-8

Module 1 x BTR E-DAT module CAT6

- 917.006 | · Module with cut-out and mounting module for 1 x BTR E-DAT module CAT6 (not included)
 ■ ■ ■ | · Also suitable for Daetwyler Unilan module MS 1-8

Module 1 x Systimax CAT6

- 917.003 | · Module with cut-out and mounting plate for 1 x Systimax CAT6 MGS500 and MGS400 series
 ■ ■ ■ | (not included)



Modules for data connections

· All modules are supplied with 2 Torx T6 screws.

Art. no.	Version
Module 1 x RDM CAT6	
917.005	- Module with cut-out and mounting plate for 1 x Reichle de Masari (RDM) CAT6 (not included)
Module 1 x BKS	
917.153	- Module with cut-out for BKS (RJ, RJ250, RJUTP, RJpro and MMC3000pro) data connections in conjunction with mounting clip 403-7540xx (not included). - Also suitable for Kerpen ELine 1200 C7 socket with help of ELine EC7 adapter clip LKD9ZE300210000), not included in scope of supply.
Module Nexans 2 x	
917.052	- Module, black, with cut-out for 2 Nexans LAN-mark-6 CAT6 (clips in with Keystone Clip Nexans) - Data socket and Keystone clip available separately
Module Nexans 1 x	
917.051	- Module, black, with cut-out for 1 Nexans LAN-mark-6 CAT6 (clips in with Keystone Clip Nexans) - Data socket and Keystone clip available separately
Module 1 x Panduit CAT6	
917.007	Module with cut-out and mounting plate (black) for 1 x Panduit CAT6 (not included)
Module 1 x Corning CAT6	
917.002	- Module with cut-out and mounting plate (black) for 1 x Tera CAT6 S250 (not included) - Suitable for Corning modules: S500 module / CAXASM-00104-C001, S500 fx / CAXASM-00104-C002, S10 ten / CAXTSM-00112-C001, S10 ten fx / CAXTSM-00112-C004, S250 module / CAXESM-00100-C001, S250 fx / CAXESM-00100-C004, S100 eL / CAXGSM-00100-C001, S100 e / CAXDSM-00100-C001
Module 2 x CAT7 Tera	
917.039	- Module with cut-out and mounting plate (black) for 2 x Tera CAT7 (not included) - DAETWYLER unilan PS 1/8 CAT7, CORNING S1200 module S1200 shielded CAT7 +
Module 1 x CAT7 Tera	
917.008	- Module with cut-out and mounting plate (black) for 1 x Tera CAT7 (not included) - DAETWYLER unilan PS 1/8 CAT7, CORNING S1200 module S1200 shielded CAT7 +



Manufacturer	917.000	917.001	917.061	917.062	917.038	917.006	917.003	917.002	917.051	917.052	917.053	917.008	917.038	917.007	917.005
Bachmann versions															
CAT6 coupling, shielded 940.044	x	x			x	x									
CAT6 coupling, unshielded 940.112	x	x	x	x											
CAT5e coupling 940.057	x	x	x	x											
ISDN RJ12 socket unshielded	x	x	x	x											
CAT6a 10GB socket TKM, shielded, for automatic telephone 918.035	x	x	x	x											
CAT6a 10GB socket TKM, shielded, with 3.0 m cable and RJ45 plug / 918.033	x	x	x	x											
CAT6a 10GB socket TKM, shielded, with 5.0 m cable and RJ45 plug / 918.034	x	x	x	x											
Socket cover / blank cover Keystone black / 917.057	x	x	x	x											
RJ45 shutter / 930.143	x	x													
OWG - LC duplex Keystone / 918.071	x	x	x	x											
OWG-SC Keystone / 918.072	x	x	x	x											
OWG-ST Keystone / 918.073	x	x	x	x											
OWG-MT-RJ Keystone / 918.074	x	x	x	x											
TOSLINK Keystone / 918.045	x	x	x	x											
Tyco Electronics / AMP NETCONNECT*															
SL series 110Connect jacks CAT6	X	x	x	x											
SL series 110Connect jacks CAT5e	X	x	x	x											
SL series 110Connect jacks CAT3	X	x	x	x											
SL series toolless jacks CAT5e	x	x	x	x											
SL series toolless jacks CAT3	x	x	x	x											
Modular telephone coupler RJ45 / RJ11 coupler	x	x	x	x											
AMP-TWIST-6S SL jack CAT6	x	x	x	x											
Standard 110Connect jacks CAT5e		x		x											
Standard 110Connect jacks CAT3 RJ45 / RJ11		x		x											
AMP-TWIST 6AS SL RJ45 jack	x	x	x	x											
ADC KRONE*															
KM8 RJ45 Modular Keystone shielded		x		x											
KM8 RJ45 Modular Keystone unshielded		x		x											
BELDEN*															
Giga Flex Keystone	x	x	x	x											
Giga Flex MDVO	x	x	x	x											
BKS* (can be used with mounting clip 403-7540xx (not included))															
RJ, RJ250, RJUTP, RJpro and MMC3000pro											x				

*Name and product designation of respective manufacturer

Manufacturer	917.000	917.001	917.061	917.062	917.038	917.006	917.003	917.002	917.051	917.052	917.053	917.008	917.038	917.007	917.005
BRAND-REX*															
10GPLUS jack shielded	x	x	x	x											
Augmented category 6 shielded tool-free jack / AC6JAKS000	x	x	x	x											
CAT5e GIGAPlus jack 110 IDC 568		x		x											
CAT6 Keystone plus		x		x											
CAT6 Keystone snap in	x	x	x	x											
CAT6 Plus		x		x											
Cat6Plus shielded module / C6CJAKS000CR	x	x	x	x											
Category 6 shielded tool-free jack 7 C6CJAKS000	x	x	x	x											
BTR**															
C6A module 180° / 130B11-E					x	x									
E-DAT module CAT6a 8(8)					x	x									
E-DAT module coupling 8(8) CAT6 1309A0-I	x	x	x	x	x	x									
E-DAT module coupling 8(8) CAT6 1309A0-I					x	x									
UTP module CAT5e / 130A08-I / 130A08-I-B1	x	x	x	x											
UAE module CAT5e unshielded 130908-	x	x	x	x											
UAE module CAT6 130909-I / 130909-I-B1					x	x									
UTP module 8 (8) CAT6 / 130A10-I / 130A10-29-I / 130A10-29-I-B1	x	x	x	x											
CIMABOX*															
CAT5e and CAT6 Keystone CJ545U / CJ545F	x	x	x	x											
Shielded and unshielded CJ645U / CJ645F	x	x	x	x											
COBINET*															
Patch cable coupling TopConnect RJ45			x	x											
RJ45 module TopKey			x	x											
CORNING*															
S10 TEN / CAXTSM-00112-C001								x							
S10 TEN fx / CAXTSM-00112-C004								x							
S100 e / CAXDSM-00100-C001								x							
S100 eL / CAXGSM-00100-C001								x							
S1200 module S1200 shielded CAT7 / CAXFSM-00100-C001												x	x		
S250 fx / CAXESM-00100-C004								x							
S250 module / CAXESM-00100-C001								x							
S500 fx / CAXASM-00104-C002								x							
S500fx module / CAXBSM-00104-C002	x	x	x	x											
S500 module / CAXBSM-00104-C001	x	x	x	x											
S500 module / CAXASM-00104-C001								x							

*Name and product designation of respective manufacturer

Manufacturer	917.000	917.001	917.061	917.062	917.038	917.006	917.003	917.002	917.051	917.052	917.053	917.008	917.038	917.007	917.005
DAETWYLER**															
unilan RJ45 coupling CAT6 417 446	x	x	x	x											
unilan module KS 1 / 8 CAT6 RJ45 418 050	x	x	x	x											
unilan module KS 1 / 8 CAT5e RJ45 418 051	x	x	x	x											
unilan module KST 1 / 8 toolless CAT6 RJ45 418 053	x	x	x	x											
unilan module KU 1 / 8 CAT6 418 080	x	x	x	x											
unilan module KU 1 / 8 CAT6 418 081	x	x	x	x											
unilan module KU 1 / 8 CAT5e 418 082	x	x	x	x											
unilan module KU 1 / 8 CAT5e 418 083	x	x	x	x											
unilan® module PS-GG45 7A 1000 MHz 400 102 + 400 103****		x		x											
unilan® module KS-T 6A 1/8 tool-less cat. 6A/EA shielded 418 060	x	x	x	x											
unilan® module KS-TS 6 1/8 tool-less slimline cat.6/EA shielded 418 054	x	x	x	x											
unilan® RJ45 Keystone coupler CAT6 / 418 057	x	x	x	x											
unilan® module KS-T5 1/8 tool-less cat. 5e shielded / 418 055	x	x	x	x											
unilan® RJ45 module MS-K 1/8 cat.6a shielded - modular solution 440 001	x	x	x	x											
unilan® module MS-K Plus 1/8 cat. 6A shielded 440 004	x	x	x	x											
unilan MS 1 / 8 CAT6 RJ45					x	x									
unilan RJ45 feedthrough coupling CAT6					x	x									
unilan MU 1 / 8 CAT6 RJ45					x	x									
unilan PS 1 / 8 CAT7												x	x		
	x	x	x	x											
EFB ECOLAN*															
E-20050	x	x	x	x											
E-20051	x	x	x	x											
E-20060	x	x	x	x											
E-20061	x	x	x	x											
37.486.1	x	x	x	x											
37.488.1	x	x	x	x											
37.508.2	x	x	x	x											
		x		x											
ERSYS*															
CAT5C-SIJ-FKey-002		x		x											
Ersys 356k-8c5e		x		x											
Ersys 628MC-8-C5E		x		x											
	x	x	x	x											
GIGAMEDIA*															
RJ45 CAT6 UTP / STP	x	x	x	x											
RJ45 CAT6 contacts 110 UTP / STP	x	x	x	x											
RJ45 CAT5e UTP / STP	x	x	x	x											
3M*															
Volition RJ45 K6 module without shielding cover*		x		x											


*Name and product designation of respective manufacturer

Manufacturer	917.000	917.001	917.061	917.062	917.038	917.006	917.003	917.002	917.051	917.052	917.053	917.008	917.038	917.007	917.005
KERPEN*															
Eline 250 MLS RJ45 shielded	x	x	x	x											
Eline 250 MLS RJ45 unshielded	x	x	x	x											
ELine 600® GG45 socket / 9ZE20001	x	x	x	x											
VarioKeystone socket module RJ45					x	x									
	x	x	x	x											
NEXANS* (can only be fitted with additional Keystone clip)															
LANmark-5 snap-in EVO									x	x					
LANmark-6 EVO RJ45 snap-in									x	x					
LANmark-6 10G snap-in									x	x					
LANmark-7 GG45 snap-in									x	x					
					x	x									
Panduit*															
Mini-Com® Mini-Jack™ category 3 UTP jack modules														x	
Mini-Com® TX5e™ keyed shielded jack modules														x	
Mini-Com® category 6 UTP coupler module														x	
Reichle de Masari*															
RDM CAT6															x
RUTENBECK*															
UM-real.cat.6a A	x	x	x	x											
	x	x	x	x											
SETEC*															
CAT6 modular Keystone jack shielded	x	x	x	x											
SeSix eXtra Keystone jack XKJ	x	x	x	x											
SeSix universal Keystone jack UKJ	x	x	x	x											
SeSix modular Keystone jack MKJ	x	x	x	x											
SYSTIMAX*															
MGS500 CAT6 series							x								
MGS400 series							x								
								x							
TELEGÄRTNER*															
AMJ module K CAT6+	x	x													
AMJ coupling K CAT6	x	x													
AMJ coupling K CAT5e	x	x													
	x	x	x	x											
TKM*															
RJ-MOD - cat. 6 / 4677682	x	x	x	x											
GG45 / 4677701 (can be fitted with Keystone clip)	x	x	x	x											

* Name and product designation of respective manufacturer

Video and audio modules

See the glossary for detailed information on use/application



Art. no. | Version

Custom module 1 x VGA + mini stereo jack**Black**

917.045

- Front: VGA socket and mini stereo jack
- Rear: VGA socket and mini stereo jack with approx. 0.1 m cable
- Requires approx. 70 mm installation depth

**Custom module 1 x VGA + mini stereo jack****Black**

917.071

- Front: VGA socket and mini stereo jack
- Rear: 10-pole (VGA) and 3-pole (stereo) screw terminal
- Requires approx. 50 mm installation depth

**Custom module 1 x VGA + mini stereo jack****White**

917.160

- Front: VGA socket and mini stereo jack
- Rear: 10-pole (VGA) and 3-pole (stereo) screw terminal
- Requires approx. 50 mm installation depth

**Custom module 1 x VGA + mini stereo jack****Black**

917.073

- Front: VGA socket and mini stereo jack
- Rear: 5 x BNC socket with approx. 0.3 m cable (VGA) and 3-pole (stereo)
- Requires approx. 50 mm installation depth

**Custom module 1 x VGA + mini stereo jack****Black**

917.150

- Front: VGA socket and mini stereo jack
- Rear: VGA + mini stereo jack socket, each with approx. 0.2 m cable
- Requires approx. 50 mm installation depth

**Custom module 1 x VGA + mini stereo jack and button for MediaNet switch****Black**



917.134

- Front: VGA socket and mini stereo jack + button, blue illuminated
- Rear: VGA socket and mini stereo jack with approx. 0.1 m cable + RJ12 socket for button
- Requires approx. 70 mm installation depth



All modules are supplied with 2 Torx T6 screws. For suitable cables see the Accessories section

Art. no.	Version	
Custom module 1 x VGA + mini stereo jack and button for MediaNet switch		Black
917.074	- Front: VGA socket and mini stereo jack + button, blue illuminated - Rear: 10-pole (VGA) and 3-pole (stereo) screw terminal + micro clamp terminal (button) - Requires approx. 50 mm installation depth	 
Custom module 1 x VGA + mini stereo jack and button for MediaNet switch		Black
917.077	- Front: VGA socket and mini stereo jack + button, blue illuminated - Rear: 5 x BNC socket with approx. 0.3 m cable (VGA) and 3-pole (stereo) + micro clamp terminal (button) - Requires approx. 50 mm installation depth	 
Custom module 1 x VGA		Black
917.011	- Front: VGA socket - Rear: VGA socket - Requires approx. 70 mm installation depth	 
Custom module 1 x VGA		Black
917.069	- Front: VGA socket - Rear: 10-pole screw terminal (VGA) - Requires approx. 50 mm installation depth	 
Custom module 1 x VGA		Black
917.070	- Front: VGA socket - Rear: 5 x BNC socket with approx. 0.3 m cable (VGA) - Requires approx. 35 mm installation depth	 
Custom module 1 x VGA		Black
917.072	- Front: VGA plug - Rear: 10-pole screw terminal (VGA) - Requires approx. 50 mm installation depth	 



Video and audio modules

See the glossary for detailed information on use/application

Front

Rear

Art. no.

Version

**Custom module 1 x DVI-I + mini stereo jack****Black**

917.021



- Front: DVI-I socket and mini stereo jack
- Rear: DVI-I socket and mini stereo jack, each with approx. 0.1 m cable
- Requires approx. 75 mm installation depth

**Custom module 1 x DVI-I****Black**

917.078



- Front: DVI-I socket
- Rear: DVI-I socket with approx. 0.1 m cable
- Requires approx. 75 mm installation depth

**Custom module 1 x HDMI Keystone****Black**

918.040



- Front: HDMI socket
- Rear: HDMI socket, without cable
- Fits into Keystone frame 917.000 or 917.001
- Requires approx. 85 mm installation depth

**Custom module 1 x HDMI****Black**

917.143



- Front: HDMI socket
- Rear: 2 x 9-pole screw terminal (HDMI)
- Requires approx. 40 mm installation depth

**Custom module 1 x HDMI****White**

917.183



- Front: HDMI socket
- Rear: 2 x 9-pole screw terminal (HDMI)
- Requires approx. 40 mm installation depth

**Custom module 1 x display port****Black**

917.145



- Front: Display port socket
- Rear: Display port socket, without cable
- Requires approx. 70 mm installation depth

Video and audio modules


See the glossary for detailed information on use/application

Art. no.	Version		Front	Rear
Module 1 x video + Cinch stereo BVM-1				
917.026	- Front: Cinch video (yellow) + Cinch stereo (red + white) socket - Rear: Cinch socket without cable	Black		
Custom module 1 x Cinch video + stereo				
917.085	- Front: Cinch video (yellow) + Cinch stereo (red + white) socket - Rear: 10-pole screw terminal (VGA) - Requires approx. 50 mm installation depth	Black		
Custom module 1 x Cinch video + stereo				
917.161	- Front: Cinch video (yellow) + Cinch stereo (red + white) socket - Rear: 10-pole screw terminal (VGA) - Requires approx. 50 mm installation depth	White		
Module 1 x VBNC + Cinch stereo				
917.027	- Front: BNC video (yellow) + Cinch stereo (red + white) socket - Rear: BNC + Cinch socket without cable	Black		
Module 1 x S-video + Cinch stereo				
917.028	- Front: S-video (S-VHS) + Cinch stereo (red + white) socket - Rear: S-video + Cinch socket without cable	Black		
Custom module 1 x S-video + Cinch stereo				
917.081	- Front: S-video + Cinch stereo (red + white) socket - Rear: 4-pole (S-video) + 3-pole (stereo) screw terminal - Requires approx. 30 mm installation depth	Black		
Custom module 1 x S-video + Cinch stereo				
917.162	- Front: S-video + Cinch stereo (red + white) socket - Rear: 4-pole (S-video) + 3-pole (stereo) screw terminal - Requires approx. 30 mm installation depth	White		

Video and audio modules

See the glossary for detailed information on use/application

Front Rear



Art. no. | Version

Module 1 x S-video + Cinch stereo**Black**

- 917.035
- Front: S-video socket (S-VHS) + Cinch video socket (yellow)
 - Rear: S-video + video socket without cable

**Custom module 1 x S-video + Cinch video****Black**

- 917.083
- Front: S-video + Cinch video socket (yellow)
 - Rear: 4-pole screw terminal (S-video) + approx. 0,3 m cable with 2 x BNC (stereo)
 - Requires approx. 30 mm installation depth

**Custom module 1 x BNC R / G / B****Black**

- 917.088
- Front: BNC R / G / B socket (red / green / blue)
 - Rear: 6-pole screw terminal
 - Requires approx. 30 mm installation depth

**Custom module 1 x BNC R / G / B****Black**

- 917.090
- Front: BNC R / G / B socket (red / green / blue)
 - Rear: BNC R / G / B socket (red / green / blue)
 - Requires approx. 65 mm installation depth

**Custom module 1 x sat / TV / radio****Black**

- 917.030
- Front: F-plug connector (sat) and 2 x coax (TV + radio)
 - Rear: F-plug connector (sat) and 2 x coax (TV + radio)
 - Requires approx. 50 mm installation depth

**Custom module 1 x TV / radio****Black**

- 917.117
- Front: 2 x COAX (TV + radio)
 - Rear: 2 x COAX (TV + radio)
 - Requires approx. 50 mm installation depth

**Custom module 1 x Cinch stereo****Black**

- 917.022
- Front: Cinch stereo socket (red + white)
 - Rear: Cinch stereo socket (red + white) without cable
 - Requires approx. 55 mm installation depth



Video and audio modules

See the glossary for detailed information on use/application

Art. no.	Version		Front	Rear
Custom module 1 x Cinch stereo			Black	
917.089	- Front: Cinch stereo socket (red + white) - Rear: 3-pole screw terminal (stereo) - Requires approx. 35 mm installation depth			
Custom module 1 x Cinch stereo			White	
917.163	- Front: Cinch stereo socket (red + white) - Rear: 3-pole screw terminal (stereo) - Requires approx. 35 mm installation depth			
Custom module 1 x mini stereo jack 3.5 mm			Black	
917.023	- Front: 3.5 mm mini stereo jack socket (red + white) - Rear: Cinch stereo socket (red + white) - Requires approx. 65 mm installation depth			
Custom module 1 x mini stereo jack 3.5 mm Keystone			Black	
917.157	- Front: 3.5 mm mini stereo jack socket - Rear: Mini stereo jack socket with approx. 0.1 m cable - Fits into Keystone frame 917.000 or 917.001 - Requires approx. 65 mm installation depth			
Custom module 1 x mini stereo jack 3.5 mm			Black	
917.091	- Front: 3.5 mm mini stereo jack socket - Rear: 3-pole screw terminal - Requires approx. 35 mm installation depth			
Custom module 1 x mini stereo jack 3.5 mm			White	
917.164	- Front: 3.5 mm mini stereo jack socket - Rear: 3-pole screw terminal - Requires approx. 35 mm installation depth			
Custom module 1 x mini stereo jack 6.3 mm stereo			Black	
917.036	- Front: 6.3 mm stereo jack socket - Rear: Cable approx. 0.1 m with jack socket 6.3 mm - Requires approx. 65 mm installation depth			

Audio modules

See the glossary for detailed information on use/application

Front

Rear



Art. no.

Version

Custom module 1 x XLR microphone 3-pole**Black**

917.024

- Front: XLR 3-pole microphone socket
- Rear: Cable approx. 0.1 m with XLR plug 3-pole
- Requires approx. 65 mm installation depth

**Custom module 1 x XLR socket 3-pole****Black**

917.096

- Front: XLR 3-pole socket
- Rear: 3-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x XLR socket 3-pole****White**

917.165

- Front: XLR 3-pole socket
- Rear: 3-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x XLR socket 4-pole****Black**

917.099

- Front: XLR 4-pole socket
- Rear: 4-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x XLR socket 5-pole****Black**

917.101

- Front: XLR 5-pole socket
- Rear: 5-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x XLR plug 3-pole****Black**

917.095

- Front: XLR 3-pole plug
- Rear: 3-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x XLR plug 4-pole****Black**

917.098




- Front: XLR 4-pole plug
- Rear: 4-pole screw terminal
- Requires approx. 40 mm installation depth



Audio modules

See the glossary for detailed information on use/application


Art. no.	Version	
Custom module 1 x XLR plug 5-pole		Black
917.100	· Front: XLR 5-pole plug · Rear: 5-pole screw terminal · Requires approx. 40 mm installation depth	 
Custom module Combo series 1 x XLR socket 3-pole + 1 x 6.3 mm jack socket		Black
917.094	· Front: XLR socket 3-pole + 6.3 mm stereo jack socket · Rear: 2 x 3-pole screw terminal · Requires approx. 40 mm installation depth	 
Custom module 1 x Speakon 2-pole + stereo jack 6.3 mm stereo		Black
917.102	· Front: Speakon socket + 6.3 mm stereo jack · Rear: Screw terminal · Requires approx. 50 mm installation depth	 
Custom module 1 x Speakon 4-pole		Black
917.110	· Front: Speakon 4-pole socket · Rear: Screw terminal · Requires approx. 40 mm installation depth	 
Custom module 1 x loudspeaker connection stereo		Black
917.114	· Front: Stereo loudspeaker connection (red + white) · Rear: Screw terminal · Requires approx. 30 mm installation depth	 



Data transmission

See the glossary for detailed information on use/application

Front Rear



Art. no. | Version

Custom module 1 x USB 3.0 A / A Keystone**Black**

917.120

- Front: USB A socket
- Rear: USB A socket
- Fits into Keystone frame 917.000 or 917.001 (see page 72)
- Requires approx. 85 mm installation depth

**Custom module 2 x USB 2.0 A / A Keystone****Black**

917.141

- Front: 2 x USB A socket
- Rear: 2 x 4-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 2 x USB 2.0 A / A****White**

917.182

- Front: 2 x USB A socket
- Rear: 2 x 4-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module 1 x USB 2.0 A / B****Black**

917.018

- Front: USB A socket
- Rear: USB B socket
- Requires approx. 85 mm installation depth

**Custom module 1 x USB 2.0 B / A****Black**

917.019

- Front: USB B socket
- Rear: USB A socket
- Requires approx. 85 mm installation depth

**Custom module 1 x FireWire****Black**

917.037

- Front: FireWire 6-pole socket
- Rear: FireWire 6-pole socket
- Requires approx. 85 mm installation depth

**Custom module RS232 socket****Black**

917.075

- Front: RS232 SubD 9-pole socket
- Rear: 9-pole screw terminal
- Requires approx. 40 mm installation depth

**Custom module RS232 plug****Black**

917.076

- Front: RS232 SubD 9-pole plug
- Rear: 9-pole screw terminal
- Requires approx. 40 mm installation depth



Data transmission

See the glossary for detailed information on use/application

Art. no.	Version	
Custom module 1 x RS232 socket		Black
917.012	· Front: RS232 SubD 9-pole socket · Rear: RS232 SubD 9-pole socket · Requires approx. 70 mm installation depth	
Custom module 1 x RS232 crossover socket		Black
917.116	· Front: RS232 SubD 9-pole socket · Rear: RS232 SubD 9-pole crossover plug (crossed) · Requires approx. 70 mm installation depth	
Custom module PS2 mouse + keyboard		Black
917.031	· Front: 2 x MiniDIN 6-pole socket (mouse - mint green; keyboard - purple) · Rear: 2 x MiniDIN 6-pole socket (mouse - mint green; keyboard - purple) · Requires approx. 50 mm installation depth	



Power transmission

Art. no.	Version	
Custom module Power Con blue (power input)		Black
917.112	· Front: Power Con socket, blue · Rear: Screw terminal, incl. 2 crimp sleeves and cover cap · Requires approx. 40 mm installation depth	
Custom module Power Con grey (power output)		Black
917.113	· Front: Power Con socket, grey · Rear: Screw terminal, incl. 2 crimp sleeves and cover cap · Requires approx. 40 mm installation depth	



Control

See the glossary for detailed information on use/application



Art. no. | Version

Custom module with stainless steel button**Black**

- 917.046
- Front: Stainless steel button; switching capacity: 50 mA/24 V/DC;
 - Rear: 2-pole screw terminal
 - Requires approx. 30 mm installation depth

**Custom module with stainless steel button, blue illuminated****Black**

- 917.047
- Front: Stainless steel button, blue illuminated (ring illuminated); switching capacity: 50 mA/24 V/DC
 - Rear: 4-pole solder pins
 - Requires approx. 30 mm installation depth

**Custom module with automatic switchoff button****Black**


- 917.060
- Front: Button, black;
 - Rear: GST15i2 connector with approx. 1.0 m cable (suitable for power strips with automatic switchoff device, e.g. STEP switchoff device 906.005)
 - Requires approx. 40 mm installation depth

**Custom module with button****Black**

- 917.152
- Front: On/Off switch
 - Rear: Approx. 1.0 m 3G 1.0 mm² cable with end sleeves (labelled)
 - Requires approx. 60 mm installation depth

**Custom module with switch (to control external devices)****Black**

- 917.135
- Front: 2-pole rocker switch, green
 - Rear: Approx. 1.0 m H05VV-F 4G 1.50 mm² cable with end sleeves (labelled)
 - Requires approx. 60 mm installation depth

**Custom module with 4-key keypad for MediaNet control unit****Black**

- 917.127
- Front: 4 buttons, white, blue illuminated
 - Rear: 2 x RJ45 sockets for connecting to media controller and linking to further modules of the same type
 - Requires approx. 30 mm installation depth
 - Note: cannot be used in electrical installations.

**Custom module with 4-key keypad for KNX application****Black**

- 917.056
- Front: 4 buttons, white, blue illuminated, with various pictograms for labelling programmable on KNX installations; with integrated bus coupler; supply voltage: System voltage 30 V DC via bus push-in terminal;
 - Rear: Bus push-in terminal, 2-pole
 - Requires approx. 35 mm installation depth

**Custom module with 4-key keypad for EnOcean application****Black**

- 917.093
- Front: 4 buttons, white, blue illuminated, with various pictograms for labelling programmable on EnOcean applications; with built-in radio module, battery buffered;
 - Requires approx. 35 mm installation depth



Accessories

See the glossary for detailed information on use/application

Art. no.	Version	
Custom module blank cover		Black
917.009	- Blank cover as place holder or for you to mount your own connector - Material: Plastic, black, thickness 1.8 mm	
Custom module blank cover		White
917.166	- Blank cover as place holder or for you to mount your own connector - Material: Plastic, white, thickness 1.8 mm	
Custom module blank cover with screw dome		Black
917.010	- Blank cover as place holder or for you to mount your own connector - Screw dome on rear side of module for fixing e.g. of boards or blank holders - Material: Plastic, black, thickness 1.8 mm	
Custom module blank cover with screw dome		White
917.167	- Blank cover as place holder or for you to mount your own connector - Screw dome on rear side of module for fixing e.g. of boards or blank holders - Material: Plastic, white, thickness 1.8 mm	
Screws Torx T6 for custom modules in facility power strips		Black
917.041	Designed for 10 screwing cycles; contents: 10 pcs in colour black	
Screws Torx T6 for custom modules in electrical installations (mounting plate) and 10" + 19" panels		Black
917.111	Designed for 10 screwing cycles; contents: 10 pcs in colour black	
Torx T6 screwdriver		Black
917.040	Torx T6 screwdriver to fit the screws on the custom modules	



Media technology

Bachmann media technology systems provide a flexible and elegant solution for custom media management in conference and training rooms. From simply switching between image and sound signals to a complete central control of all media, this solution can be tailored to the needs of every user.

With its modern components, including control elements from the global market leader AMX® – plus all connecting systems, Bachmann media technology systems offer all that is required for any application. Thanks to its modular construction and intelligent cabling, the system can be quickly installed or adapted to specific requirements.

The flexibility of Bachmann complete solutions is complemented by their elegance. Regardless of how complex the Bachmann media technology system configuration is, it can be integrated seamlessly into the Bachmann facility systems.

Media Express

Plug & play technology for simplicity and efficiency.

The Bachmann media technology Media Express system lets you easily switch between different video and sound signals and is already integrated into the connection panels of the Bachmann Facility product ranges. In addition to switching between image and sound signals, Media Express also extends the network connection to each user.

Media Switch

Flexible and reliable thanks to high-quality components.

The Media Switch (Amx® inside) allows simple routing of image and sound signals from multiple users to various output devices such as projectors or monitors. All these elements can be combined with existing Bachmann facility products.

Media Control

Simple control of complex processes in media and facility applications.

The Media Control (Amx® inside) system uses control units to govern the various media from a central point. This makes it possible to activate various processes in a meeting or conference environment at the touch of a button on the Bachmann connection panel. The system is very user-friendly and easy for visitors to grasp quickly.

Media Express –

Plug & play technology for simplicity and efficiency.



Problem-free

Media Express is the solution for simple switching between image and sound signals. This system is already integrated in the connection panels of the Bachmann facility product ranges. In addition to switching between signals, it gives a network connection to each user.

With Media Express the individual connection panels are linked in a series known as a 'daisy chain'. This chain requires only one cable set with 3 connections. Connections are inserted into the connection panels on a plug-and-play basis. No programming of the units is necessary and the sequence of the connection units can be freely selected. The system initialises itself and can be used immediately.

Flexible switching

The signal-switching function enables image and sound signals to be sent from the connection panel to a beamer, projector or monitor screen. Authorisation to transmit the user's image and sound signal is activated by means of a dedicated button. An LED on the button indicates activation.

For image transmission the common 15-pole VGA sub-D system is provided on the front of the connection panel. This allows laptops to be connected easily using VGA connector cables. Of particularly practical benefit, no additional signal booster is necessary as this is integrated into the feeder box. This assures problem-free image transmission (so long as the maximum number of users and cable length are observed). The system can be built with a single infeed.

Up to 6 connection panels can be linked via connector cables. No central switching box is required. Projectors or monitors can be connected directly to the feeder box.

Simplicity of linking

Connection to the network requires only one access point (via the feeder cable). Two RJ45 LAN ports with signal boosting on each connection panel allow laptops to be connected. Thus the network is linked from one user to the next via the connector cable. The built-in network switch is designed for 10 / 100 Mbit and is sufficient, depending on the specific installation, for up to 6 participants.

Feeder box


The system structure requires the use of a feeder box. This box provides the link between the connection panels and the output devices (projector, audio, network etc.).

The benefits at a glance


- Simple plug-and-play principle
- Electronics already integrated in the connection panel
- Available for most Bachmann Facility systems
- Pre-cabled
- Image, sound and network forwarding
- Simple, decentralised signal switching
- Compact and space-saving unit

Configuration information and lists of applications are available at **www.bachmann.com**.

Should you have any questions concerning your project, contact us at **media@bachmann.com**.



Overview of Media Express connections



Technical data for Media Express:

Video/audio:

- Automatic hardware detection
- Input signal:
 - 0.7 Vss/75 ohm RGB, 5V H&V-sync, 1.8 Vss audio, 24 bit/96 kHz
 - VGA 15-pole sub-D plug
- Output signal:
 - 0.7 Vss/75 ohm RGB, 5V H&V-sync, 3.5 Vss audio, 24 bit/96 kHz
 - 26-pole sub-D socket
- Video bandwidth: (+/- 3dB) 300 MHz
- Resolution max: 1600 x 1024
- Transmission distance: 20 x MediaNet Express modules / cable length: max. 50 m total
- Audio: Stereo L/R

Connections:

- 1 x 15-pole VGA sub-D
- 1 x 3.5 mm mini stereo jack socket
- 2 x LAN RJ45 socket
- Sockets as per connection unit selected

Network:

- 2 x ports RJ45 10/100 Mbit
- CAT5 with LED (speed and active LED)

Power supply unit:

- 2.5A; 18V
- Max. current consumption per connection unit - 500 mA

Media Express

The Media Express unit can also be integrated into other Facility systems such as POWER FRAME and STEP. Please ask us for the configuration you require.

- Anodised aluminium profile, socket outlets, black, set at 35°
- Media Express
- Power input: GST18i3
- Power output: GST18i3

Art. no. | Version

1 x earthing contact, GST18i3, short (TOP FRAME, CONFERENCE) Length: approx. 260 mm

1 x Media Express

- 903.2000 |
- 1 socket outlet with earthing contact
 - 1 Media Express



3 x earthing contact, GST18i3, long (TOP FRAME, CONFERENCE) Length: approx. 444 mm



CUSTOM

1 x Media Express, 2 x custom modules

- 903.2001 |
- 3 socket outlet with earthing contacts
 - 1 Media Express
 - 2 custom modules empty



2 x earthing contact, GST18i3 (CONI) Length: approx. 356 mm



CUSTOM

1 x Media Express, 1 x custom module

- 903.3000 |
- 2 socket outlet with earthing contacts
 - 1 Media Express
 - 1 custom module empty



3 x earthing contact, GST18i3 (CONI) Length: approx. 356 mm



1 x Media Express

- 903.3001 |
- 3 socket outlet with earthing contacts
 - 1 Media Express



Media Express feeder box

Art. no. | Version

Media Express feeder box	
MediaNet Express system feeder box	



903.400	· Distribution of signals: – Image (D/V projector), 15-pole VGA sub-D to 26-pole sub-D – Sound (loudspeakers), stereo jack to 26-pole sub-D – Data (network), RJ45 to RJ45 – Signal authorisation on 26-pole sub-D – RS-232 interface for optional programming
---------	---

Media Express feeder cable

- Feeder cable length 2.0 m
- The cable set is held together in a textile-fibre sleeve

Art. no. | Version

Media Express feeder cable	
Feeder cable to feeder box	



903.500	· 1 x 15-pole VGA plug / 26-pole sub-D socket · 1 x CAT6 patch cable plug / plug, shielded · 1 x power cable, right-angle earth contact plug and GST18i3 socket
---------	---

Media Express connector cable

- Connecting cable, length 2.0 m
- The cable set is held together in a textile-fibre sleeve


Art. no. | Version

Media Express connector cable	
To link one connection unit to another	



903.600	· 1 x 26-pole sub-D (90° plug / 45° socket) · 1 x CAT6 patch cable plug / plug, shielded · 1 x power cable, Wieland GST18i3 plug and GST18i3 socket
---------	---

Typical order for 4 presentation stations



Configuration information and lists of applications are available at www.bachmann.com. Should you have any questions concerning your project, contact us at media@bachmann.com.

Media Switch –

Flexible and reliable thanks to high-quality components.



Easy to install

Today's meeting rooms are equipped such that the signal to an output device (projector etc.) can be switched between various sources. Key requirements are also ease of installation, ease of use and flexibility.

An exemplary solution to all these conditions is the MediaNet Switch system.

Problem-free

The control elements can be fitted into existing Bachmann facility products on a plug-and-play basis. Like all Bachmann media technology systems, Media Switch is also simple to plan, easy to install and straightforward to use. Multiple users can dock their laptops simultaneously via the multiple connection panels.

The VGA sockets on the connection panels allow e.g. presentations to be sent to the projector. As soon as a user presses the button on his/her connection panel, the switch selects the image signal on that panel/laptop. The connection to the switch /toggle switch is set up via a pre-prepared set of cables. Pressing the button issues a command to the switch /toggle switch to route the incoming image and sound signals to the projector and loudspeakers.


Signal booster

To ensure problem-free image signals, it is recommended that signal boosters are used with the MediaNet switch system. This enables image signals from devices with less powerful graphics cards to be transmitted with significantly better quality. The signal booster is fitted between each connection panel and the switch/toggle switch.

Switching is effected by pressing the button on a custom module with VGA and mini stereo jack on the connection panel. As soon as the button is pressed, the image and sound signals are routed to the switch/toggle switch. The button is illuminated blue until another user activates the button on his/her own connection panel to obtain signal authorisation.

The benefits at a glance

- Simple, low-cost signal switching
- Star configuration, ideal for small meeting rooms
- Plug-and-play inputs
- Decentralised switching: each user can request authorisation by pressing a button
- Several switches /toggle switches can be cascaded one after the next to expand the system for larger numbers of users
- Connects to all Bachmann Facility systems via built-in VGA, mini stereo jack and switch button connections (see art. no. 917.143)
- Pre-prepared cabling for connection between connection panel/signal booster and switch/toggle switch



Switch/toggle switch

- Power supply: 9–12 V DC 15 W
- Supplied with power cable and operating instructions in German and English



For the switch/toggle switch **903.100** there is the option of connecting the custom module **917.134**:

1. Without acknowledgement of signal authorisation, i.e. button is not illuminated when authorisation is granted.
The set with **signal authorisation 903.113** is used for this purpose (see page 114).
2. With acknowledgement of signal authorisation, i.e. button is illuminated blue when authorisation is granted.
The set with **signal authorisation 903.112** is used for this purpose (see page 114).

Art. no. Version	
Switch/toggle switch	
2 x VGA/audio input, 1 x VGA/audio output	
903.100	· RGB input / output: Analogue HD-15 (VGA)
	– Impedance 75 ohms / Max. signal level 1 V p-p – RGB bandwidth: 400 MHz -3 dB – RGB return loss: 45 dB@10 MHz, 27 dB@100 MHz – Adjacent input crosstalk: 73 dB@10 MHz, 50 dB@100 MHz
	· Audio input / output: Analogue 3.5 mm stereo/Max level 2V p-p



For the switch/toggle switch **903.101** there is the option of connecting the custom module **917.134** by means of the signal converter **903.112** (see page 114) with visual acknowledgement as button illumination.

Art. no. Version	
Switch/toggle switch	
4 x VGA/audio input, 1 x VGA/audio output	
903.101	· RGB input / output: Analogue HD-15 (VGA)
	– Impedance 75 ohms / Max. signal level 1V p-p – RGB bandwidth: 350 MHz -3 dB – RGB return loss: 45d B@10 MHz, 32 dB@100 MHz
	· Audio input / output: Analogue 3.5 mm stereo/Max level 2 V p-p

Suitable mountings on page 114



For the switch/toggle switch **903.102** there is the option of connecting the custom module **917.134** by means of the signal converter **903.112** (see page 114) with visual acknowledgement as button illumination.

Art. no. | Version

Switch/toggle switch **L x W x H: 482 x 170 x 45 mm**

6 x VGA/audio input, 1 x VGA/audio output

- 903.102
- RGB input /output: Analogue HD-15 (VGA)
 - Impedance 75 ohms / Max. signal level 1 V p-p
 - RGB bandwidth: 400 MHz -3 dB
 - RGB return loss: 45 dB@10 MHz, 2 dB@100 MHz
 - Audio input /output: Analogue 3.5 mm stereo/Max level 2 V p-p
 - Mounting for 19" fitting included

Signal booster

- Interference can sometimes occur, particularly with image transmission. This may be caused e.g. by lower-power graphics cards on the laptop or by long cable lengths
- To improve these image signals we recommend that each user uses a signal booster
- This provides optimum boosting of the signal and prevents interference when used by different users
- Additional output (VGA 15HD) allows an additional monitor to be connected
- Compact, easily-installed unit



Art. no. Version	
Signal booster VGA	
1 x VGA input, 2 x VGA output	
L x W x H: 150 x 70 x 35 mm	
903.104	· RGB input / output: Analogue HD-15 (VGA), – 1 x video IN / 2 x video OUT – Impedance 75 ohms / Max. signal level 1V p-p – Output gain 1.0 (unity) – RGB bandwidth: 400 MHz -3 dB – Power supply: 9V DC 3W · Supplied with power cable and operating instructions in German and English

Typical order for 4 presentation stations



Quantity	Art. no.	Name
4 x		Power strips from Bachmann facility systems with space for custom module
4 x	917.134	Custom module VGA, mini stereo jack and button for media switch

Desk connection panel

Quantity	Art. no.	Name
4 x	903.104	VGA signal booster
4 x	918.009	VGA connecting cable from power strip to signal booster
optional:		
4 x	918.023	Bracket

Signal booster

Quantity	Art. no.	Name
1 x	903.101	Switch 4-way VGA + audio
1 x	918.023	Bracket

Switch

Quantity	Art. no.	Name
4 x	903.107-110	VGA + sound + authorisation cable set / own choice of length
1 x	903.112	2-6-way signal converter with acknowledgement

Cabling



**Video
projector**

Audio

Configuration information and lists of applications are available at www.bachmann.com.
Should you have any questions concerning your project, contact us at media@bachmann.com.

Media Control –

Simple control of complex processes in media and facility applications.



Central control

To control a variety of media from a central point, control units are used. This makes it possible to activate various processes in a meeting or conference environment at the touch of a button on the Bachmann connection panel. The system is very simple and easy for visitors to grasp quickly. The various procedures can be individually performed between the operator panel (in the connection panel) and the control unit.

Simple to programme


Programming is very simple and can soon be achieved with the software provided and the instruction manual (German /English). Subsequent alterations or additions can also be entered without problems.

The control functions allow control of various media: e.g. projector, DVD, SAT, TV, projector screen, lighting, blinds etc.

The 2 built-in 230 V~ 10 A relays can be used for example to connect a screen directly to the control unit. This means that a power cable is sufficient for control.


The benefits at a glance

- Central control of multiple media
- Very easy to use
- Simple to install and easy-to-learn programming
- Plug-and-play operation adapted to Bachmann connection panels
- Up to 6 button modules can be connected in series or 2 strings with additional modules can be programmed for up to 24 button commands
- Multiple buttons can be programmed on the control unit with the same command (thus also allowing decentralised control)
- Simple connection of button modules via standard RJ45 patch cables (plug / plug)
- 2 built-in relays, 230 V~ 10 A with 1 earthing contact coupling for direct connection
- Ready-to-connect unit with accessories (programming cable, IR transmitter)
- Can be retrofitted to existing systems
- Pre-programmed demo version on CD
- Basic programming can be reinstalled if necessary (from CD or download)
- If desired, programming (sequences, devices etc.) can be created and made available by Bachmann as an option




Media control

The software supplied makes even complex procedures simple to programme.



Start programmed procedures by pressing button



Pictograms for other button functions are provided

Cascadable up to 6 button arrays with 24 procedures

Keypad on page 114



Suitable mountings on page 114

Media Control

- Memory: 8 Kb
- 2 x 230V~ relay 10A built-in
- 2 x RS-232 interface
 - Baud rate 1200–57 600
 - Data bits 7/8
 - Stop bits 1/2
 - Command string 1–22 bytes
- 2 x infrared interface PPM or PWM
 - PWM frequency 30–62 KHz
- Power connection: 100–240V~
- PSU, programming cable, 2 x infrared transmitters, programming software and operating instructions in German and English included



Art. no. | Version

Control unit		L x W x H: 225 x 125 x 45 mm
Control system with programming function		

- | | |
|---------|---|
| 903.105 | <ul style="list-style-type: none">• Control system with programming function• I/O port: External switch detect input |
|---------|---|



Control unit TCP/IP		L x W x H: 225 x 125 x 45 mm
Control system with programming function and TCP/IP interface		

- | | |
|---------|--|
| 903.106 | <ul style="list-style-type: none">• Control system with programming function and TCP/IP interface• Devices from different manufacturers can communicate via the network• I/O port: Input: External switch detect |
|---------|--|

Programming according to requirements

Available for control units 903.105 and 903.106

- | | |
|---------|---|
| 903.114 | <ul style="list-style-type: none">• Programming is undertaken by entering:<ul style="list-style-type: none">– connected devices (manufacturer, type)– required procedures (max. 24 commands)• The file is sent via e-mail |
|---------|---|

Suitable mountings on page 114

Switch function

Combined source switch for 4 to 2 VGA, 6 to 2 S-video or CVBS and 10 to 2 stereo audio signals. In all cases the output signal is present on the two outputs at the same time.

Ideal for applications with multiple different signal sources - RGBHV, S-video, CVBS and audio. The 6 video inputs can be driven with either S-video or CVBS signals. A combination of both signal types is possible.

The 10 audio inputs are designed for unbalanced stereo audio signals. One output offers an unbalanced and the other a balanced stereo signal for further processing. The audio input signal levels and the volume of the audio outputs are adjustable. Sound and video can both be silenced (mute / blank).

Control function

The functions are controlled manually via the front operator panel or remotely via RS-232 from a button module on a connection panel. When operating the unit via RS-232 it is possible to switch audio and video inputs separately. A programmable RS-232 output port is also provided; this can be used to control displays or projectors.



Art. no. | Version

Presentation switch/toggle switch		L x W x H: 150 x 70 x 35 mm
4 x input / 2 x output VGA, 10 x input / 2 x output audio, 6 x input / 2 x output S-video		
903.103	- Inputs / signals: 4 x RGBHV, 6 x S-video/FBAS, 10 x stereo audio - Outputs: 2 of each (dual) - Bandwidth: 350 MHz - Stereo audio: unbalanced to balanced - Front operator panel and operation via RS-232 - RS-232 control output for connected reproducing equipment - Power supply: 100 – 240V AC 15W - Supplied with power cable and operating instructions in German and English - Includes mounting for 19" fitting	

Suitable mountings on page 114

Typical order for 4 presentation stations



Quantity	Art. no.	Name
4 x		Power strips from Bachmann facility systems with space for custom module
4 x	917.134	Custom module VGA, mini stereo jack and button for media switch
1-6 x	917.127	Custom module button

Desk connection panel

Quantity	Art. no.	Name
4 x	903.104	VGA signal booster
4 x	918.009	VGA connecting cable from power strip to signal booster
optional:		
4 x	918.023	Bracket

Signal booster

Quantity	Art. no.	Name
1 x	903.101	Switch 4-way VGA + audio
1 x	918.023	Bracket

Switch

Quantity	Art. no.	Name
1 x	903.105	Control unit
1 x	903.111	Control unit converter

Control unit

Quantity	Art. no.	Name
1-6 x	918.006 - 008	Patch cable to connect custom module button 917.127

Cable output



Video projector



Audio



Screen



Light



Blinds

Configuration information and lists of applications are available at www.bachmann.com.
Should you have any questions concerning your project, contact us at media@bachmann.com.



Facility control modules

Pushbutton modules in the Bachmann custom-module format offer convenient control of light and blinds in open-plan and individual offices and in meeting and conference rooms.

The control module is installed within the user's easy reach on the desk connection panel at office workstations or in meeting rooms. Then the lighting and blinds settings can be controlled with ease from the user's seat. The increased convenience lets the user respond to changing environmental situations - and thus save energy.



KNX pushbutton module 4-way

The 4-way KNX pushbutton module is designed as a custom module and can be integrated into Bachmann Facility systems either by the manufacturer or retrospectively. Installation in rack and electrical installations is also possible with the custom module system.

Functions such as switching, dimming, storage of lighting scenes, blind control etc. can be programmed by specialist personnel using the standard ETS software. For this, specialist knowledge and in-depth KNX training is required.

Each button can be custom configured and labelled accordingly (common pictograms are supplied). The blue illumination indicates the activity status.

This pushbutton module can be simply installed by KNX-trained personnel. The appropriate bus coupling is built into the module and can be simply connected to the bus cable by means of clips.

KNX/EIB 4-button custom module



Front:

- 4 x buttons, square, self-labelling, blue backlit, programmable on EIB/KNX installations
- With integral bus coupler and bus terminal (can be labelled with physical address)
- Supply voltage: System voltage 30 V DC via bus terminal
- Use: e.g. as buttons for controlling lighting, blinds etc.



Art. no.	Version
917.056	Rear: · BUS plug-in terminals · Requires approx. 35 mm installation depth

Micro clamp terminals

917.056	Rear: · BUS plug-in terminals · Requires approx. 35 mm installation depth
---------	---



EnOcean pushbutton module 4-way

The EnOcean pushbutton offers wireless control of e.g. lighting, blinds, projector screen etc. Installation is simple: The pushbutton module can be used in Bachmann desk connection panels with custom modules or in wall or trunking installations. The required control signals are transmitted wirelessly to the receiving device. Each button can be separately programmed. With EnOcean technology (868 MHz), interference is practically eliminated.

No cable installation is required for this module. Power is obtained from a built-in battery that will last for up to 1 million switching cycles.

If required the EnOcean pushbutton module can also be linked into the KNX building control system bus.

EnOcean 4-button custom module



Art. no. | Version

Micro clamp terminals

917.093	Rear:
	· Includes battery
	· Requires approx. 35 mm installation depth



- Front:
- 4 x buttons, square, self-labelling, backlit blue
 - Programmable on EnOcean applications
 - Supply voltage: Radio module battery-backed
 - Includes inserter with common pictograms
 - Use: e.g. as buttons for controlling lighting, blinds etc.



Custom modules

Art. no. | Version

Custom module VGA, mini stereo jack and button for media switch

- | | |
|---------|--|
| 917.134 | <ul style="list-style-type: none"> · Custom module to fit in Bachmann connection panels · 1 x VGA 15-pole socket / socket · 1 x 3.5 mm jack socket with approx. 0.1 m cable and 3.5 mm jack socket · 1 x button, blue illuminated, with approx. 0.1 m cable and RJ12 for controlling switch · Requires approx. 70 mm installation depth |
|---------|--|

Custom module with 4-key keyboard for MediaNet control unit

Can be used in all facility systems



- | | |
|---------|---|
| 917.127 | <ul style="list-style-type: none"> · Custom module, can also be retrofitted · 4 buttons, white, blue illuminated, with various pictograms for labelling · Rear: 2 x RJ45 sockets for connecting to media controller and linking to further modules of the same type · Includes inserter with common pictograms · Requires approx. 80 mm installation depth |
|---------|---|

Patch cable plug / plug

To connect custom module 917.127 to signal converter



- | | | |
|---------|-------|--------------------------------|
| 918.006 | 1.0 m | · End 1: RJ45 Hirose TM12 plug |
| 918.007 | 3.0 m | · End 2: RJ45 Hirose TM12 plug |
| 918.008 | 5.0 m | · Shielded |

Signal converter Media

Art. no. | Version

2-way signal converter

To implement the authorisation signals of each participant. Without visual acknowledgement on button.



- | | |
|---------|---|
| 903.113 | <ul style="list-style-type: none"> · Input: 2 x RJ12 socket · Output: 1 x 2-pole terminal for connection to switch · Only usable with 903.100 switch |
|---------|---|

For the switch / toggle switch 2 x, 4 x and 6 x VGA / audio, the custom module 917.134 is connected by means of the 2-6-way RS 232 signal converter (903.112) with visual acknowledgement as button illumination.

**2-6-way signal converter**

L x B x H: 225 x 125 x 45 mm

To implement the authorisation signals of each participant. With visual acknowledgement on button.

- | | |
|---------|--|
| 903.112 | <ul style="list-style-type: none"> · Input: 6 x RJ12 socket · Output: 1 x 9-pole RS-232 sub-D · With 1.0 m cable with push-in terminal to connect 2-pole terminal to switch · Includes PSU |
|---------|--|

Converter box

For connecting an additional series of button modules



- | | |
|---------|--|
| 903.111 | <ul style="list-style-type: none"> · Media converter for connection to control unit · End 1: RS-232 · End 2: RJ45 · Includes PSU |
|---------|--|

Mounting for converter / control unit

For fitting under the desk/tabletop



- | | |
|---------|---|
| 918.023 | · Mount for fitting under a desk/tabletop (see page 98) |
|---------|---|

Combi cables and extensions

Art. no.	Length	Version
VGA 15-pole HD extension cable		
1 x VGA		
918.009	1.0 m	· High-quality VGA cable to connect: – connection panel to laptop – connection panel to signal booster – signal booster to monitor / TV (optional) · End 1: 1 x 15-pole VGA HD plug · End 2: 1 x 15-pole VGA HD plug
940.047	3.0 m	
940.048	5.0 m	
1 x VGA, 1 x mini stereo jack		
918.066	1.0 m	· High-quality VGA cable to connect: – connection panel to laptop – connection panel to signal booster – signal booster to monitor / TV (optional) · End 1: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm · End 2: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm · Plug with metal housing and shielding
918.067	3.0 m	
918.068	5.0 m	
918.069	10.0 m	
Media combi cable		
1 x VGA, 1 x mini stereo jack, 1 x control signal		
903.107	1.0 m	· Professional high-quality VGA cable also with audio and control cable for switching the switch via the button in the custom module 917.134 · End 1: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm: 1 x RJ12 for button · End 2: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm: 1 x RJ12 for button · Plug with metal housing and shielding
903.108	3.0 m	
903.109	5.0 m	
903.110	10.0 m	



Accessories

Art. no.	Version
STEP BASE 3 x earthing contact, GST18i3	
Power outlet for switch and control unit	
336.600	· Plastic profile, socket outlets black · 3 socket outlets with earthing contact, set at 35° · Power input: GST18i3 plug, power output: GST18i3 socket



LanLight® combines power, network connectivity, connections to media and even lighting in a modular, multifunctional system whose consistently modular construction lets you adapt and use it flexibly in office environments. The system creates order in providing the various connections required at the workplace, and so increases safety. With its clear design language and high quality materials it fits harmoniously and unobtrusively into its surroundings.


The LanLight® base module can accommodate a variety of module inserts. These include floor box inserts for all media - from earthing contact power outlets to HDMI sockets - that are also available fully pre-installed with tested connecting cables.

A special feature is the new type of self contacting used in the base LanLight® module with mobile power column, in which all connections are created by a single plugging action.

LanLight® fits into a hole of only 152 mm diameter. This ease of installation, together with its compact size and the functionality provided by the modular design mean that installations and energy consumers can be fitted only in those positions where they are really needed. Thus LanLight® can be installed to meet the exact requirements and is equally easy to remove. Benefit: during restructuring, individual system components are reused time and again and the usual provision of installations is no longer necessary.

The benefits at a glance

- Delivers exactly what is needed to each workstation
- Provides power, data and media connections and lighting
- Modular and multifunctional - from cable connections and the floor box to mobile power columns (with or without light fittings)
- Attractive, harmonious visual design
- No tangle of cables under the desk
- Provides optimal lighting



Used together with consolidation points, LanLight® can deliver power, data, media and lighting to practically any point in the room. The optimum cable length is up to 9 metres.



reddot design award
winner 2011

LanLight[®]

Modular installation solution offering flexible
supply to office workstations

LanLight[®]
SMART SUPPLY SYSTEM

LanLight® offers ...

- a cable outlet
- a floor box with various inserts for a wide range of applications
- plug-in mobile power columns with two power circuits and up to eight data connections with self-contacting interface (mobile column)
- plug-in power columns with two power circuits and up to eight data connections with prepared patch cables
- a plug-in lighting module, one-sided, with lighting head that swivels on two axes
- a plug-in lighting module, two-sided, with lighting head that swivels




Basic unit 924.1016
Modular installation box

Floor outlet

No insert required

Floor box versions



Connection plate 924.4000
4 x power Wieland GST15i3
8 x Keystone mount



Earth contact connection plate 924.4002
2 x earth contact
4 x Keystone mount



Media connection plate 924.4003
3 x power Wieland GST15i3
3 x custom media module mount

Basis for patch versions



Patch column mount 924.1041
Cone for patch column

Basis for self-contact system



Connection plate 924.4005
Self-contact system
2 x power for max.
2 x data cable set 924.700



Data cable set 924.700
4 x Terra CAT7 jack, 6 m in length

Level 1

Level 2

Lift-off cap set 924.1038
for 5 mm or 8 mm floor coverings



Lift-off cap set

Lift-off cap set 924.1018
Stainless steel



Twist-off cover 924.1046
for floor coverings,
with water protection



Patch column 640 mm

924.5002: 2 x earth contact, 4 x CAT6_a jack including 6 m supply cable
924.5003: 4 x earth contact, 8 x CAT6_a jack including 6 m supply cable



Mini patch column 924.6000
150 mm, 2 x earth contact



Twist-off cover 924.1046
for floor coverings, with
water protection



Lift-off cap set 924.1040
for 5 mm or 8 mm
floor coverings



Lift-off cap set
Self-contact system

Lift-off cap set 924.1039
Stainless steel



Mobile column 640 mm

924.5000: 2 x earth contact, 4 x CAT6_a 10Gbit
924.5001: 4 x earth contact, 8 x CAT6_a 10Gbit



You can obtain lamps from our
LanLight® partner on request

Level 3

Lamps

Level 1: LanLight® basic unit



Art. no. | Version

Basic unit for all LanLight® components

Modular installation box

- | | |
|----------|---|
| 924.1016 | <ul style="list-style-type: none"> · For fitting in raised and false floors · Fastening in round cut-out with 152 (+1) mm diameter · For floor thicknesses from 25 to 70 mm (min. floor thickness 35 mm for column versions) · Fixed using three clamping claw fasteners · Total height: 97 mm, installation depth: 93 mm, external diameter: 162 mm · Die-cast aluminium |
|----------|---|

Level 2: LanLight® inserts

Art. no. | Version

8P/4S connection plate with breakout cable and GST18i3 plug


Connection plate for fitting in the LanLight® lift-off cap set



- | | |
|----------|--|
| 924.4001 | <ul style="list-style-type: none"> · To connect up to 4 Wieland GST15i3 sockets (power) and 8 data jacks (Keystone) · Rear strain relief for power connections · Disengagement aid for Wieland GST15i3 plugs · 4 x Wieland GST15i3 panel jack, fitted, incl. 0.2 m H05VV-F3G 2.5 mm² supply cable connected to GST18i3 plug · For connecting up to 8 data jacks (Keystone) · Rear strain relief for power connections · Coded connecting points (data 1-8, power A-D) · Diameter: 114.8 mm |
|----------|--|

8P/4S connection plate for mains connection by client

Connection plate for fitting in the LanLight® lift-off cap set



- | | |
|----------|--|
| 924.4000 | <ul style="list-style-type: none"> · To connect up to 4 Wieland GST15i3 sockets (power) and 8 data jacks (Keystone) · Rear strain relief for power connections · Disengagement aid for Wieland GST15i3 plugs · Coded connecting points (data 1-8, power A-D) · 4 x Wieland GST15i3 panel jack · Connecting up to 8 data jacks (Keystone) · Diameter: 114.8 mm |
|----------|--|

Earthing contact unit 4P/2S with breakout cable and GST18i3 plug

Connection plate for fitting in the LanLight® lift-off cap set



- | | |
|----------|---|
| 924.4009 | <ul style="list-style-type: none"> · For connecting up to 4 data jacks (Keystone) · Rear strain relief for power connections integrated in housing · Coded connecting points (data 1-4, power A-B) · Incl. 2 x 0.2 m H05VV-F3G 2.5 mm² supply cable connected to GST18i3 plug · Diameter: 114.8 mm |
|----------|---|

Earth contact unit for 4P/2S connection plate for mains supply by client

Connection plate for fitting in the LanLight® lift-off cap set



- | | |
|----------|---|
| 924.4002 | <ul style="list-style-type: none"> · To connect up to two phases to the earthing contact socket outlets · For connecting up to 4 data jacks (Keystone) · Rear strain relief for power connections integrated in housing · Coded connecting points (data 1-4, power A-B) · Diameter: 114.8 mm |
|----------|---|

Art. no. | Version

Connection plate for 3 x custom modules and 3 x power with breakout cable and GST18i3 plug

CUSTOM

Connection plate for fitting in the LanLight® cover guide

- 924.4004
- For connecting up to 3 Bachmann custom modules
 - 3 x Wieland GST15i3 panel jack, fitted, incl. 0.2 m H05VV-F3G 2.5 mm² supply cable connected to GST18i3 plug
 - Rear strain relief for power connections
 - Disengagement aid for Wieland GST15i3 plugs
 - Coded connecting points (data 1-3, power A-C)
 - Diameter: 114.8 mm



Media connection plate 3 x custom module and 3 x power for mains connection by client

CUSTOM

Connection plate for fitting in the LanLight® lift-off cap set

- 924.4003
- To connect up to 3 Wieland GST15i3 sockets (power) and 3 data jacks (Keystone)
 - Rear strain relief for power connections
 - 3 x Wieland GST15i3 panel jack
 - Disengagement aid for Wieland GST15i3 plugs
 - Coded connecting points (data 1-3, power A-C)
 - Diameter: 114.8 mm



Self-contact 10 Gbit 4P/2S with breakout cable and GST18i3 plug

Connection plate to fit in the modular installation box

- 924.4006*
- Base unit for holding self-contacting power column 924.5000 or 924.5001
 - Prepared to hold 1-2 sets of data cables 924.700
 - Coded connecting points (data 1-8, power A-B)
 - For 924.1041
 - 2 x Wieland GST15i3 panel jack, fitted, incl. 0.2 m H05VV-F3G 2.5 mm² supply cable connected to GST18i3 plug
 - Diameter: 114.8 mm



10 Gbit self-contact for mains connection by client

Connection plate to fit in the modular installation box

- 924.4005*
- Base unit for holding self-contacting power column 924.5000 or 924.5001
 - Prepared to hold 1-2 sets of data cables 924.700
 - Coded connecting points (data 1-8, power A-B)
 - For 924.1041
 - 2 x Wieland GST15i3 panel jack
 - Diameter: 114.8 mm



Data cable set

For self-contact connection plates 924.4005 and 924.4006

- 924.700*
- 4 x Tyco Electronics CAT7 (Terra) jacks to Tyco Electronics CAT6a plug
 - Column, 2-sided with 8 ports: Requires 2 x data cable set 924.700
 - Column, 1-sided with 4 ports: Requires 1 x data cable set 924.700
 - Cable length 6 m each
 - Assembled into bundle of cables



Conical column holder

Cone as column holder

- 924.1041
- Used to directly mount the LanLight® columns
 - For 924.5002, 924.5003 and 924.6000



* No storage type

Lift-off cap variants

Art. no. | Version



Lift-off cap set with stainless steel inlay

Lift-off cap set to fit in the modular installation box

- 924.1018
- Two positions: open during use / closed when not in use
 - With latch for when open
 - With dust protection as cable bushing
 - With labelling card for connections
 - With stainless steel inlay
 - Inlay diameter: inside 49 mm, outside 142 mm
 - Lift-off cap diameter 146.4 mm, cap guide diameter 128.8 mm



Lift-off cap set 5 mm / 8 mm

Lift-off cap set to fit in the modular installation box

- 924.1038
- Two positions: open during use / closed when not in use
 - With latch for when open
 - With dust protection as cable bushing
 - With labelling card for connections
 - For gluing dry maintained surfaces with thicknesses 5 mm or 8 mm (e.g. carpet, laminate)
 - Inlay diameter: inner 49 mm, outer 142 mm, lining depth 5 mm or 8 mm
 - Lift-off cap diameter 146.4 mm, cap guide diameter 128.8 mm



Lift-off cap set, self-contacting, with stainless steel inlay

Lift-off cap set to fit in the self-contacting cone

- 924.1039*
- Two positions: open during use / closed when not in use
 - With latch for when open
 - With labelling card for connections
 - With stainless steel inlay
 - Inlay diameter: inner 49 mm, outer 142 mm, depth 5 mm or 8 mm
 - Lift-off cap diameter 146.4 mm, cap guide diameter 128.8 mm



Lift-off cap set, self-contacting, 5 mm / 8 mm

Lift-off cap set to fit in the self-contacting cone

- 924.1040*
- Two positions: open during use / closed when not in use
 - With latch for when open
 - With labelling card for connections
 - For gluing dry maintained surfaces with thicknesses 5 mm or 8 mm (e.g. carpet, laminate)
 - Inlay diameter: inner 49 mm, outer 142 mm, lining depth 5 mm or 8 mm
 - Lift-off cap diameter 146.4 mm, cap guide diameter 128.8 mm



Twist-off cover for 12 mm inlay

Twist-off cover to screw onto cone to hold column

- 924.1046
- Cover to close modular installation box with cone (924.1016, 924.1041)
 - With water protection
 - For inlay (e.g. stone/tile) around 12 mm thick
 - Incl. mounting key and sleeves
 - Inlay diameter: inside 139 mm

* No storage type

LanLight® is a trademark of Bierbrauer Hoff Planungsgesellschaft mbH

Level 3: LanLight® extension units

Art. no. | Version

Self-contacting column, 10 Gbit 4P/2S, one-sided

Column, 10 Gbit, for 1-2 workstations

- 924.5000*
- For simply plugging into and unplugging from LanLight® cone holder (924.1041)
 - 2 socket outlets with earthing contact (2 phases) and 4 Tyco Cat6a jacks
 - Coded connecting points (data 1-4, power A-B)
 - Fully pre-wired, incl. 4 x Tyco Terra Cat7 plug for self-contact
 - Socket outlets: 2-pole with earthing contact, 16A/3680W, AC250V, IP20, black
 - Column can be extended by inserting a LanLight® system lamp
 - Height 640 mm, diameter 95 mm



Self-contacting column, 10 Gbit 8P/4S, two-sided

Column, 10 Gbit, for 3-4 workstations

- 924.5001*
- For simply plugging into and unplugging from LanLight® cone holder (924.1041)
 - 4 socket outlets with earthing contact (2 phases) and 8 Tyco Cat6a jacks
 - Coded connecting points (data 1-8, power A-D)
 - Fully pre-wired, incl. 8 x Tyco Terra Cat7 plug for self-contact
 - Socket outlets: 2-pole with earthing contact, 16A/3680W, AC250V, IP20, black
 - Column can be extended by inserting a LanLight® system lamp
 - Height 640 mm, diameter 95 mm



Patch column 4P/2S, one-sided

Column for 1-2 workstations

- 924.5002
- For simply mounting on LanLight® cone holder (924.1041)
 - 2 socket outlets with earthing contact (2 phases) and 4 CAT6a jacks (Keystone)
 - Coded connecting points (data 1-4, power A-B)
 - 2 x power supply cable 6 m H05VV-F3G 2.5 mm² connected to Wieland GST18i3 plug
 - 4 x data cables 6 m CAT6a jack to CAT6a plug
 - Socket outlets: 2-pole with earthing contact, 16A/3680W, AC250V, IP20, black
 - Column can be extended by inserting a LanLight® system lamp
 - Column material: Extruded aluminium, powder-coated RAL 9006
 - Height 640 mm, diameter 95 mm



Patch column 8P/4S two-sided

Column for 3-4 workstations

- 924.5003
- For simply mounting on LanLight® cone holder (924.1041)
 - 4 socket outlets with earthing contact (2 phases) and 8 CAT6a jacks (Keystone)
 - Coded connecting points (data 1-8, power A-D)
 - 4 x power supply cable 6 m H05VV-F3G 2.5 mm² connected to Wieland GST18i3 plug
 - 8 x data cables 6 m CAT6a jack to CAT6a plug
 - Socket outlets: 2-pole with earthing contact, 16A/3680W, AC250V, IP20, black
 - Column can be extended by inserting a LanLight® system lamp
 - Height 640 mm, diameter 95 mm



Mini patch column 2S

Mini column


- 924.6000
- Mini patch column for simply mounting on LanLight® cone holder (924.1041)
 - 2 socket outlets with earthing contact (2 phases)
 - Coded connections (power A-B)
 - 30 mm surge water protection
 - 2 x 0.2 m breakout cable H05VV-F3G 2.5 mm² and GST18i3 plug incl. GST T-piece
 - Socket outlets: 2-pole with earthing contact, 16A/3680W, AC250V, IP20, black
 - Height 150 mm, diameter 95 mm



* No storage type

You can obtain lamps from our LanLight® partner on request

F: Front / R: Rear



Consolidation point


Installation solutions from a single supplier

Bachmann's new system for under-floor distribution and installation, based on the MUTO (multi-user terminal outlet) concept, offers a coherent and simple installation solution that brings power and data to the desktop.

The consolidation points for power and data are linked to the floor distributor in the conventional way. Floor outlets and desktop power strips from the Bachmann facility range complete the installation kit. From the consolidation point the floor outlet allows power and data to be conveyed with ease to the workstation. This dispenses with complicated and inflexible installations such as traditional floor box systems.

Thanks to the "open-office cabling", CP and MUTO concepts the network installation is flexible, future-proof and at the same time cost-optimised. The combination of power and data connections can be found in various Bachmann facility systems. They thus offer a user-centred unit providing all necessary connections.

In the main Bachmann catalogue you can also find different desktop power strips for mounting on top of or fitting into office workstation desks. All versions can be configured as required and supplied ready for use.



CP mounting

- Robust steel plate mounting for CPs
- Mountings with secure, tool-free clip-in and release mechanism
- Anchors firmly on the floor with integrated screw-on brackets
- Mountings with extra step protection of approx. 200 kg incl. CP unit
- Raised position of CP units for greater protection in case of minor ingress of water



Power CP

- Power CP is fully wired and electrically tested at the factory
- Power connections with connector systems by Wieland (Gesis GST); Wago (Winsta) versions available on request
- Other connector systems can be used where required
- Time-optimised on-site installation
- Future-proof thanks to flexible structure



Power CP reconnectable



Data CP

- CP data - flexible and modular based on custom modules
- Various manufacturers' systems can be integrated
- Easy to install and future-proof thanks to modular structure
- Should a change be necessary, only the data connector unit is changed
- Mounting and unit remain unchanged
- Additional strain relief for data connection can be provided with cable ties



Consolidation point units for power

- Fully wired and electrically tested
- With Wieland GST18i3 plug connector

Art. no. | Version

Consolidation point units for power

Short

919.2000	· 6-way GST18i3 socket, black, 1-phase · Power input: GST18i3
919.2001	· 2 x 3-way GST18i3 socket, 2-phase · Sockets in black and red · Power input: GST18i3

Consolidation point units for power

Long

919.2002	· 12-way GST18i3 socket, black, 1-phase · Power input: GST18i3
919.2003	· 2 x 6-way GST18i3 socket, 2-phase · Sockets in black and red · Power input: GST18i3
919.2004	· 3 x 4-way GST18i3 socket, 3-phase · Sockets in black and red and grey · Power input: 3 x GST18i3 socket
919.2005	· 3 x 4-way GST18i3 socket, 3-phase · Sockets in red and black grey · Power entry is via the end cap with rewirable terminal for allowing connection by user

Consolidation point units for data

- Without power, to integrate with Bachmann custom modules
- Anodised aluminium profile

Art. no. | Version

CUSTOM

Consolidation point units for data

912.000	· 3 x custom modules, empty · In short: 217 mm
912.001	· 6 x custom modules, empty · Long: 356 mm

Consolidation point mounting

- Colour black (RAL 9005)
- Mounting in steel plate

Art. no. | Version

Consolidation point mounting

L x W x H: 295 x 85 x 65 mm

919.1100	· Short (for units with 3 modules)
----------	------------------------------------

Consolidation point mounting

L x W x H: 435 x 85 x 65 mm

919.1101	· Long (for units with 6 modules)
----------	-----------------------------------



Floor outlet for dry-maintained floors

Outlet for dry-maintained floors (raised and false floors) from 24 mm thickness for the cable outlet from the subfloor (consolidation point) to the power strip on the desk or table. The outlet features a very simple universal fixing. With one rotation of each of the two eccentric Allen bolts in the outer ring, the outlet is anchored firmly into the floor, yet can easily be removed again if required. 2 flaps, each of which can be opened to a position independent of the other, through which cabling is routed out from floor. The flaps can be snap-fastened in open positions, thus preventing cables becoming bent and possibly damaged. If required the flaps can be rotated through 130° with the inner ring. Textile-fibre sleeves or cable management systems from the Bachmann range can be docked to the outlet flaps. If the outlet is no longer used, the flaps can be lowered and used as a blank cover that can be stepped on.

- Exit point/floor outlet for power and data cables
- Fits in raised floors with thicknesses from 24 mm
- Hole diameter 112 mm
- Simple fixing mechanism with Allen bolts
- 2 flaps, rotatable through approx. 130°, for cable outlet
- Material: polyamide (halogen free)

Art. no. | Version

Exit point/floor outlet

RAL 9005

919.1000 | · Black RAL 9005



Data cables → Transfer of data within various categories

(see glossary) Used for network and IP telephone services

Art. no.	Length	Version
----------	--------	---------



CAT5e patch cable plug/plug

918.003	1.0 m	· CAT5e cable shielded, grey
940.052	3.0 m	· Conforms to ISO / IEC 11801 and EN 50173
940.053	5.0 m	· End 1 and 2: RJ45 plug with kink protection nozzle and protective tongue for interlock · Suitable for e.g. CAT5e socket / socket 940.057



CAT6 patch cable plug/plug

940.040	3.0 m	· CAT6 cable shielded, grey
940.041	5.0 m	· Conforms to ISO / IEC 11801 and EN 50173 · End 1 and 2: RJ45 plug with kink protection nozzle and protective tongue for interlock · Suitable for e.g. CAT6 socket / socket 940.044



CAT6a patch cable plug/plug

918.006	1.0 m	· CAT7 cable shielded, black
918.007	3.0 m	· Conforms to IEC 61156-6
918.008	5.0 m	· End 1 and 2: RJ45 Hirose TM12 CAT6a plug with kink protection nozzle and unlocking tongue · Suitable for e.g. CAT6 socket / socket 940.044



CAT6a patch cable plug

918.033	3.0 m	· CAT7 cable shielded, black
918.034	5.0 m	· Conforms to IEC 61156-6 · End 1: RJ45 Hirose TM12 CAT6a plug with kink protection nozzle and unlocking tongue. End 2: CAT6a TKM 10 Gb Keystone socket. · Fits into Keystone frames 917.000 / 917.001 / 917.061 / 917.062



RJ12 patch cable plug/plug

940.089*	3.0 m	· RJ12 cable unshielded, black · Conforms to ISO / IEC 11801 and EN 50173 · End 1 and 2: RJ12 plug with kink protection nozzle · Suitable for e.g. RJ12 socket / socket 940.085
----------	-------	--

VGA 15-pole HD with and without mini stereo jack cable (stereo 3.5 mm) →

Transfer of analogue image and audio signals

Art. no.	Length	Version
----------	--------	---------



Combi cable VGA 15-pole HD with mini stereo jack

918.066	1.0 m	· High-quality cable, highly flexible, black
918.067	3.0 m	· End 1: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm
918.068	5.0 m	· End 2: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm
918.069	10.0 m	· Plug with metal housing and shielding, additional ferrite cores are not needed · Can be used with custom modules with VGA + mini stereo jack socket / socket (e.g. 917.045 etc.)



VGA 15-pole HD

918.009	1.0 m	· High-quality cable, flexible, black
940.047	3.0 m	· End 1: 1 x 15-pole VGA HD plug
940.048	5.0 m	· End 2: 1 x 15-pole VGA HD plug · Can be used with custom modules with VGA socket / socket (e.g. 917.011)

* No storage type

Media combi cable VGA 15-pole HD with mini stereo jack

(3.5 mm stereo) and RJ12 (signal control) for media switch

Art. no.	Length	Version
Combi cable VGA 15-pole HD with mini stereo jack and signal control		
903.107	1.0 m	· High-quality cable, highly flexible, black
903.108	3.0 m	· End 1: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm and RJ12 plug
903.109	5.0 m	· End 1: 1 x 15-pole VGA HD plug, 1x mini stereo jack plug, 3.5 mm and RJ12 plug
903.110	10.0 m	· Plug with metal housing and shielding, additional ferrite cores are not needed · Can be used with custom modules with VGA + mini stereo jack socket / socket and button (e.g. 917.134)



HDMI connecting cable → digital transmission of image and sound signals

Art. no.	Length	Version
HDMI connecting cable		
918.019	3.0 m	· HDMI cable, black
918.020	5.0 m	· End 1: 1 x HDMI plug 19-pole · End 2: 1 x HDMI plug 19-pole · Can be used with custom modules with HDMI socket / socket (e.g. 918.040)



DVI-I connecting cable → digital transmission of image signals

(compatible with DVI-A and DVI-D plug connectors)

Art. no.	Length	Version
DVI-I connecting cable		
918.017	3.0 m	· DVI cable, black
918.018*	5.0 m	· End 1: 1 x DVI plug · End 2: 1 x DVI plug · Can be used with custom modules with DVI-I socket / socket (e.g. 917.021 / 917.078)



Cinch video + stereo connecting cable → transmission of analogue image and sound signals

Art. no.	Length	Version
Cinch video + stereo connecting cable		
918.015*	3.0 m	· Cinch set of connecting cables, black
918.016*	5.0 m	· End 1: Cinch plug (red + white + yellow) · End 2: Cinch plug (red + white + yellow) · Can be used with custom modules with Cinch socket / socket (e.g. 917.026)



S-video (Hosiden) connecting cable → transmission of analogue image signals

Art. no.	Length	Version
S-video (Hosiden) connecting cable		
940.104*	3.0 m	· S-video (Hosiden) connecting cable, black
940.105*	5.0 m	· End 1: S-video plug · End 2: S-video plug · Can be used with custom modules with S-video socket / socket (e.g. 917.028 / 917.035)



* No storage type

3.5 mm mini stereo jack connecting cable → transmission of sound signals



Art. no.	Length	Version
----------	--------	---------

3.5 mm mini stereo jack connecting cable for sound signals

918.010	1.5 m	· 3.5 mm mini stereo jack connecting cable, black
918.011	2.5 m	· End 1: 3.5 mm mini stereo jack plug
918.012	5.0 m	· End 2: 3.5 mm mini stereo jack plug · Can be used with custom modules with mini stereo jack socket / socket (e.g. 917.045 / 917.157)

Cinch stereo connecting cable → transmission of sound signals



Art. no.	Length	Version
----------	--------	---------

Cinch stereo connecting cable for sound signals

940.049	3.0 m	· Cinch stereo connecting cable, black · End 1: Cinch stereo plug (red + white) · End 2: Cinch stereo plug (red + white) · Can be used with custom modules with Cinch socket / socket (e.g. 917.027 / 917.028 / 917.022 / 917.023)
---------	-------	---

XLR connecting cable → transmission of sound signals (e.g. from microphone)



Art. no.	Length	Version
----------	--------	---------

XLR 3-pole connecting cable for audio signals

918.013	3.0 m	· XLR 3-pole connecting cable, black
918.014	5.0 m	· End 1: XLR 3-pole plug with interlock · End 2: XLR 3-pole socket with interlock · Can be used with custom modules with XLR connection (e.g. 917.024)

USB connecting cable → transmission of data



Art. no.	Length	Version
----------	--------	---------

USB A/A connecting cable

918.021	1.0 m	· USB A/A connecting cable, black
940.045	3.0 m	· End 1: Plug A
918.022	5.0 m	· End 2: Plug A · Can be used with custom modules with USB A socket / socket (e.g. 917.120 / 917.019)

USB A/B connecting cable

940.046	3.0 m	· USB A/B connecting cable, black · End 1: Plug A · End 2: Plug B · Can be used with custom modules with USB B socket (e.g. 917.018)
---------	-------	---

FireWire connecting cable → transmission of data



Art. no.	Length	Version
----------	--------	---------

FireWire connecting cable

918.024	4.5 m	· FireWire connecting cable, black · End 1: FireWire 6-pole plug · End 2: FireWire 6-pole plug · Can be used with custom modules with FireWire socket / socket (e.g. 917.037)
---------	-------	--

Power supply cables for Bachmann facility systems



Cables fitted with Wieland GST18 plug-in connectors are available to connect facility products to the mains power supply. The advantages of these cables and their connectors, which are used all over the world, are flexibility in terms of length, the possibility of exchanging them should length requirements change, and availability for a variety of countries. Even extending the power supply to other power strips presents no problem and can usually be done without tools.

Art. no.	Length	Version
----------	--------	---------

Device supply cable, GST18 earthing contact		Black
375.000	1.5 m	· Cable: H05VV-F 3G 1.5 mm² · End 1: Right angle plug with earthing contact · End 2: Wieland GST18i3 socket
375.075	2.0 m	
375.003	3.0 m	
375.005	4.0 m	
375.007	5.0 m	
375.039	10.0 m	



Halogen-free cable		
375.044	2.0 m	· Cable: S05VV-F 3G 1.5 mm² · End 1: Right angle plug with earthing contact · End 2: Wieland GST18i3 socket
375.045	3.0 m	
375.046	5.0 m	

Device supply cable with additional earth connection

- Pre-assembled power supply cables with integrated earth connection
- Earthing of the power strip is independent of the installation
- Ideal in combination with STEP power strips (page 56 onwards)
- Table/desk-mounted frames can be earthed independently of the power strip fitted in them

Art. no.	Length	Version
----------	--------	---------

Device supply cable, GST18 earthing contact		Black
With additional earth connection		
375.115	2.0 m	· Cable: H05VV-F 3G 1.5 mm² · End 1: Right angle plug with earthing contact · End 2: Wieland GST18i3 socket with 0.3 m 1.5 mm² green/yellow with M6 ring terminal end
375.116	3.0 m	
375.117	5.0 m	



Device supply cable, GST18, CH / Switzerland plug		Black
375.016	1.5 m	· Cable: H05VV-F 3G 1.0 mm² · End 1: CH / Switzerland plug · End 2: Wieland GST18i3 socket
375.017	3.0 m	
375.018	5.0 m	



Device supply cable, GST18, UK 13A plug		Black
375.068	2.0 m	· Cable: H05VV-F 3G 1.5 mm² · End 1: UK 13A plug · End 2: Wieland GST18i3 socket
375.069	3.0 m	
375.070	4.0 m	



Device extension cable, GST18/GST18		Black
375.050	0.3 m	· Cable: H05VV-F 3G 1.5 mm² · End 1: Wieland GST18i3 plug · End 2: Wieland GST18i3 socket
375.053	1.0 m	
375.038	2.0 m	
375.055	3.0 m	



Halogen-free cable		Black
375.080	0.3 m	· Cable: S05Z1Z1-F3G 1.5 mm² · End 1: Wieland GST18i3 plug · End 2: Wieland GST18i3 socket
375.081	1.0 m	
375.082	2.0 m	
375.083	3.0 m	



Device extension cable, GST15/GST18		Black
375.127	1.5 m	· Cable: H05VV-F 3G 1.5 mm² · End 1: Wieland GST15i3 plug · End 2: Wieland GST18i3 socket
375.128	3.0 m	
375.129	5.0 m	



LanLight®

**wieland**

Cables with ST18 connector system (older system, cannot be plugged in under load)



Art. no.	Length	Version
----------	--------	---------


Device supply cable, ST18 earthing contact**Black**

375.004	1.5 m	· Cable: H05VV-F 3G 1.5 mm ²
375.079	2.0 m	· End 1: Right angle plug with earthing contact
375.040	3.0 m	· End 2: Wieland ST18/3 socket
375.076	5.0 m	

**Device extension cable, ST18/ST18****Black**

375.071	0.5 m	· Cable: H05VV-F 3G 1.5 mm ²
375.072	1.0 m	· End 1: Wieland ST18/3 plug
375.073	1.5 m	· End 2: Wieland ST18/3 socket
375.064	3.0 m	

Connectors / distributors



Art. no.	Version	Version
----------	---------	---------

Coupler**Black****No interlock**

375.500	GST/GST	· Allows easy linking of e.g. two STEP power strips with the same or different plugging systems
375.515	GST/ST	
375.516	ST/GST	· 1 x input (plug section) and 1 x output (socket section)

Multiplier, GST18**For power distribution**

375.101	1 x input, 2 x output (1)	· Input: 3-pole plug
375.102	1 x input, 2 x output (2)	· Output: 3-pole socket
375.105	1 x input, 3 x output (3)	

Through-wired for 3-phase power, 5 and 3-pole

375.106	1 x input, 1 + 6 x output	· Input: 1 x 5-pole plug
		· Output: 1 x 5-pole socket;
		· 6 x 3-pole socket per outer cable

Interlocks



Art. no.	Version	Version
----------	---------	---------

Interlock for appliance plugs and couplings**Compliant with VDE 0628**

375.518	Wieland 05.587.3156.1	· Snaps onto the corresponding plugs and couplings
---------	-----------------------	--

**Locking latch (interlock)****Compliant with VDE 0628**

375.501	Black	· For snap-in built-in plug and coupling
	Wieland 05.584.0153.0	

Accessories



Art. no.	Version	Version
----------	---------	---------

End cap


375.503	Black	· Plugs into the snap-in built-in plug and coupling
	Wieland 05.561.3653.1	

Fitting accessories



Art. no.	Version	Version
Appliance plug with screw terminal, GST18i3		
375.504	Black Wieland 92.932.3053.1	· Ready to fit, with strain relief · For cross section 0.75 – 2.5 mm ² , solid and flexible wires can be connected without end sleeves
375.517	White Wieland 92.932.3052.0	· For cable diameters 6.5 – 10.5 mm (H05VV, NYM) · Sheath stripping length 31 mm; stripped length: 7 mm
Appliance plug with spring-loaded terminal, GST18i3		
Lockable, coded		
940.073	Bright red Wieland 92.934.0553.0	· Ready to fit, with strain relief · For rigid cables 1.5 – 2.5 mm ² , flexible cables 1.5 mm ² with end sleeves
940.074	Pebble grey Wieland 92.934.0153.0	· 2 connections per pole, not mounted, for cables H05VV, NYM (diameter 7.8 – 10.3 mm) · Sheath stripping length 45 mm, insulation stripped length 1.5 mm ² and 2.5 mm ² : 9 mm
Appliance coupling with screw terminal, GST18i3		
375.505	Black Wieland 92.931.3053.1	· Ready to fit, with strain relief · For cross section 0.75 – 2.5 mm ² , solid and flexible wires can be connected without end sleeves
375.514	White Wieland 92.931.3053.0	· For cable diameters 6.5 – 10.5 mm (H05VV, NYM) · Sheath stripping length 31 mm; stripped length: 7 mm
Appliance coupling with spring-loaded terminal, GST18i3		
Lockable, coded		
940.070	Bright red Wieland 92.933.0553.0	· Ready to fit, with strain relief · For rigid cables 1.5 – 2.5 mm ² , flexible cables 1.5 mm ² with end sleeves
940.071	Pebble grey Wieland 92.933.0153.0	· 2 connections per pole, not mounted, for cables H05VV, NYM (diameter 7.8 – 10.3 mm) · Sheath stripping length 45 mm, insulation stripped length 1.5 mm ² and 2.5 mm ² : 9 mm
Built-in snap-in spring-loaded plug, GST18i3		
With interlock		
375.506	Black Wieland 92.032.9658.1	· For material thickness 0.5 – 1.5 mm; engages in cut-out in housing
375.519	White Wieland 92.032.9658.0	· Flexible cable 0.5 – 1.5 mm ² with end sleeve · Rigid cable 0.5 – 2.5 mm ²
375.520	Bright red Wieland 92.032.8558.0	· Stripped length 0.5 – 1.5 mm ² : 8 mm, stripped length 2.5 mm ² : 9 mm
375.521	Pebble grey Wieland 92.032.9758.0	
Built-in snap-in spring-loaded coupling, GST18i3		
With interlock		
375.507	Black Wieland 92.031.9658.1	· For material thickness 0.5 – 1.5 mm engages in cut-out in housing
375.523	Bright red Wieland 92.031.8558.0	· Stripped length 0.5 – 1.5 mm ² : 8 mm, stripped length 2.5 mm ² : 9 mm
375.524	Pebble grey Wieland 92.031.9758.0	





CABLE MANAGEMENT

Perfect installation solutions

Bachmann banishes unwieldy cables from workstations. The KABELSCHLANGE® cable management system allows the optimum routing of cables at workstations between desk, floor box, wall duct and various devices.

Bachmann can offer the best cable management system for every situation. Whether the cables run along the floor or are routed from the floor to the desk, the systems are mutually compatible. A well-thought-out and integrated cable management concept is available to you.

Our various systems are available as standard in black and silver colour finishes but we can supply other custom colours on request.

Individual Connecting Shortening Extending

Flexible cable management system

- The chain links are safe to step on and break-proof, and can be moved about relative to one another
- 2 connector shoulders for the transmission of forces (including torques and lateral forces)
- Special geometry enables individual cables to be unfurled through the sides of the links without risking crushing

Art. no.	Colour	Version
----------	--------	---------

Kabelschlange® Classic (for horizontal and vertical cable routing)

930.030	Black	• 3-chamber system to separate low-current, data and power cables
930.031	Silver	• 46 chain links, W x H: approx. 53 x 23 mm • Length (separated): approx. 100 cm, pushed together: approx. 72 cm



Kabelschlange® Cube (for horizontal and vertical cable routing)

930.058	Black	• 2-chamber system to separate data and power cables
930.059	Silver	• 34 chain links, W x H: approx. 55 x 25 mm • Length (separated): approx. 100 cm, pushed together: approx. 69 cm



Kabelschlange® Pro (for horizontal and vertical cable routing)

930.032	Black	• Increased resistance to being stepped on even in high foot traffic areas such as passages
930.033	Silver	• 5 chain links can withstand short-term loads of up to 120 kg • 2-chamber system to separate data and power cables • Can also be connected directly to ® Classic • 34 chain links, W x H: approx. 90 x 24 mm • Length (separated): approx. 100 cm, pushed together: approx. 70 cm



Kabelschlange® Premium Set (for horizontal and vertical cable routing)

930.049	Black	• Designer top-of-the range Premium Set:
930.050	Silver	16 chain links, W x H: approx. 70 x 35 mm 1 x metal base plate in appropriate colour 1 x connection to desk or table in appropriate colour • The chain links can be pushed together completely to form a self-locking, elliptical cable duct. • 2-chamber system to separate data and power cables • Length incl. base plate and connection to desk or table approx. 78 cm • Length without accessories approx. 75 cm • Length (pushed together): approx. 59 cm in the set



Kabelschlange® Quadro Set (for vertical cable routing)

930.016	Black	• Functional and looks-oriented set:
930.017	Silver	23 quadratic chain links, W x H: approx. 45 x 45 mm 1 x metal base plate in appropriate colour 1 x connection to desk or table in appropriate colour • The Quadro system is particularly resistant to being pulled and can therefore be used for ceiling-mounted installations in rooms up to around 5 metres in height. • 2-chamber system to separate data and power cables • Length incl. base plate and connection to desk or table approx. 76 cm



Kabelschlange® Quadro (as addition to set with art. no.: 930.016 and 930.017)

930.018	Black	• As addition to set with art. no.: 930.016 and 930.017
930.019	Silver	• For height-adjustable seating / standing combinations or desk/ table heights of 75 cm or more and for items suspended from the ceiling • 32 links, length approx. 100 cm



Kabelschlange® FLEX II Set (for vertical cable routing)

930.022	Black	• Compact and flexible set:
930.023	Silver	38 chain links, W x H: approx. 55 x 22 mm 1 x metal base plate in appropriate colour 1 x connection to desk or table in appropriate colour • 2-chamber system to separate data and power cables and for items suspended from the ceiling • Length incl. base plate and connection to desk or table approx. 75 cm



NEW

Furniture accessories

Art. no.	Colour	Version
----------	--------	---------

Kabelschlange® FLEX II (as addition to set with art. no.: 930.022 and 930.023)

930.020	Black	· For seating / standing combinations
930.021	Silver	· 54 links. Length approx. 100 cm

Easy-Bridge®

930.027	Silver	· Aluminium floor duct that can be stood on, length 100 cm · Can be connected straight to the Kabelschlange Pro® · For carpet
---------	--------	---

Easy-Bridge®

930.028	Silver	· Aluminium floor duct that can be stood on, length 100 cm · Can be connected straight to the Kabelschlange Pro® · For smooth floors
---------	--------	--

Easy-Steel® assembly rod

930.024*		· Dimensions: Length 750 mm, diameter 5 mm
----------	--	--

Easy-Desk-3G®

930.025*	Silver	· Securing Easy-Steel® assembly rod
----------	--------	-------------------------------------

Easy-Connect®

930.026*	Silver	· Universal coupling
----------	--------	----------------------

Easy-Desk-2B®

930.029	Black	· Adapter for connecting vertically to furniture
930.090	Silver	· Can be combined with Easy-Stop® and Easy-Steel® · Includes 2 screws 4 x 12 mm

Easy-Stop-2B2K®

930.091	Black	· 3-part cable strain relief for Kabelschlange® Classic, Cube, Pro
930.092	Silver	· Can be combined with Easy-Desk-2B® and Easy-Steel® · Includes clamping screws

Cable bracket set with strain relief

930.051	Black	· For screwing into place underneath the top of a desk or table · consisting of: cable bracket incl. 2 fixing screws and strain relief with adjusting screw
---------	-------	--

E-Cube-K-540® power column for power and data supply

930.166		· To hold sockets indoors (e.g. art. no.: 333.0122) · Material: anodised aluminium / plastic · Dimensions: Height approx. 54 cm/ cover approx. 22.3 x 22.3 cm/ floor approx. 24 x 24 cm · Hole size 80 mm including Easy Outlet® telescopic cover
---------	--	--

Accessories for connecting to floor

Art. no.	Colour	Version
----------	--------	---------

Easy-Outlet® floor unit

930.098*	Black	· Floor-level built-in unit
930.099*	Silver	· High-tensile splayed attachment · Suitable for dry-maintained raised and false floors

Easy-Cover® telescopic cover for floor unit

930.100*	Black	· Telescopic cover set for Easy-Outlet® floor unit
930.137	Silver	

* No storage type

NEWIllustration shows
930.099 and 930.137

Accessories for connecting to floor

Art. no.	Colour	Version
Easy-Cover-I® (system connection for floor unit)		
930.162*	Black	· Connection for 1 x Cube, Pro, Classic or Flex
930.138*	Silver	· Material: PP for use in floor outlet
Easy-Cover-II® (system connection for floor unit)		
930.163*	Black	· Connection for 2 x Cube, Pro, Classic or Flex
930.139*	Silver	· Material: PP for use in floor outlet
Easy-Cover-Quadro® (system connection for floor unit)		
930.164*	Black	· Connection for 1 x Kabelschlange® Quadro
930.160*	Silver	· Material: PP for use in floor outlet
Easy-Cover-Premium® (system connection for floor unit)		
930.165*	Black	· Connection for 1 x Kabelschlange® Premium
930.161*	Silver	· Material: PP for use in floor outlet
Easy-Switch® distributor (for Kabelschlange® Classic, Cube, Pro)		
930.034*	Black	· 3-way distributor
930.035*	Silver	· includes 4 coupling links KS Cube®
Easy-Switch® distributor (for Kabelschlange® Classic, Cube, Pro and a vertical connection K. Premium)		
930.057*	Black	· 4-way distributor with fixing screw and base plate · includes 4 coupling links KS Cube®
Easy-Cap®		
930.044*	Black	· Cover cap for Easy-Switch connections that are not being used
930.045*	Silver	
Easy-Clip-S® floor outlet adapter for all common floor outlets		
930.036*		· For floor outlet for Kabelschlange® Classic · Dimensions: L x W: approx. 86 x 47 mm
Easy-Clip-L® floor outlet adapter for all common floor outlets		
930.054*		· For floor outlet for Kabelschlange® Pro and Cube · Dimensions: L x W: approx. 91.5 x 51 mm



Accessories for connecting to ceiling

Art. no.	Colour	Version
Easy-Cover-B® (system connection with low transfer of force to suspended ceilings)		
930.093*	White	· Blank cover made of polypropylene
Easy-Cover-I® (system connection with low transfer of force to suspended ceilings)		
930.094*	White	· Connection for 1 x Cube, Pro, Classic or Flex · Material: POM for suspended ceilings
Easy-Cover-II® (system connection with low transfer of force to suspended ceilings)		
930.095*	White	· Connection for 2 x Cube, Pro, Classic or Flex · Material: POM for suspended ceilings
Easy-Cover-Quadro® (system connection with low transfer of force to suspended ceilings)		
930.096*	White	· Connection for 1 x Kabelschlange® Quadro · Material: POM for suspended ceilings
Easy-Cover-Premium® (system connection with low transfer of force to suspended ceilings)		
930.097*	White	· Connection for 1 x Kabelschlange® Premium · Material: POM for suspended ceilings

* No storage type



BRIDGE – the cable duct




Art. no.	Length	Version
----------	--------	---------

CABLE BRIDGE**Dimensions: (W x H) 146 x 9 mm**

Cable duct, straight

930.060	1.0 m	· Anodised aluminium profile, rippled for anti-slip effect
930.061	2.0 m	· 3-chamber system allowing power and data cables to be routed separately
· Can be fixed with double-sided tape or screwed into place on the floor (see fixing accessories)		

**CABLE BRIDGE**


Bracket for cable duct

930.062	45°	· Bracket made from anodised aluminium
930.063	90°	

**CABLE BRIDGE**

Linking element for cable duct

930.064	Straight	· Link for connecting straight cable ducts
· Screwed into place with integral Allen keys		
· 2 items		

**CABLE BRIDGE**

Fixing accessories for cable duct

930.065	Straight	· For screwing on the ends of the cable ducts
· 4 items		



Wrap textile-fibre sleeves

Wrap textile-fibre sleeves bundle and protect cables and wires in office and home environments.


The elastic braided sheath with its monofilament fibres assures fire and abrasion resistance and is thus also ideal for professional and industrial use.



Automatic Wrap

The benefits at a glance

- Simple installation with low costs and low labour input
- More flexible than coiled or wound solutions
- 25 % overlap for secure cable bundling
- Resistant to chemicals and solvents
- Halogen-free
- Resistant to cuts and abrasions
- Retains its shape within operating temperature range -75 °C to +125 °C



Art. no.	Length	Version
----------	--------	---------

Automatic Wrap

Dimensions: diameter 2.54 cm = 1 inch

930.900	1.0 m	• Black
930.901	2.0 m	• Black
930.902	3.0 m	• Black

Automatic Wrap

Dimensions: diameter 5.08 cm = 2 inches

930.903	1.0 m	• Black
930.904	2.0 m	• Black
930.905	3.0 m	• Black



Manual Wrap in colour

The benefits at a glance

- Strong Velcro fastener for frequent access
- Can be stretched over plugs and sockets
- Halogen-free
- Resistant to chemicals and solvents
- Melting point ~230 °C



Art. no.	Version	Version
----------	---------	---------

Manual Wrap

Dimensions: diameter 3.18 cm = 1 ¼ inches

930.906*	1.0 m	• Black
930.907*	2.0 m	• Black
930.908*	3.0 m	• Black

Dimensions: diameter 5.08 cm = 2 inches

930.909*	1.0 m	• Black
930.910*	2.0 m	• Black
930.911*	3.0 m	• Black



* No storage type

4-key keypad

Programmable illuminated buttons for controlling equipment and media.

10-inch (10") panel

A mounting frame with a standardised width of 10" = 254 mm, with holes for bolting to 10" racks. Used for events equipment, media and laboratory systems and in data centres. As a rule the panels have a height of 1 height unit (1 U) with a specified height of 1.75" = 44.5 mm.

19-inch (19") panel

A mounting frame with a standardised width of 19" = 482.6 mm, with holes for bolting to 19" racks. Frequently used for events equipment, media and laboratory systems and in data centres. As a rule the panels have a height of 1 height unit (1 U) with a specified height of 1.75" = 44.5 mm.

Audio jack or tip-ring-sleeve (TRS) connector

Internationally accepted electrical connector for AC or DC in the low-voltage (SELV – safety extra-low voltage) range. Jack plugs, sockets and couplings are used most typically for audio signals or for connecting a small electronic device to a power supply unit. Jack plugs are often used for connecting headphones to audio equipment. Versions available: **3.5 mm (mini audio jack)** for portable devices (MP3 players, Discmans etc.), sound cards and small headphones. **6.35 mm (jack)** for stereo systems and electronic music equipment (mixing desks, effects units, synthesisers, keyboards, electric pianos, electric guitars and guitar amplifiers).

BNC connectors – Bayonet Neill Concelman

These are coaxial connectors with a bayonet lock for high frequencies up to approx. 1 GHz, in some cases up to 4 GHz, with a defined wave impedance of 50 or 75 Ω (interchangeable). They are used chiefly in radio and video systems. The BNC design has however also been used for the transmission of weak DC and low-frequency AC signals and impulses in laboratory applications because of the shielding of the outer conductor from electrical interference. The coaxial construction thus provides protection against external electric fields. For this reason, connections to measuring devices such as oscilloscopes, frequency counters and function generators generally use BNC-type cables.

Bandwidth

The difference between two frequencies that form the limits of a specific, unbroken frequency range between them.

Blank

Function in video output devices of switching to a black still frame.

CAT

In data connection technology the following main categories and classes for equipment performance are generally accepted:

Category	Class	MHz	GB
CAT5e	D	100	1
CAT6	E	250	1
CAT6a	E	500	10
CAT7	F	600	10
CAT7a	F	1.000	

The difference between category and class is that the individual components such as cable, socket, connector etc. are graded into categories. The overall performance of the sum of these components, i.e. of the complete data network, is referred to as the class. The class of the network as a whole is thus determined by the weakest component. Example: CAT6 cable and plug are connected to a CAT5e socket, the overall network attains only class D. Additionally, a distinction is made in data connection equipment between shielded and unshielded components. Worldwide, unshielded versions are most commonly used; however, in Germany almost 100% of cabling is shielded. The currently applicable standard for this area of data connection technology is summarised in EN 50173.

Cinch (RCA)

For non-standardised connectors for electrical signals, primarily on coaxial cables. Use: Audio white = left analogue channel (sometimes also black); Audio red = right analogue channel; Orange = digital audio; Video yellow = composite video, analogue unmodulated TV picture signal in baseband (VBS or CVBS); Video green = Y (brightness); Video blue = Pb (colour difference); Video red = Pr (colour difference)

Coaxial ('coax') cable

Coaxial cable is a special type of cable with concentrically arranged conductors for carrying high-frequency signals, such as in TV systems for analogue CVBS or for digital studio signals (DSC).

Composite Video

See **Cinch (RCA)**

Control unit

See **Media control systems**

Crossover

In computer networking, a cross or crossover cable is an eight-wire twisted-pair cable with an RJ45 plug at each end, but where some of the wires have been swapped over in one of the plugs. It is required e.g. where two computers are connected together directly. It is also possible, instead of a crossover cable, to use an uncrossed cable in conjunction with a crossover adaptor to obtain the required crossing of wire pairs. The simplest use of a crossover cable is to link two computers with network cards without necessarily requiring a hub or switch. The two computers thus connected form a complete network on the smallest possible scale. Crossover cables can normally be dispensed with in gigabit Ethernet, since Auto-MDI-X is defined in the standard for this and is supported by most devices. In a crossover cable, the sent data wire is crossed with the received data wire at one end, so that data exchange is possible over a direct connection. If the send and receive wires had not been swapped at one end, no link between the machines would be obtained.

CVBS

See **Cinch (RCA)**

DVB – Digital Video Broadcasting

By 2010 all radio and TV channels in Germany are expected to be transmitted via digital video broadcasting (DVB). The transmission paths available are terrestrial frequencies (DVB-T), cable (DVB-C) and satellite (DVB-S). A mobile radio standard (DVB-H) is still at the testing stage. In all cases a special receiver is required to receive the signal.

DVB-T allows up to 24 TV channels to be received via a conventional domestic TV antenna. The channels are broadcast without encryption and are free of charge. So far, commercial broadcasters have only engaged in DVB-T in urban areas.

DVB-C offers more channels – theoretically up to 500. However, a prerequisite for receiving the signal is a paid-for cable connection. Commercial broadcasters using the digital cable network usually encrypt the signal, which then requires a smart card from the network operator to decode.

Display port

A port for conveying image and sound signals (e.g. monitor, DVD player, plasma TV etc.).

DVI – Digital Video Interface

A digital interface for video signals. In this system the sound has a separate input. The high-definition (HD) formats however use the new HDMI input. There are three different types of digital video interface:

DVI-A carries analogue signals only,
DVI-I is capable of transmitting both analogue and digital signals, and **DVI-D** carries digital signals only. If the new TFT monitor has a DVI-D interface, the old graphics card with analogue VGA output cannot be connected to it.

EIB

The European Installation Bus (EIB) is a standard to EN50090 that describes how sensors and actuators should be connected together in a domestic installation. It also defines the communications protocol. The EIB thus controls, for example, lighting and shutters or other shade-providing devices, heating, locking and alarm systems. EIB has subsequently been further developed and been known since 2002 as the KNX standard.

Ethernet

A protocol that controls data transfer in local area networks (LANs). This standard was developed by the Californian Xerox corporation in 1976.

F connectors

(IEC 60169-24) are coaxial plugs with screw locking designed for high frequencies up to about 5 GHz with a defined wave impedance of 75 Ω. The most commonly used connector in satellite television systems worldwide.

FireWire

The FireWire interface is used for rapid data exchange between a computer and multimedia or other peripheral devices. Thanks to its high transfer rate, FireWire can also be used as an alternative to Ethernet (IP over FireWire).

Full HD TV

Full HD models offer TV and video images with 1920 x 1080 pixels – currently the highest pixel number in HDTV broadcasts or high-definition feeds. This picture quality represents five times the resolution of conventional TV pictures. Even when observed close up, the viewer cannot see any kind of pixel structure. Video projections profit in particular from full HD resolution. The term is mostly used to describe the ability of an HDTV-capable device to output the highest possible HD resolution.

Hardware detect

Automatic detection of incoming signals, e.g. if a laptop is connected to an output device while switched on, the output device automatically recognises this newly-connected device.

HDMI – High Definition Multimedia Interface

Interface for picture and sound information in HDTV and HD television systems. It enables fully digital transmission of video and digital sound with up to eight channels. The HDCP digital copy-protection system is built in.

HDTV – High Definition Television

HDTV has significantly higher resolution, shows the picture more sharply and with more detail, and is broadcast with an aspect ratio of 16:9 rather than the traditional 4:3. Resolution is up to 1920 x 1080 pixels. To receive HD pictures, a TV set is required that carries the "HD ready" seal.

Hi-Fi – High Fidelity

Hi-Fi (high fidelity) is a quality standard for audio playback equipment.

Hosiden

See **S-Video**.

Impedance

Impedance, sometimes also known as AC resistance, states the ratio of electrical voltage across a consumer (component, cable etc.) to the current drawn. Impedance is important when matching high-frequency cables and also in the transmission of electromagnetic waves in free space. If for example the input impedance of a device does not match that of the incoming cable, reflections occur that reduce the energy transmitted and that can cause resonance effects and thus a non-linear frequency response.

ISDN – Integrated Services Digital Network

International standard for a digital telephone network. Allows multiple channels to transmit simultaneously. A basic ISDN connection offers the user two independently available channels for telephone or internet. Bandwidth is 64 kb/s.

Keystone

Universal dimensions (19.3 x 14.7 mm) for cutouts for mounting components.

KNX

KNX technology resulted from the confluence of three European bus standards, the European Installation Bus (EIB), the European Home Systems Protocol (EHS) and Batibus (used in heating/ventilation/climate control) to create a unified technological platform for all areas of home and building systems in the form of an international industry standard. KNX allows central control of practically all components of home and building systems technology, from lighting through heating to alarm systems, and offers advantages of convenience, security and economy for functional buildings as well as in residential settings. The KNX specification was presented by the then newly founded KNX Association in spring 2002. Based on the EIB standard, with which the new technology platform remains fully compatible, KNX emerged from expansions using new configuration mechanisms and transfer media that had originally been developed for Batibus and EHS. By 2003 KNX was ratified by CENELEC, the Brussels-based European committee for electrical standards, as European Standard EN 50090. Shortly afterwards it was ratified by the CEN standards institute under EN 13221-1 as the European standard for the automation of buildings.

**LAN – Local Area Network**

Computer network that links various computers and peripheral devices via cables or wireless over a restricted physical area.

Loudspeaker connections

Stereo (red + white) screw terminals for audio signals.

LC

This connector is similar to the SC but smaller.

Media control

Control of video, power, lighting and audio systems in a building. Sound, light and video are controlled by appropriate commands. Media control allows all the devices to be used in a presentation to be linked and controlled in the desired time sequence.

Mini audio jack

A 3.5 mm jack socket for audio signals (e.g. from laptop or PC to loudspeakers).

Mini USB

A compact plug or socket version of the USB standard. This version was developed for devices with restricted space such as mobile telephones and digital cameras.

MTRJ

An optical connector that accepts two fibres; the junctions are embedded in a common plastic block in the shape of an RJ45 connector. This design also prevents any confusion of the outward and return line and is easy to insert and to remove. This connector is suitable for single-mode and multi-mode fibres.

MUTE

Switching of audio devices to silence.

OWG – Optical waveguides

Cables made up of, or including, optical fibre conductors with connectors for transmitting optical signals in the visible, ultraviolet or infrared ranges. Fibre-optic cables form a reasonably pliable medium for transmitting optical signals or even higher-powered optical radiation.

Overvoltage protection with filter

Overvoltage protection – conforms to DIN VDE 0620-1:-2002-01, EN 61643-11:08-2007, type 3, discharge current 6.5 kA, response time < 25 nS. Suitable for 16A (miniature fuse on request) with varistors, temperature fuse, gas discharge arrester, visual LED function and failure indicator (acoustic signalling also available on request). Mains and frequency filters – conforming to VDE 0565-3:05-2006 for voltage peaks up to 30 MHz, damping diagram on data sheet.

PAL – Phase Alternating Line

The conventional television standard in Europe for analogue TV signals with a resolution of 720 x 576 pixels.

Potential-free contact

Used for communicating a status between electrical devices. Contact is normally established via a relay or optical coupler. This ensures that the electric circuits of the respective devices remain galvanically isolated from one another. This solution is the simplest and safest method for e.g. transmitting digital data electrically.

PowerCON

A type of 3-pole power connector with coding and interlocking, most frequently used for stage equipment. The interlock mechanism protects against the plug being accidentally pulled out of its socket.

PS/2 interface (PS/2 connection, PS/2 port, originally 'auxiliary port'). Commonly used 6-pin serial interface for input devices (e.g. mouse and keyboard) on personal computers.

Pushbutton

Illuminated blue, various types, e.g. in desk control panels for controlling equipment. Rocker buttons are used for up/down control of external devices, e.g. screen, blinds etc.

Pushbutton: automatic switchoff

Power strips that feature an automatic switchoff device are used to automatically switch off the power to the connected equipment. Pressing the button subsequently restores power to the connected equipment.

Pushbutton: stainless steel

For connection by the user to control equipment and media.

RCA

See **Cinch (RCA)**

RGB signal

In a RGB signal the colours red, green and blue are each transmitted and/or stored in their own channel. RGB signals are used for video transmission e.g. on computers with a VGA interface or in video systems with SCART connections.

RJ (registered jack) connectors

These are standardised connectors for telecommunications cables. The standards describe the physical form of plugs and sockets and their contact configurations, and are designated by the letters RJ and a number (e.g. RJ-45), with or without the hyphen. Examples: RJ12 6P6C/RJ45 8P8C

RJ12

see **RJ (registered jack) connectors**

Router

A device that forwards data packets through various networks. The router serves to calculate the connections between, for example, two local networks (LANs) and automatically establishes the optimum path for the data packets.

RS-232

Serial interface standard with 25-pole or 9-pole connector for serial data transmission. Also known as V.24. Both one-to-one pinouts and crossover configurations are commonly used.

SC

An optical connector used in new LAN installations. The right-angled design can be used for multi-mode and single-mode (monomode) glass fibres. Average insertion loss is about 0.2 dB, maximum approx. 0.4 dB. The advantage of SC over the ST connector is the push-pull design – i.e. the plug locks in automatically when inserted and is released when pulled out. This allows the use of duplex connectors (two connectors linked by a duplex clip) and duplex connections can be inserted or removed simultaneously.

Speakon

A connector designed for loudspeakers, offering a robust construction, a 20 A contact current capacity and secure interlocking. Speakon connectors are available in two-pole, four-pole and eight-pole versions; the 2-pole and 4-pole types are mutually compatible. The eight-pole version has a larger physical size. The number of contacts available in a single connector makes it possible to connect multi-channel passive systems, satellite subwoofer systems or multi-channel monitor loudspeaker constellations via a single cable.

ST

This connector (also known as a BFOC connector) is common in LANs and is suitable for single-mode and multi-mode optical fibre cables. Average insertion loss is about 0.3 dB, maximum approx. 0.5 dB.

S-Video/ Super Video system

S-Video, also known as the Y/C process, designates a special analogue video signal process in which the 'luminance' (brightness) information is transmitted and processed separately from the 'chrominance' (colour information). An example application of S-Video is in VHS video recorders.

S-VHS – Super Video Home System

An improved, downward-compatible VHS standard for home video-band recording that offers better picture resolution and greater colour accuracy. Horizontal image resolution is some 2/3 better than in VHS. S-VHS is a standard, not a connector. The S-VHS standard signal may however be transmitted via the S-Video (Hosiden) connector.

Switch

A network component for linking multiple computers or network segments within a local area network (LAN). Switches analyse network traffic and make logical decisions.

TOSLINK

A standardised optical waveguide connection system for optical signals in the range up to about 20 Mbps. Used to carry digital audio signals between audio devices.

TrueHD

Audio standard for high-resolution media such as Blu-ray and HD DVD. TrueHD allows 100 % loss-free compression of audio data. The codec allows a data rate of up to 18 Mbps.

USB – Universal Serial Bus

USB is used to connect a variety of devices together by cable. USB is a bit-serial bus on which the individual bits of a data packet are transmitted one after another. Devices with USB can be connected to one another while operating, since the newly connected devices are automatically detected. USB is used to connect, for example, printers, digital cameras, MP3 players and hard disks to a computer.

VBS

See **Cinch (RCA)**

VGA / audio switch


Switches between multiple input sources (e.g. several laptops) as required and forwards the signal to output media devices (e.g. projector, monitor, loudspeaker).

VGA – Video Graphics Array

refers to a computer graphics standard (EISA, 1987) that defines specific combinations of image resolution and number of colours (colour bit depth) as well as repeat frequency. VGA allows a resolution of 640 x 480 pixels, while VGA cables allow a higher resolution. The 15-pole VGA socket is used to transmit image signals (e.g. from laptop or PC monitor to a projector, VGA switch box etc.)

XLR

Industry standard for electrical plug connections. Used in professional public-address and recording studio systems. 3-pole XLR connectors are used for analogue microphone and loudspeaker signals and for digital AES/EBU signals. 5-pole connectors are used for DMX digital lighting control data.



M earthing contact 35° / 90° Earthing contact

Socket type: earthing contact 16A/250V~ max. 3600W

- Conforms to DIN VDE 0620-1 Design DIN 49 440
- Colours: black, red, white, grey
- Set at 35°
- Module width 42.5 mm
- For use in: Germany, Austria, Netherlands, Italy (parts), Spain, Portugal, Sweden, Norway, Finland, Slovenia, Romania, Hungary, Afghanistan, Andorra, Vatican State, San Marino, Estonia, South Korea, Indonesia, Iceland, Chile, Bulgaria



M-UTE 35° / 90° France

Socket type: UTE / France 16A/250V~ max. 3600W

- Conforms to NF C 61-314
- Child-proof
- Colours: black, red, white, grey
- Set at 35°
- Module width 42.5 mm
- For use in: France, Belgium, Poland, Monaco, Slovakia, Czech Republic



M-UTE IT red France

Socket type: UTE / France IT red 16A/250V~ max. 3600W

- Conforms to NF C 61-314
- Child-proof and with additional plug-in fuse
- Colour: red
- Set at 35°
- Module width 42.5 mm
- For use in: France, Belgium, Poland, Monaco, Slovakia, Czech Republic



M-CH 0° / 90° Switzerland

Socket type: Switzerland CH 10A/250V~ max. 2500W

- Conforms to SEV 1011:98
- Colours: black, red
- Set at 0°
- Module width 35 mm
- For use in: Switzerland, Liechtenstein



M-USA 0° USA

Socket insert, USA 15A/115V~ max.

- Conforms to UL
- Colour: black
- Set at 0°
- Module width 32 mm
- For use in: USA, Canada, Mexico, South America (some regions)



M-UK FUSE 45° UK

Socket insert, UK, individually fused, 3.15A/240V~ or 5A/240V~

- Conforms to BS 5733:1995
- Individually fused, selectable 3.15A or 5A
- Child-proof
- Colour: black
- Set at 45°
- For use in: UK as per standard for office furniture



M-UK 90° UK

Socket type: UK 13A/240V~

- Conforms to BS 1363
- Child-proof
- Colour: black
- Set at 90°
- Module width 54 mm
- For use in: UK, Ireland, Singapore, Malaysia, Cyprus, Malta, Hong Kong, Dubai


M-IT 35°

Italy



Socket outlet combination with protective contact / Italy 10A/230V or 16A/230V~

- Child-proof
- Colour: black
- Set at 35°
- Module width 45 mm
- For use in: Italy, South Tyrol, South America (some regions)

**M-AUS 90°**

Australia



Socket outlet combination Australia 10A/250V

- Conforms to AS/NZS 3112
- Colour: black
- Set at 90°
- Module width 45 mm
- For use in: Australia, New Zealand, Argentina

**M-CN 90°**

China



Socket insert, China, 10A/250V

- Conforms to CCC
- Colour: black
- Set at 90°
- Module width 42.5 mm
- Can be used in China


**M-DK 35°**

Denmark



Socket type: Denmark household 10A/250V~

- Conforms to DS/IEC 60884-1:2004
- Colour: black
- Set at 35°
- Module width 42.5 mm
- For use in: Denmark

**M-DK EDV 35°**

Denmark



Socket type: Denmark IT 10A/250V~

- Conforms to DS/IEC 60884-1:2004
- Colour: black
- Set at 35°
- Module width 42.5 mm
- For use in: Denmark

**M-IEC 10A**

Socket insert, non-heating appliance socket, 10A/250V~

- Conforms to IEC 320
- Colour: black
- Set at 90°
- Module width 42.5 mm
- Can be used internationally

**M-IEC 16A**

Socket insert, non-heating appliance socket, 16A/250V~

- Conforms to IEC 320
- Colour: black
- Set at 90°
- Module width 42.5 mm
- Can be used internationally

**M-GST18i3**

Socket insert GST18i3 16A/250V~

- Conforms to DIN VDE 0628
- Colours: black, red, white, pebble grey
- Set at 90°
- Module width 42.5 mm
- Can be used internationally



3-pole plug systems with earthing contact

Suitable for all European countries except Italy, England and parts of Switzerland.

**Right angle plug with earthing contact Type 30**

With dual earthing contact system



Suitable for (e.g.):

- H03VV-F 3G 0.75 mm²
- H05VV-F 3G 0.75 mm²
- H05VV-F 3G 1.00 mm²
- H05VV-F 3G 1.50 mm²
- H07BQ-F 3G 1.50 mm²
- H05BQ-F 3G 0.75 mm²

**Central plug with earthing contact Type 31**

With dual earthing contact system



Suitable for (e.g.):

- H03VV-F 3G 0.75 mm²
- H05VV-F 3G 1.00 mm²
- H05VV-F 3G 1.50 mm²
- 05RV4-F 3G 0.75 mm²
- H03V4V4-H 3G 1.00 mm²
- H03RT-H 3G 0.75 mm²

**Central plug with earthing contact Type 32**

With dual earthing contact system and splash water protection



Suitable for (e.g.):

- H05VV-F 3G 1.50 mm²
- H05RR-F 3G 0.75 mm²
- H05RR-F 3G 1.50 mm²
- H07RN-F 3G 1.00 mm²
- H07RN-F 3G 1.50 mm²
- H07BQ-F 3G 1.50 mm²
- H07RN-F 3G 2.50 mm²

**Earthing contact coupling Type 34**

Suitable for (e.g.):

- H05VV-F3G 1.00 mm²
- H05VV-F 3G 1.50 mm²
- H05VV-F 3G 2.50 mm²
- H07RN-F 3G 1.00 mm²
- H07RN-F 3G 1.50 mm²

Swiss plugs and couplings

Version tested by SEV.

**Swiss plug Type 11, 10 A**

2-pole




Suitable for (e.g.):

- H03VH2-F 2 x 0.75 mm²
- H05VH2-F 2 x 1.0 mm²
- H05VV-F 2 x 1.00 mm²

**Swiss plug Type 12, 10 A**

3-pole



Suitable for (e.g.):

- H05VV-F 3G 1.00 mm²
- H05VV-F 3G 1.50 mm²

**Swiss coupling Type 11 D**

2-pole



Suitable for (e.g.):

- H03VH2-F 2 x 0.75 mm²
- H03VV-F 2 x 0.75 mm²
- H05VV-F 2 x 1.00 mm²

**Swiss plug Type 23, 10 A / 16 A**

3-pole



Suitable for (e.g.):

- H05VV-F 3G 1.00 mm²
- H05VV-F 3G 1.50 mm²



International plugs

Plug with protection class 0 **Type 44**
2-pole

Suitable for (e.g.):

- H03VV-F 2 x 0.75 mm²
- H05VV-F 2 x 0.75 mm²
- H05VV-F 2 x 1.00 mm²
- H05VV-F 2 x 1.50 mm²



UK plug **Type 45-2, 13 A**
2-pole, moulded, with 13 A fuse fitted

Suitable for (e.g.):

- H03VH2-2 x 0.75 mm²
- H05VH2-2 x 0.75 mm²
- H03VV-F 2 x 0.75 mm²
- H05VV-F 2 x 0.75 mm²
- H05VV-F 2 x 1.00 mm²



UK plug **Type 45, 13 A**
3-pole, moulded, with 13 A fuse fitted

Suitable for (e.g.):

- H03VV-F 3G 0.75 mm²
- H05VV-F 3G 0.75 mm²
- H05VV-F 3G 1.00 mm²
- H05VV-F 3G 1.50 mm²



USA plug UL/CSA **Type 46-2**
2-pole

Cable types to suit your requirements.



USA plug UL/CSA **Type 46**
3-pole

Cable types to suit your requirements.



Italy plug **Type 49, 10 A**
3-pole

Suitable for (e.g.):

- H05VV-F3G 0.75 mm²
- H05VV-F3G 1.00 mm²



Italy plug **Type 50, 16 A**
3-pole

Suitable for (e.g.):

- H05VV-F3G 1.50 mm²



Denmark plug **Type 47, 10 A**
3-pole

Suitable for (e.g.):

- H05VV-F3G 0.75 mm²
- H05VV-F3G 1.00 mm²
- H05VV-F3G 1.50 mm²



Denmark right angle plug **Type 47W, 10 A**
3-pole

Suitable for (e.g.):

- H05VV-F3G 0.75 mm²
- H05VV-F3G 1.00 mm²
- H05VV-F3G 1.50 mm²



Denmark IT plug **Type 48, 10 A**
3-pole

Suitable for (e.g.):

- H05VV-F3G 0.75 mm²
- H05VV-F3G 1.00 mm²
- H05VV-F3G 1.50 mm²



Denmark right angle plug **Type 48W, 10 A**
3-pole


Suitable for (e.g.):

- H05VV-F3G 0.75 mm²
- H05VV-F3G 1.00 mm²
- H05VV-F3G 1.50 mm²



2-pole plug systems without earthing contact

Suitable for all European countries except Italy, England and parts of Switzerland.

**Euro flat plug****Type 20 F**

Suitable for (e.g.):

- H03VVH2-F 2 x 0.75 mm²
- H05VVH2-F 2 x 0.75 mm²

**Euro flat plug****Type 20**

Suitable for (e.g.):

- H03VVH2-F 2 x 0.75 mm²
- H05VVH2-F 2 x 0.75 mm²
- H03VV-F 2 x 0.75 mm²
- H05VV-F 2 x 0.75 mm²

**Contour plug****Type 24 G**

Suitable for (e.g.):

- H05RN-F 2 x 1.00 mm²
- H07RN-F 2 x 1.00 mm²
- H07RN-F 2 x 1.50 mm²
- H05BQ-F 2 x 1.00 mm²
- H07BQ-F 2 x 1.50 mm²

**Contour plug****Type 24 K**

Suitable for (e.g.):

- H05VV-F 2 x 0.75 mm²
- H05VV-F 2 x 1.00 mm²

**Contour plug****Type 24 S**

Splash water protected, impact resistant

Suitable for (e.g.):

- H07RN-F 2 x 1.00 mm²
- H07RN-F 2 x 1.50 mm²
- H05BQ-F 2 x 1.0 mm²
- H05BQ-F 2 x 1.5 mm²

IEC appliance connectors

Non-heating appliance plug, central Type 35 S 2-pole, 70 °C Suitable for (e.g.): · H05VV-F 2 x 0.75 mm ² · H05VV-F 2 x 1.00 mm ²	 	Non-heating appliance plug, central Type 35 S 3-pole, 70 °C Suitable for (e.g.): · H05VV-F 3G 0.75 mm ² · H05VV-F 3G 1.00 mm ²	 
Non-heating appliance socket outlet, central Type 35-2 2-pole, 70 °C Suitable for (e.g.): · H05VV-F 2 x 0.75 mm ² · H05VV-F 2 x 1.00 mm ²	 	Non-heating appliance socket outlet, central Type 35 3-pole, 70 °C Suitable for (e.g.): · H05VV-F 3G 0.75 mm ² · H05VV-F 3G 1.00 mm ²	 
Side-entry non-heating appliance socket Type 35-2 W 2-pole, right, left, 70 °C Suitable for (e.g.): · H05VV-F 2 x 0.75 mm ² · H05VV-F 2 x 1.00 mm ²	 	Side-entry non-heating appliance socket Type 35 W 3-pole, right, left, 70 °C Suitable for (e.g.): · H05VV-F 3G 0.75 mm ² · H05VV-F 3G 1.00 mm ²	 
Small appliance socket Type 25 D 120 °C, fitted Suitable for (e.g.): · H03WH2-F 2 x 0.75 mm ²	 	High-temperature appliance socket Type 37 155 °C, fitted Cable types to suit your requirements.	 

Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.
28	317.000	132	375.040	44	902.008	71	903.001	59	906.031	21	911.905
28	317.001	131	375.044	44	902.009	102	903.100	60	906.067	21	911.906
28	317.006	131	375.045	44	902.010	102	903.101	59	906.071	21	911.907
29	317.100	131	375.046	44	902.011	103	903.102	59	906.080	21	911.908
29	317.101	131	375.050	45	902.012	110	903.103	59	906.1059	21	911.909
29	317.102	131	375.053	45	902.0161	104	903.104	59	906.1075	21	911.910
28	317.117	131	375.055	44	902.017	109	903.105	59	906.1086	21	911.913
22	333.1007	132	375.064	45	902.017	109	903.106	59	906.1306	22	912.000
22	333.1008	131	375.068	44	902.018	115	903.107	16	909.000	126	912.000
60	336.003	131	375.069	45	902.018	129	903.107	17	909.001	23	912.001
60	336.004	131	375.070	45	902.0182	115	903.108	16	909.002	126	912.001
60	336.006	132	375.071	45	902.0183	129	903.108	16	909.0023	22	912.002
60	336.014	132	375.072	45	902.0184	115	903.109	17	909.0026	22	912.003
60	336.015	132	375.073	45	902.0185	129	903.109	17	909.0027	23	912.004
59	336.039	131	375.075	44	902.019	115	903.110	17	909.0028	23	912.005
59	336.046	132	375.076	45	902.019	129	903.110	17	909.0029	22	912.0055
60	336.065	132	375.079	44	902.024	114	903.111	16	909.003	23	912.006
59	336.067	131	375.080	44	902.039	114	903.112	16	909.004	23	912.007
59	336.072	131	375.081	53	902.200	114	903.113	17	909.005	23	912.008
59	336.076	131	375.082	54	902.201	109	903.114	16	909.0056	22	912.009
59	336.079	131	375.083	54	902.202	97	903.2000	16	909.0057	22	912.010
59	336.088	132	375.101	53	902.203	97	903.2001	16	909.0058	23	912.011
59	336.600	132	375.102	53	902.204	97	903.3000	16	909.0059	23	912.012
115	336.600	132	375.105	53	902.2049	97	903.3001	17	909.006	23	912.0122
59	336.601	132	375.106	54	902.205	98	903.400	16	909.0060	23	912.0123
59	336.603	131	375.115	53	902.206	98	903.500	17	909.007	23	912.0124
59	336.604	131	375.116	53	902.207	98	903.600	17	909.008	23	912.0125
59	336.606	131	375.117	53	902.208	38	904.000	17	909.009	23	912.013
59	336.626	131	375.127	54	902.209	38	904.0001	16	909.010	23	912.014
25	338.0080	131	375.128	53	902.211	38	904.001	16	909.011	22	912.015
25	338.0081	131	375.129	53	902.213	38	904.002	17	909.012	22	912.0156
11	338.0200	132	375.500	53	902.214	38	904.003	17	909.013	22	912.016
11	338.0201	132	375.501	54	902.228	38	904.004	17	909.014	22	912.0167
20	338.0203	61	375.502	55	902.229	38	904.005	17	909.015	23	912.0168
20	338.0204	132	375.503	55	902.230	38	904.006	17	909.016	23	912.0169
20	338.0205	133	375.504	54	902.231	38	904.007	16	909.017	23	912.017
20	338.0206	133	375.505	54	902.232	39	904.008	16	909.018	23	912.0170
11	338.0210	133	375.506	53	902.300	39	904.009	17	909.019	22	912.0171
11	338.0212	133	375.507	55	902.301	39	904.010	17	909.020	23	912.0172
20	338.0214	133	375.514	55	902.302	39	904.011	16	909.025	23	912.018
11	338.0219	132	375.515	53	902.400	38	904.020	16	909.028	23	912.019
11	338.0221	132	375.516	54	902.401	38	904.021	16	909.029	23	912.021
20	338.0227	133	375.517	54	902.402	38	904.022	17	909.033	23	912.022
11	338.0230	132	375.518	53	902.403	38	904.023	17	909.050	22	912.023
11	338.0231	133	375.519	53	902.404	38	904.024	16	909.058	23	912.024
46	339.1000	133	375.520	53	902.4048	38	904.025	16	909.065	23	912.025
46	339.1001	133	375.521	54	902.405	38	904.026	20	911.000	23	912.035
46	339.1002	133	375.523	53	902.406	38	904.027	20	911.001	22	912.037
46	339.1004	133	375.524	53	902.407	38	904.045	20	911.002	22	912.045
46	339.1005	61	375.529	53	902.408	39	904.900	20	911.003	7	913.000
46	339.1006	44	902.000	54	902.409	59	906.000	20	911.004	7	913.005
131	375.000	44	902.001	53	902.411	59	906.001	20	911.005	28	915.000
131	375.003	44	902.002	54	902.428	59	906.002	25	911.500	28	915.001
132	375.004	45	902.003	55	902.429	59	906.003	25	911.501	28	915.004
131	375.005	44	902.004	55	902.430	49	906.005	25	911.502	31	915.500
131	375.007	44	902.0048	54	902.431	60	906.005	25	911.503	31	915.501
131	375.016	44	902.0049	54	902.432	59	906.0055	21	911.900	31	915.502
131	375.017	44	902.005	53	902.500	59	906.0059	21	911.901	31	915.503
131	375.018	44	902.0050	55	902.501	59	906.0060	21	911.902	29	916.000
131	375.038	44	902.006	55	902.502	59	906.009	21	911.903	29	916.001
131	375.039	45	902.007	71	903.000	59	906.0113	21	911.904	29	916.002



Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.	Page	Art. no.
29	916.003	70	917.064	85	917.163	126	919.1100	135	930.031	33	931.900
29	916.0039	70	917.065	85	917.164	126	919.1101	135	930.032	61	940.024
29	916.004	70	917.066	86	917.165	126	919.2000	135	930.033	128	940.040
29	916.0040	71	917.067	91	917.166	126	919.2001	137	930.034	128	940.041
29	916.0041	71	917.068	91	917.167	126	919.2002	137	930.035	72	940.044
29	916.0042	81	917.069	70	917.168	126	919.2003	137	930.036	130	940.045
29	916.005	81	917.070	70	917.169	126	919.2004	137	930.044	130	940.046
29	916.010	80	917.071	88	917.182	126	919.2005	137	930.045	115	940.047
28	916.059	81	917.072	82	917.183	120	924.1016	135	930.049	128	940.047
28	916.060	80	917.073	47	918.001	122	924.1018	135	930.050	115	940.048
29	916.0601	81	917.074	21	918.002	122	924.1038	136	930.051	128	940.048
28	916.061	88	917.075	128	918.003	122	924.1039	137	930.054	130	940.049
29	916.0611	88	917.076	114	918.006	122	924.1040	137	930.057	128	940.052
28	916.062	81	917.077	128	918.006	121	924.1041	135	930.058	128	940.053
28	916.063	82	917.078	114	918.007	122	924.1046	135	930.059	72	940.057
29	916.082	83	917.081	128	918.007	120	924.4000	138	930.060	133	940.070
29	916.1129	84	917.083	114	918.008	120	924.4001	138	930.061	133	940.071
72	917.000	83	917.085	128	918.008	120	924.4002	138	930.062	133	940.073
72	917.001	84	917.088	115	918.009	121	924.4003	138	930.063	133	940.074
75	917.002	85	917.089	128	918.009	121	924.4004	138	930.064	72	940.083
74	917.003	84	917.090	130	918.010	121	924.4005	138	930.065	72	940.085
75	917.005	85	917.091	130	918.011	121	924.4006	136	930.090	128	940.089
74	917.006	90	917.093	130	918.012	120	924.4009	136	930.091	61	940.096
75	917.007	113	917.093	130	918.013	123	924.5000	136	930.092	61	940.097
75	917.008	87	917.094	130	918.014	123	924.5001	137	930.093	17	940.099
91	917.009	86	917.095	129	918.015	123	924.5002	137	930.094	129	940.104
91	917.010	86	917.096	129	918.016	123	924.5003	137	930.095	129	940.105
81	917.011	86	917.098	129	918.017	123	924.6000	137	930.096	61	940.108
89	917.012	86	917.099	129	918.018	121	924.700	137	930.097	72	940.112
88	917.018	87	917.100	129	918.019	14	925.0022	136	930.098		
88	917.019	86	917.101	129	918.020	14	925.0023	136	930.099		
82	917.021	87	917.102	130	918.021	14	925.0034	136	930.100		
84	917.022	87	917.110	130	918.022	14	925.0044	47	930.120		
85	917.023	91	917.111	114	918.023	14	925.0047	136	930.137		
86	917.024	89	917.112	130	918.024	14	925.0049	137	930.138		
83	917.026	89	917.113	61	918.025	14	925.100	137	930.139		
83	917.027	87	917.114	73	918.033	14	925.101	73	930.143		
83	917.028	89	917.116	128	918.033	15	925.500	137	930.160		
84	917.030	84	917.117	73	918.034	15	925.501	137	930.161		
89	917.031	73	917.120	128	918.034	15	925.800	137	930.162		
74	917.032	88	917.120	73	918.035	15	925.801	137	930.163		
74	917.033	90	917.127	73	918.040	35	928.003	137	930.164		
84	917.035	114	917.127	82	918.040	35	928.004	137	930.165		
85	917.036	80	917.134	74	918.045	35	928.005	136	930.166		
88	917.037	114	917.134	115	918.066	35	928.006	47	930.180		
74	917.038	90	917.135	128	918.066	35	928.900	47	930.182		
75	917.039	71	917.139	115	918.067	135	930.016	47	930.183		
91	917.040	71	917.140	128	918.067	135	930.017	139	930.900		
91	917.041	88	917.141	115	918.068	135	930.018	139	930.901		
80	917.045	82	917.143	128	918.068	135	930.019	139	930.902		
90	917.046	82	917.145	115	918.069	136	930.020	139	930.903		
90	917.047	80	917.150	128	918.069	136	930.021	139	930.904		
75	917.051	90	917.152	74	918.071	135	930.022	139	930.905		
75	917.052	75	917.153	74	918.072	135	930.023	139	930.906		
90	917.056	73	917.157	74	918.073	136	930.024	139	930.907		
112	917.056	85	917.157	74	918.074	136	930.025	139	930.908		
72	917.057	72	917.158	55	918.106	136	930.026	139	930.909		
49	917.060	72	917.159	55	918.107	136	930.027	139	930.910		
90	917.060	80	917.160	33	918.900	136	930.028	139	930.911		
72	917.061	83	917.161	35	918.900	136	930.029	33	931.000		
72	917.062	83	917.162	127	919.1000	135	930.030	33	931.001		



Bachmann GmbH & Co. KG

Ernstthaldenstr. 33 / 70565 Stuttgart / Germany

Telephone +49 711 866 02-0 / Fax +49 711 866 02-34

info@bachmann.com / www.bachmann.com